Project Name _____ **Qty** _____

Type _____ **Catalog / Part Number** _____



GL1960 - Medium Gallery II						
Shade	Straight Edge (S)	Flared Edge (F)	Bell Edge (B)	Round with Flared Rim (RF)	Round with Round Rim (RR)	Round with Square Rim (RS)
Diameter	17.9″	18″	19.5″	18.7″	18.4″	19.2″
Height	13.5″	12.6″	13.7″	14.8″	14.4″	14.1″

Certifications

cULus LISTED · IP66 · NightSky®

Mounting Configuration


Wall Mount


1 Arm Mount


2 Arm Mount @ 180°


2 Arm Mount @ 90°


3 Arms @ 120°


3 Arms @ 90°


4 Arms @ 90°


1Arm MidMount


2Arm MidMount @180


Stem Hung


Chain Hung


Catenary

Description

The GL1960 Gallery™ series is a medium scale, decorative pendant luminaire with a cast aluminum driver housing and spun aluminum shades. The housing and shades is available in a variety of shapes and styles for any application.
EPA: .50 (ft²) | WEIGHT: 28 LBS

Features

Mounting Configuration
1W: Wall Mount
1A: 1 Arm Mount
2A: 2 Arm Mount @ 180°
2A90: 2 Arm Mount @ 90°
3A: 3 Arms @ 120°
3A90: 3 Arms @ 90°
4A: 4 Arms @ 90°
1AM: 1Arm MidMount
2AM: 2Arm MidMount @180
SH44: Stem Hung
CH44: Chain Hung
CAT: Catenary

Luminaire
GL1960: Medium Gallery

Shade Style
S: Straight Edge
B: Bell Edge
RF: Round with Flared Rim
F: Flared Edge
RR: Round with Round Rim
RS: Round with Square Rim

Housing
BFR: Base Fixture Round
BFS: Base Fixture Stepped
GRR: Glow Rings Round
GRS: Glow Rings Stepped
SRR: Solid Rings Glow Top, Round
SRS: Solid Rings Glow Top, Stepped
GWR: Glow Window Round
GWS: Glow Window Stepped
BSR: Blank Top Solid Rings Round
BSS: Blank Top Solid Rings Stepped

Sternberg reserves the right to make changes to this product at any time without prior notice and such modification shall be effective immediately.
2026.10.22 Copyright © 2026 Sternberg

Finish


Black Textured


Urban Gun Metal Textured


Urban Gun Metal Matte


Urban Bronze Textured


Urban Bronze Matte


Urban Silver Textured


Urban Silver Matte


Urban White Textured


Urban White Matte


Custom Match

CCT - Color Temp (K)


2,700K



3,000K


3,500K


4,000K


5,000K

Distribution Type


Type 2


Type 3


Type 4


Type 5

Finish	**BKT:** Black Textured **UGMT:** Urban Gun Metal Textured **UGM:** Urban Gun Metal Matte **UBT:** Urban Bronze Textured **UB:** Urban Bronze Matte **USLT:** Urban Silver Textured **USL:** Urban Silver Matte **UWHT:** Urban White Textured **UWH:** Urban White Matte **CM:** Custom Match
Lens	**CA:** Clear Acrylic **SA:** Sag Acrylic **SV1:** Flat SoftVue™ Light Diffused Acrylic **SV2:** Flat SoftVue™ Moderate Diffused Acrylic **SV4:** Flat SoftVue™ Maximum Diffused Acrylic **SV1SA:** SoftVue™ Light Diffused Sag Acrylic **SV2SA:** SoftVue™ Moderate Diffused Sag Acrylic **SV4SA:** SoftVue™ Maximum Diffused Sag Acrylic
Hangstraight	**HSHB:** Standard Horizontal Hangstraight, Ball Finial **HSHS:** Standard Horizontal Hangstraight, Spike Finial **HSHN:** Standard Horizontal Hangstraight, No Finial **EZ:** Vertical Hangstraight, Large, "EZ" Mount
Optional Control Receptacle	**R7:** 7-Pin control receptacle only
Optional Control	**PE:** Twist-Lock Photocontrol (120V-277V) **PE4:** Twist-Lock Photocontrol (347V-480V) **SC:** Shorting Cap **PEC:** Electronic Button Photocontrol (120V-277V) **PEC4:** Electronic Button Photocontrol (480V)
Optional Fuse	**FHD:** Double Fuse and Holder
Optional House Side Shield	**BLOC:** Back Light Optical Control

Light Source

LED	**12L:** 12 LEDs **24L:** 24 LEDs	**16L:** 16 LEDs
CCT - Color Temp (K)	**27:** 2,700K **35:** 3,500K **50:** 5,000K	**30:** 3,000K **40:** 4,000K
Distribution Type	**T2:** Type 2 **T4:** Type 4	**T3:** Type 3 **T5:** Type 5
Driver	**MDL006:** 120V-277V, 60mA **MDL008:** 120V-277V, 80mA **MDL010:** 120V-277V, 100mA **MDL012:** 120V-277V, 120mA **MDL014:** 120V-277V,140mA	**MDH006:** 347V-480V, 60mA **MDH008:** 347V-480V, 80mA **MDH010:** 347V-480V,100mA **MDH012:** 347V-480V,120mA **MDH014:** 347V-480V,140mA

Important

Virtual Patent Marking Notice

This website (https://www.lmpg.com/patents-trademarks) is provided to satisfy the virtual patent marking provisions of applicable jurisdictions. Some products listed may be covered by additional patents not referenced here.

Sternberg reserves the right to make changes to this product at any time without prior notice and such modification shall be effective immediately.
2026.10.22 Copyright © 2026 Sternberg

How to Order

Mounting Configuration	Luminaire	Shade Style	Housing	LED	CCT - Color Temp (K)	Distribution Type	Driver	Lens	Hangstraight
1W Wall Mount **1A** 1 Arm Mount **2A** 2 Arm Mount @ 180° **2A90** 2 Arm Mount @ 90° **3A** 3 Arms @ 120° **3A90** 3 Arms @ 90° **4A** 4 Arms @ 90° **1AM** 1Arm MidMount **2AM** 2Arm MidMount @180 **SH44** Stem Hung **CH44** Chain Hung **CAT** Catenary [1]	**GL1960** Medium Gallery	**S** Straight Edge **F** Flared Edge **B** Bell Edge **RR** Round with Round Rim **RF** Round with Flared Rim **RS** Round with Square Rim	**BFR** Base Fixture Round **BFS** Base Fixture Stepped **GRR** Glow Rings Round **GRS** Glow Rings Stepped **SRR** Solid Rings Glow Top, Round **SRS** Solid Rings Glow Top, Stepped **GWR** Glow Window Round **GWS** Glow Window Stepped **BSR** Blank Top Solid Rings Round **BSS** Blank Top Solid Rings Stepped	**12L** 12 LEDs **16L** 16 LEDs **24L** 24 LEDs	**27** 2,700K **30** 3,000K **35** 3,500K **40** 4,000K **50** 5,000K	**T2** Type 2 **T3** Type 3 **T4** Type 4 **T5** Type 5	**MDL006** 120V-277V, 60mA [2] **MDH006** 347V-480V, 60mA [2] **MDL008** 120V-277V, 80mA [2] **MDH008** 347V-480V, 80mA [2] **MDL010** 120V-277V, 100mA [3] **MDH010** 347V-480V,100mA [3] **MDL012** 120V-277V, 120mA [4] **MDH012** 347V-480V,120mA [4] **MDL014** 120V-277V,140mA [3] **MDH014** 347V-480V,140mA [3]	**CA** Clear Acrylic **SA** Sag Acrylic **SV1** SoftVue™ Light Diffused **SV2** SoftVue™ Moderate Diffused **SV4** SoftVue™ Maximum Diffused **SV1SA** SoftVue™ Light Diffused Sag Acrylic **SV2SA** SoftVue™ Moderate Diffused Sag Acrylic **SV4SA** SoftVue™ Maximum Diffused Sag Acrylic	**HSHB** Standard Horizontal Hangstraight, Ball Finial **HSHS** Standard Horizontal Hangstraight, Spike Finial **HSHN** Standard Horizontal Hangstraight, No Finial **EZ** Vertical Hangstraight, Large, "EZ" Mount [5]

Notes:

1. Requires EZ hang-straight.
2. 12L system only.
3. 24L system only.
4. 12L or 16L system only.
5. Not for use with R7.

Sternberg reserves the right to make changes to this product at any time without prior notice and such modification shall be effective immediately.
2026.10.22 Copyright © 2026 Sternberg

How to Order

Optional Control Receptacle	Optional Control	Optional Fuse	Optional House Side Shield [8]	Finish
R7 7-Pin control receptacle only [6]	**PE** Twist-Lock Photocontrol (120V-277V) [7] **PE4** Twist-Lock Photocontrol (347V-480V) [7] **SC** Shorting Cap [7] **PEC** Button Photo Control (120V-277V) **PEC4** Button Photocontrol (480V)	**FHD** Double Fuse and Holder	**BLOC** Back Light Optical Control [9]	**BKT** Black Textured **UGMT** Urban Gun Metal Textured **UGM** Urban Gun Metal Matte **UBT** Urban Bronze Textured **UB** Urban Bronze Matte **USLT** Urban Silver Textured **USL** Urban Silver Matte **UWHT** Urban White Textured **UWH** Urban White Matte **CM** Custom Match

Notes:

6. Only available with HORIZONTAL hangstraight.
7. Requires control receptacle.
8. Not for use with T5 optic.
9. Only available with T2, T3 and T4.

Sternberg reserves the right to make changes to this product at any time without prior notice and such modification shall be effective immediately.
2026.10.22 Copyright © 2026 Sternberg

Specifications

Housing	The heavy wall permanent mold heat sink is constructed of low-copper aluminum 356 alloy for enhanced corrosion resistance and high tensile strength. The finned heat sink efficiently dissipates heat from the source and is covered with an spun aluminum shade.
LED Module	The field replaceable internal LED module comes factory sealed with an IP66 rating. The internal heat sink is sealed to the lens to protect the LED platform from the outside elements.
Recommended Arms	This luminaire pairs well with the variety of arms: **OD, ON, R2, OA, CA and CSA** An assortment of alternate arms are available to suit any application. Build your assembly in Genesis to review different arm styles.
Hang-Straight	A hang-straight transition is required for most hanging mounting configurations. The Standard **(HSHx)** is an aluminum ball and swivel horizontal hang-straight. Available with a spike **(S)**, a ball **(B)**, or no finial **(N)**. The hang-straight slips a **4" long by 2-3/8" OD** horizontal tenon. The **(EZ)** is a cast stainless steel ball and swivel vertical hang-straight. The special 2-part design allows for easy installation. It is factory installed under an arm and on the fixture.
Catenary Mount	The Catenary mount option includes a cast aluminum span wire clamp, which accommodates cables **1/4"-5/8"** in diameter. Below the clamp is a decorative cast aluminum wire box and cover which transitions to the **EZ** vertical Hangstraight for fixture attachment. **Aircraft Cable by others.**
Hardware	Includes Stainless steel hardware. Most finishes will include hardware with a Black Oxide conversion coating. Light finishes will get non-color coated hardware **(Whites and Silvers)**
Lens	Optional glare reducing SoftVue™ lens provides optimal visual comfort.
UL Listing	UL listed per UL1598 and CSA C22.2 No. 250.0 for the United States and Canada. Suitable for Wet Locations operating in an ambient temperature of up to 40°C (105°F)
Electronic Driver	The LED driver is UL recognized and will be securely mounted inside the fixture, for optimized performance and longevity. It will be supplied with a quick-disconnect electrical connector on the power supply, providing easy power connections for fixture installation and maintenance. It will have DC voltage output and be a constant current design. It runs at 50/60HZ and will have overload, overheat, and short circuit protection. It will be supplied with a supplemental line-ground, line-neutral and neutral-ground electrical surge protection in accordance with IEEE/ANSI C62.41.2 guidelines. It will be a high efficiency driver with a THD less than 20% and a high-power factor greater than .9. It will be dimming capable using a 0-10V signal, consult factory for more information.
NightSky® Friendly	Dark sky design properties with a U0 BUG rating for specific configurations.
IP Rating	IP66 rated luminaire for enhanced protection against dust and water intrusion.
Finish	Our 6 Stage Polyester Powder coat paint system offers a beautiful high-end finish that holds up to even the most extreme environments. Each part is inspected for quality and consistency before being released for shipment. Our system exceeds AAMA 2604, AAMA 2605, ASTM D523 and ASTM D4214 requirements.
Urban Finish	The Urban finish palette was created to highlight a modern, elegant aesthetic. All finishes are a 1 part powder coat with metallic flakes for a superior appearance. Finishes are available in textured or matte. Available finishes include: **Black Textured, Urban Gun Metal, Urban Bronze, Urban Silver and Urban White**
Custom Finish	Custom finishes are offered to adapt to any application. **Custom Match** option is available to blend sternberg product with the site, consult factory for more information.
Warranty	7-year limited warranty. See Website for Terms and Conditions.

Sternberg reserves the right to make changes to this product at any time without prior notice and such modification shall be effective immediately.
2026.10.22 Copyright © 2026 Sternberg

LEDs	The LEDs in this system will be fully shielded in a direct downward position to maximize efficiency. The LEDs are mounted to maximize thermal transfer to the heat sink surface. The LEDs shall be 100% recyclable; not contain lead, mercury or any other hazardous substances and shall be RoHS compliant. Lumen maintenance shall be determined in accordance with IESNA TM-21, based on LED manufacturer LM-80 test data of no less than 6,000 hours and in-situ testing of the luminaire by an NVLAP accredited Energy Efficient Lighting Products lab. The high-performance white LEDs will have a predicted lumen depreciation of approximately 100,000 hours with greater than 70% of initial output. The high brightness, high-output white LEDs shall be 4000K nominal (2700K, 3000K, 3500K or 5000K optional) correlated color temperature (CCT). Photometrics comply with LM79 testing standards. **CCT Lumen Derate Values from 4,000K (70+ CRI)** 2,700K (70+ CRI)=**.85** 3,000K (70+ CRI)=**.92** 3,500K (70+ CRI)=**1.00** 5,000K (70+ CRI)=**1.00** **Consult factory for custom correlated color temperature (CCT) or color rendering index (CRI).**
Optics	The luminaire shall be provided with individual, refractor type optics applied to each LED. The luminaire shall provide Type ___ (2, 3, 4 or 5) light distribution per the IESNA classifications. Testing shall be done in accordance with IESNA LM-79.
Backlight Optical Control	**BLOC Optic (BLOC):** An optional "Back Light Optical Control" shield can be provided at the factory. This is an internal optic level "House Side Shield" offering significantly reduced backlight and glare while maintaining the original design aesthetics of the luminaire. **External House Side Shield (HSS):** An optional external 120° House Side Shield helps control backlight. Spun aluminum panel painted to match fixture.
Photocontrols	**Button Photocell:** The photocontrol shall be mounted on the fixture and pre-wired to driver. The electronic button type photocontrol is instant on and will turn on at 1.5 footcandles and will turn off at 2-3 footcandles. See pole spec sheet for pole mounted version. **Twist-Lock Style (Hangstraight Mount):** The photocontrol shall be mounted externally on the hangstraight and pre-wired to driver. The twist lock type photocontrol is instant on with a 3-6 second turn off, and shall turn on at 1.5 footcandles with a turn-off at 2-3 footcandles. If an **R7** is specified alongside a **BALL** or **SPIKE** style finial on hang-straight, a decorative cap (with window) is included to cover a **STANDARD** photocell. Use the **NO FINIAL** hangstraight option if the **R7** is used with a **WIRELESS CONTROLLER** .

Lumen Chart(s)

Tested with CA lens

Model #	T2 DELIVERED LUMENS	BUG	EFFICACY (LPW)	T3 DELIVERED LUMENS	BUG	EFFICACY (LPW)	T4 DELIVERED LUMENS	BUG	EFFICACY (LPW)	T5 DELIVERED LUMENS	BUG	EFFICACY (LPW)	WATTAGE
24L-40-T_-MDL014	11595	B2U0G2	131.8	10900	B2U0G2	123.9	11160	B2U0G2	126.8	11530	B3U0G2	131.0	88
24L-30-T_-MDL014	10705	B2U0G2	121.6	10060	B2U0G2	114.3	10300	B2U0G2	117.0	10645	B3U0G2	121.0	88
24L-27-T_-MDL014	9810	B2U0G2	111.5	9225	B2U0G2	104.8	9445	B2U0G2	107.3	9755	B3U0G2	110.9	88
24L-40-T_-MDL010	8705	B2U0G2	140.4	8220	B2U0G2	132.6	8385	B2U0G2	135.2	8650	B3U0G1	139.5	62
24L-30-T_-MDL010	8035	B2U0G2	129.6	7590	B2U0G2	122.4	7740	B2U0G2	124.8	7985	B3U0G1	128.8	62
24L-27-T_-MDL010	7365	B2U0G2	118.8	6955	B2U0G2	112.2	7095	B2U0G2	114.4	7320	B3U0G1	118.1	62
16L-40-T_-MDL012	6895	B1U0G1	135.2	6465	B1U0G1	126.8	6660	B1U0G2	130.6	6880	B3U0G1	134.9	51
16L-30-T_-MDL012	6365	B1U0G1	124.8	5970	B1U0G1	117.1	6150	B1U0G2	120.6	6350	B3U0G1	124.5	51
16L-27-T_-MDL012	5835	B1U0G1	114.4	5470	B1U0G1	107.3	5635	B1U0G2	110.5	5820	B3U0G1	114.1	51
12L-40-T_-MDL012	5145	B1U0G1	131.9	4820	B1U0G1	123.6	4940	B1U0G1	126.7	5110	B2U0G1	131.0	39
12L-30-T_-MDL012	4750	B1U0G1	121.8	4450	B1U0G1	114.1	4560	B1U0G1	116.9	4715	B2U0G1	120.9	39
12L-27-T_-MDL012	4355	B1U0G1	111.7	4080	B1U0G1	104.6	4180	B1U0G1	107.2	4325	B2U0G1	110.9	39
12L-40-T_-MDL008	3630	B1U0G1	139.6	3405	B1U0G1	131.0	3500	B1U0G1	134.6	3615	B2U0G1	139.0	26
12L-30-T_-MDL008	3350	B1U0G1	128.8	3145	B1U0G1	121.0	3230	B1U0G1	124.2	3335	B2U0G1	128.3	26
12L-27-T_-MDL008	3070	B1U0G1	118.1	2880	B1U0G1	110.8	2960	B1U0G1	113.8	3060	B2U0G1	117.7	26
12L-40-T_-MDL006	2825	B1U0G1	141.3	2645	B1U0G1	132.3	2720	B1U0G1	136.0	2825	B1U0G0	141.3	20
12L-30-T_-MDL006	2610	B1U0G1	130.5	2440	B1U0G1	122.0	2510	B1U0G1	125.5	2610	B1U0G0	130.5	20
12L-27-T_-MDL006	2390	B1U0G1	119.5	2240	B1U0G1	112.0	2300	B1U0G1	115.0	2390	B1U0G0	119.5	20

Sternberg reserves the right to make changes to this product at any time without prior notice and such modification shall be effective immediately.
2026.10.22 Copyright © 2026 Sternberg

Hangstraight

Horizontal Hang-straights slip fit 4" long by 2-3/8" OD horizontal tenon



Standard Horizontal Hangstraight, Spike Finial **(HSHS)**



Standard Horizontal Hangstraight, Ball Finial **(HSHB)**



Standard Horizontal Hangstraight, No Finial **(HSHN)**



"EZ" Vertical hangstraight **(EZ)**

Housing | Upper Portion



Round Housing



Stepped Housing

Sternberg reserves the right to make changes to this product at any time without prior notice and such modification shall be effective immediately.
2026.10.22 Copyright © 2026 Sternberg

Stepped Housing with Straight Edge Shade



Base Fixture Stepped (**BFS)**



Glow Window Stepped **(GWS)**



Solid Rings Glow Top Stepped **(SRS)**



Glow Rings Stepped **(GRS)**



Blank Top Solid Rings Stepped **(BSS)**

Sternberg reserves the right to make changes to this product at any time without prior notice and such modification shall be effective immediately.
2026.10.22 Copyright © 2026 Sternberg

Round Housing with Straight Edge Shade



Base Fixture Round **(BFR)**



Glow Window Round **(GWR)**



Solid Rings Glow Top Round **(SRR)**



Glow Rings Round **(GRR)**



Blank Top Solid Rings Round **(BSR)**

Sternberg reserves the right to make changes to this product at any time without prior notice and such modification shall be effective immediately.
2026.10.22 Copyright © 2026 Sternberg

Shade Styles



Straight Edge **(S)**



Flared Edge **(F)**



Bell Edge **(B)**



Round with Round Rim **(RR)**



Round with Flared Rim **(RF)**



Round with Square Rim **(RS)**

Sternberg reserves the right to make changes to this product at any time without prior notice and such modification shall be effective immediately.
2026.10.22 Copyright © 2026 Sternberg

Options



Double Fuse Holder & (2) 3A Fuses **(FHD)**



Button Photocell **(PEC or PEC4)**



Back Light Optical Control **(BLOC)**



7-Pin NEMA Twist-Lock Receptacle **(R7)**



NEMA Receptacle Shorting Cap **(SC)**



NEMA Twist-Lock Photocell **(PE or PE4)**

Recommended Arms

An assortment of alternate arms are also available



(OD) Arm



(R2) Arm



(OA) Arm



(CA) Arm

Sternberg reserves the right to make changes to this product at any time without prior notice and such modification shall be effective immediately.
2026.10.22 Copyright © 2026 Sternberg