alphabet


PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

NU3

3" Round Variable Wall Wash Tunable White

NSF | AT airtight | DF dead-front | PR plenum rated | wet rated

WW BEAM (Note: Specifications are subject to change without notice)		
14mm COB PERFORMANCE DATA		
LED LIGHT ENGINE	NOMINAL DELIVERED LUMENS	SYSTEM WATTAGE
10LM	950LM @35K/95CRI	15W
15LM	1300LM @35K/95CRI	20W
Notes	Delivered lumens based on wall wash optic, (see page 2)	



FEATURES

- Light Uniformity from ceiling line (15') to floor with no scalloping
- Achieved through variable (In-field) light angle adjustment with Brightview lensing
- Placement of light intensity at any desired wall location
- Wide range of spacing flexible provides ability to navigate ceiling obstructions.

DIMMING AND CONTROLS

- eldoLED flicker free 0-10V dimming to 0%
- eldoLED flicker free DALI dimming to 0%
- DMX-512/RDM dim to 0%
- Wireless control options, dim to 1% (see page 12)

CONSTRUCTION

- Lexan™ (PC) highly resistant to impact and heat (240°F)
- Optimal material for wireless signal connectivity
- Shatter proof acrylic bezel lens
- Electrocoated 16-gauge cold-rolled steel construction
- Accommodates ceiling thickness from 1/8" to 1-1/4"
- Fixture is pre-set and shipped at 30deg tilt
- **CUTOUT DIMENSION:**
  Trimmed - 3-3/8"
  Millwork - 3-3/8"
  Trimless - 3-1/2"

LED

- Luminus tunable white COB: 95 CRI, R9 > 70: SDCM = 4-step MacAdam Ellipse; Lumen Maintenance: L_{70} > 54,000 hrs


LISTING


- ULus Listed to UL1598 & UL2108; cUL Listed to CSA C22.2 #250.0
- IP65 with lens - Suitable for wet locations with lens - Suitable for damp locations without lens
- Non-conductive, dead-front construction (Shower Approved)
- NSF/ANSI-2 with lens (Non-Food and Splash Zones)
- **Declare.** - LBC Red List Approved
- 5 Year Limited warranty

ELECTRICAL

- Power factor ≥ 0.9
- 2kV driver input surge protection
- Max. ambient installation temperature 95°F (35°C)


TRIM OPTIONS


Trimmed


Trimless


Trimless Millwork

BEAM SPREADS


71°

alphabet

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

ORDERING CODE

SERIES	**NU3**	NU3
TYPE	**RVW**	round variable wall wash
	RVWT	round variable wall wash trimless
	RVWTM	round variable wall wash trimless millwork
LED	**TW**	tunable white (Luminus)
DELIVERED LUMENS	**10LM**	950 lm
	15LM	1300 lm
	Standard Configuration: 3500K 90CRI **WW** Optic **Calculated Delivered Lumens** = [Delivered Lumen Value] x [CCT Multiplier] x [Optic Multiplier] x [Lens Multiplier]	
CCT	**1840**	1800K to 4000K tunable white
	2765	2700K to 6500K tunable white

CCT	1800K	2000K	2400K	2700K	3000K	3500K	4000K
CCT MULTIPLIER FOR LUMEN OUTPUT	0.74	0.76	0.83	0.88	0.96	1	1.09
EML RATIO	0.21	0.33	0.46	0.54	0.6	0.69	0.73

CCT	2700K	3000K	3500K	4000K	5000K	5700K	6500K
CCT MULTIPLIER FOR LUMEN OUTPUT	0.96	0.97	1	1.01	1.04	1.06	1.09
EML RATIO	0.52	0.62	0.76	0.83	0.96	1.02	1.07

CRI	**95**	95 typical, 90 minimum
OPTIC & LM MULTIPLIER	**WW**	wall wash with diffused angle bending lens
TRIM COLOR	**BK**	black
	WH	white
	MC	matte chrome
	BZ	bronze
	CC[1]	custom color, consult factory for details
	Antimicrobial finish, add **AM** to black, white or matte chrome i.e. BKAM.	
	Not applicable to trimless option. Do not include in trimless ordering code.	
BEZEL COLOR	**BK**	black
	WH	white
	MC	matte chrome
	BZ	bronze
	CC[1]	custom color, consult factory for details
	Antimicrobial finish, add **AM** to black, white or matte chrome i.e. BKAM.	

ORDERING CODE

MOUNTING OPTIONS	**NC**	new construction plate
	NC-F	new construction plate, fixed driver
	IC	insulation contact housing
	ICAT	insulation contact/airtight housing
	CP	chicago plenum housing
	RET	retrofit, no ceiling plate
VOLTAGE	**UNV**	120V-277V
	LVL[2,3]	low voltage luminaire
DIMMING	**DIM10Z**[4]	eldoLED flicker free 0-10V dim 0.1%
	DALIZ-DT6	flicker free DALI-2, DT6, dim to 0%
	DALIZ-DT8	flicker free DALI-2, DT8, dim to 0%
	DMX-RJ45	DMX control dimming to 0.1% with RJ45 connection
	DMXZ-RJ45	DMX-512/RDM dim to 0% with RJ45 input
	DMX-WL	DMX-512/RDM dim to 0% with lead wire input
	DMX-XLR	DMX-512/RDM dim to 0% with XLR input
	NLT	nLight control interface: Cat-5/RJ45, dim to off
	REMOTE DX COMPACT DRIVER (ref. page 11 for available options)	
	WIRELESS (ref. page 12 for available options)	

YOUR COMPLETED ORDERING CODE

Follow the steps to specify your fixture, example:

NU3 - RVW - TW - 10LM - 2765 - 95 - WW - WH - WH - NC - UNV - DIM10Z

NOTES


1. Custom set up fee plus minimum quantity required per color.
2. Available with NC or RET mounting options only
3. Must select DX dimming with LVL.
4. Requires 2 wall controllers (see wiring diagram).

*EldoLED uses logarithmic dimming curve as standard.
For linear dimming curve, add "LIN" after dimming code, i.e. DIM10LIN.

alphabet

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

PHOTOMETRIC DATA DIAGRAM



PHOTOMETRIC DATA CHARTS

FOOT CANDLE MEASUREMENT

TUNABLE WHITE WALL WASH 10LM-10° TILT 95CRI 3500K																		
MOUNTING DISTANCE	2' FROM WALL						3' FROM WALL						4' FROM WALL					
FIXTURE SPACING	2' ON CENTER		3' ON CENTER		4' ON CENTER		2' ON CENTER		3' ON CENTER		4' ON CENTER		3' ON CENTER		4' ON CENTER		6' ON CENTER	
DISTANCE FROM CEILING	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT
1'	9.1	8.7	6.8	5.3	6.4	2.8	0.6	0.6	0.5	0.4	0.5	0.1	0.1	0	0.1	0	0.1	0
2'	37.1	35.9	27.1	23.4	23.1	15.3	8.8	8.4	7	6.1	5.8	3.2	2.9	2.8	2.3	2.2	1.7	1.3
3'	40.1	39.6	29.3	27.2	23.7	19.4	16.5	15.9	13.1	11.9	10.3	6.8	7.9	7.7	6.3	6	4.7	3.8
4'	31.6	31.7	23.6	22.8	18.7	17.1	18.3	18	14.6	13.8	11	8.5	11.5	11.3	9.3	9	6.8	5.9
5'	22.9	23.1	17.6	17.4	14	13.4	16.8	16.6	13.5	13	9.9	8.4	12.7	12.5	10.3	10.1	7.5	6.8
6'	16.4	16.6	13	13	10.5	10.3	14.1	14.1	11.5	11.3	8.3	7.6	12.1	12.1	10	9.9	7.3	6.8
7'	11.8	12	9.7	9.7	7.9	7.9	11.4	11.5	9.5	9.4	6.9	6.5	10.8	10.8	9.1	9	6.7	6.4
8'	8.7	8.8	7.3	7.4	6.1	6.1	9.1	9.2	7.7	7.7	5.7	5.5	9.3	9.3	7.9	7.9	5.9	5.7
9'	6.5	6.6	5.6	5.7	4.7	4.8	7.3	7.4	6.2	6.3	4.7	4.6	7.8	7.9	6.8	6.8	5.1	5
10'	4.9	5	4.3	4.4	3.7	3.8	5.8	5.9	5.1	5.1	3.9	3.8	6.6	6.6	5.7	5.8	4.4	4.4

NOTE

1. Performance based on typical reflectance values and room dimensions. IES files available at ledrabrands.com

alphabet

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

PHOTOMETRIC DATA CHARTS

FOOT CANDLE MEASUREMENT

TUNABLE WHITE WALL WASH 10LM-20° TILT 95CRI 3500K																		
MOUNTING DISTANCE	2' FROM WALL						3' FROM WALL						4' FROM WALL					
FIXTURE SPACING	2' ON CENTER		3' ON CENTER		4' ON CENTER		2' ON CENTER		3' ON CENTER		4' ON CENTER		3' ON CENTER		4' ON CENTER		6' ON CENTER	
DISTANCE FROM CEILING	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT
1'	23.3	20.4	18.1	11.6	17.3	6.1	2.1	1.5	1.9	0.8	1.8	0.2	0.1	0.1	0.1	0	0.1	0
2'	62.3	58.9	45.9	37.6	39.9	24.1	18.9	17.1	15.3	12.2	13.1	6	7.3	6.9	5.8	5.1	4.5	2.9
3'	55.1	53.9	40.2	36.7	32.9	26	27.7	26.2	22.1	19.4	17.8	10.7	15.7	15.1	12.5	11.5	9.4	7
4'	38.7	38.6	28.8	27.6	22.9	20.5	26.6	25.8	21.2	19.6	16.2	11.9	19.4	18.9	15.6	14.7	11.5	9.4
5'	26	26.2	20	19.6	15.9	15.1	22	21.7	17.7	16.9	13	10.8	19	18.7	15.4	14.9	11.3	9.9
6'	17.6	17.9	14	13.9	11.2	11	17.2	17.2	14	13.7	10.2	9.1	16.7	16.6	13.8	13.5	10.1	9.2
7'	12.2	12.4	10	10	8.2	8.1	13.2	13.3	10.9	10.8	8	7.4	14	14	11.7	11.6	8.6	8.1
8'	8.7	8.8	7.3	7.4	6.1	6.1	10.1	10.2	8.5	8.5	6.3	6	11.4	11.4	9.7	9.7	7.2	6.9
9'	6.4	6.5	5.5	5.5	4.6	4.7	7.8	7.9	6.7	6.7	5	4.9	9.2	9.3	7.9	8	6	5.8
10'	4.8	4.8	4.2	4.2	3.6	3.6	6.1	6.2	5.3	5.4	4	4	7.5	7.5	6.5	6.6	5	4.9

TUNABLE WHITE WALL WASH 10LM-30° TILT 95CRI 3500K																		
MOUNTING DISTANCE	2' FROM WALL						3' FROM WALL						4' FROM WALL					
FIXTURE SPACING	2' ON CENTER		3' ON CENTER		4' ON CENTER		2' ON CENTER		3' ON CENTER		4' ON CENTER		3' ON CENTER		4' ON CENTER		6' ON CENTER	
DISTANCE FROM CEILING	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT
1'	35.6	31.5	28.4	17.4	27.3	8.4	4.3	3.3	4	1.9	3.9	0.5	0.3	0.3	0.3	0.2	0.3	0.1
2'	74.5	70.9	55.2	44.8	48.3	28	26	23.7	21.2	16.7	18.5	7.7	11.3	10.7	8.9	7.9	7.1	4.4
3'	58	57	42.3	38.6	34.6	27	33.1	31.5	26.4	23.2	21.5	12.5	20.8	20.1	16.6	15.3	12.6	9.1
4'	37.6	37.6	27.9	26.8	22.2	19.9	29.1	28.3	23.1	21.5	17.7	12.8	23.3	22.9	18.6	17.7	13.8	11.2
5'	24	24.2	18.3	18	14.5	13.8	22.5	22.3	18	17.3	13.3	11	21.2	21	17.2	16.6	12.5	10.9
6'	15.6	15.8	12.3	12.3	9.9	9.7	16.7	16.7	13.6	13.3	9.9	8.8	17.7	17.6	14.5	14.3	10.6	9.6
7'	10.5	10.7	8.6	8.6	7	6.9	12.4	12.4	10.2	10.1	7.4	6.9	14.1	14.2	11.8	11.7	8.6	8.1
8'	7.3	7.4	6.1	6.2	5.1	5.1	9.2	9.3	7.7	7.7	5.7	5.4	11.1	11.2	9.4	9.4	7	6.7
9'	5.3	5.3	4.5	4.6	3.8	3.8	6.9	7	5.9	6	4.4	4.3	8.7	8.8	7.5	7.5	5.6	5.5
10'	3.9	3.9	3.4	3.4	2.9	2.9	5.3	5.4	4.6	4.6	3.5	3.4	6.9	6.9	6	6	4.6	4.5

NOTE


1. Performance based on typical reflectance values and room dimensions. IES files available at ledrabrands.com

alphabet


PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

TRIM OPTIONS

TRIM/BEZEL COLORS




WH




MC



BK





BZ




CC

TRIMMED










ceiling cutout
3-3/8" diameter

ceiling thickness
1/8" to 1-1/4"

MILLWORK










ceiling cutout
3-3/8" diameter

ceiling thickness
1/8" to 1-1/4"

TRIMLESS







ceiling cutout
3-1/2" diameter

ceiling thickness
1/4" to 1-1/4"

In a continuing effort to offer the best product possible we reserve the right to change, without notice, specifications or materials that in our opinion will not alter the function of the product.


PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

MOUNTING OPTIONS


RATINGS / CERTIFICATIONS	NC	RET	IC	ICAT	CP
TYPE NON-IC	✔	✔			
TYPE IC			✔	✔	
CHICAGO PLENUM (CCEA)					✔
SUITABLE FOR AIR HANDLING PLENUMS	✔	✔	✔	✔	✔
REDUCED AIRFLOW (WITH LENS) ASTM E283	✔	✔	✔	✔	✔


MOUNTING TYPE	STANDARD CEILING THICKNESS	STANDARD CEILING CUTOUT
TRIM	1/8" to 1-5/8"	3-3/8"
TRIMLESS	1/8" to 1-5/8"	3-1/2"
MILLWORK (TRIMLESS)	1/8" to 1-5/8"	3-3/8"

PLENUM HEIGHT



NEW CONSTRUCTION - NC







ADDITIONAL MOUNTING INFO	
New Construction Bar Hangers (included)	Mounting Length: 14-3/4" to 26"
Extension Kit p/n: K20266 (ordered separately, 1 per fixture)	*Extends a pair of Bar Hangers* Total Mounting Length: 29" to 48"

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			


MOUNTING OPTIONS


10LM-15LM (DIM10Z / DALIZ-DT6 / DALIZ-DT8)
(BELOW CEILING ACCESSIBLE)





10LM-15LM (DIM10Z / DALIZ - DT6 / DALI - DT8) - FIXED
(ABOVE CEILING ACCESSIBLE)







PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			


MOUNTING OPTIONS

10LM-15LM (DMX-WL / DMX-XLR / DMX -RJ45)
(ABOVE CEILING ACCESSIBLE)






10LM-15LM (NLT)
(ABOVE CEILING ACCESSIBLE)





PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			


MOUNTING OPTIONS

IC - INSULATION CONTACT | ICAT - INSULATION CONTACT / AIR TIGHT | CP - CHICAGO PLENUM
(DIM10Z / DALIZ-DT6 / DALIZ-DT8)











BOX SIZE	L 1	L 2	W	H
A	15 - 7/16"	11 - 3/4"	8 - 1/2"	6 - 3/4"


BOX TYPE / LUMEN OUTPUT - WW BEAM									
LUMEN OUTPUT	BOX-A			BOX-B			BOX-C		
	CP	IC	ICAT	CP	IC	ICAT	CP	IC	ICAT
10LM	✔	✔	✔	✔	✔	✔	✔	✔	✔
15LM	✔	✔	✔	✔	✔	✔	✔	✔	✔

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

RETRO OPTIONS







NU3 SERIES - Goof Ring, Round

PRODUCT	ROUND CEILING HOLE CUTOUT RANGE[1]	GOOF RING SIZE	ORDERING CODE
NU3-RD NU3-RA NU3-RW	3.38" to 3.88"	OD = 6.0"	GF-3R-1-XX[2]
	3.89" to 4.5"		GF-3R-2-XX[3]
	4.51" to 5.0"		GF-3R-3-XX[3]
	5.01" to 5.5"	OD = 7.0"	GF-3R-4-XX[3]
	5.51" to 6.0"		GF-3R-5-XX[3]


1. Choose the appropriate range only if your ceiling cutout measurement falls within that range.
   Example: - If your ceiling cutout is 4.75" inches, choose the range 4.51" to 5.0".
   - If your ceiling cutout is 5.5" inches, choose the range 5.01" to 5.5".
2. Upper goof ring not included.
3. Upper goof ring included.

*XX - Indicates finish color. Only available in WH or BK. Complete ordering code by adding WH or BK to ordering code.
Example: GF-3R-1-WH
*Accommodates max ceiling thickness up to 1 1/4" for RD, RA and up to 5/8" for RW.

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			


PLENUM HEIGHT

(NC-LVL-DX) NEW CONSTRUCTION REMOTE DX DRIVER



NOMINAL LED VOLTAGE: 36VDC


Customer to order CC Remote Driver separately or POE Node by others.




REMOTE COMPACT DRIVER

REMOTE COMPACT DRIVER (DIMMING)

DX ORDERING OPTIONS	
DIM10Z-DX	remote compact eldoLED flicker free 0-10V dim 0.1% driver
DALIZ-DT6-DX	remote compact eldoLED flicker free DALI-2, DT6, dim to 0.1% driver
DALIZ-DT8-DX	remote compact eldoLED flicker free DALI-2, DT8, dim to 0.1% driver
DMX-RJ45-DX	remote compact DMX-512/RDM dim to 0% with RJ45 input driver






*Remote DX can power LEDs up to 330FT (18 AWG).
Customer will recieve a single remote compact driver per fixture.


PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

WIRELESS OPTIONS

NC - NEW CONSTRUCTION (10LM-15LM)
PLENUM SIDE




NC - NEW CONSTRUCTION (10LM-15LM)
DX REMOTE



Customer must verify system design and installation with their controls provider (e.g., Lutron). Wireless signal strength, reliability, performance, and commissioning are the responsibility of the customer. Remote DX can power LEDs up to 330FT (18 AWG), but adequate wireless signal is customers responsibility.

RET - RETRO 10LM - 15LM
PLENUM SIDE



YOUR COMPLETED ORDERING CODE
Follow the steps to specify your fixture, example:
NU3 - RVW - TW - 10LM - 2765 - 95 - WW - WH - WH - NC - UNV - DIM10Z - AWND
NU3 - RVW - TW - 10LM - 2765 - 95 - WW - WH - WH - NC - LVL - DIM10Z - AWND - DX

LUTRON Athena

ORDERING CODE

AWND . . . . . .athena wireless node (DALI2 Driver) - integrated / above ceiling

AWND-DX . .athena wireless node (DALI2 Driver) - remote DX Compact Driver



MODEL NUMBER

athena node model #: A-WN-D01-RF

POWER SUPPLY

(DALI2 Driver): Moons D4i DALI2 LED driver with DALI Bus Power, Dim-to-off

legrand WATTSTOPPER® PLUS

ORDERING CODE

CLMD . . . . . .connected lighting module (DALI2 Driver) - integrated / above ceiling

CLMD-DX. . .connected lighting module (DALI2 Driver) - remote DX Compact Driver



MODEL NUMBER

CLM model #: ZBHA-CLM-DIM

POWER SUPPLY

(DALI2 Driver): Moons D4i DALI2 LED driver with DALI Bus Power, Dim-to-off