alphabet


PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

NU1


1" Round Downlight Standard White

NSF · AT airtight · PR plenum rated · wet rated





Trim



Trimless



Trimless Millwork

22° - 60° BEAM (Note: Specifications are subject to change without notice)			
6mm COB PERFORMANCE DATA			
LED LIGHT ENGINE	**NOMINAL DELIVERED LUMENS**	**DRIVE CURRENT**	**LED WATTAGE**
07LM	690LM @30K/80CRI	150mA	5.5W
10LM	890LM @30K/80CRI	200mA	7.5W
15LM	1280LM @30K/80CRI	300mA	11W
07LM	590LM @30K/90CRI	150mA	5.5W
10LM	760LM @30K/90CRI	200mA	7.5W
15LM	1090LM @30K/90CRI	300mA	11W
Notes	Delivered lumens based on 60D optic with no lens, (see page 2)		

17° BEAM (Note: Specifications are subject to change without notice)			
4.2mm COB PERFORMANCE DATA			
LED LIGHT ENGINE	**NOMINAL DELIVERED LUMENS**	**DRIVE CURRENT**	**LED WATTAGE**
07LM	610LM @30K/80CRI	150mA	5.5W
07LM	520LM @30K/90CRI	150mA	5.5W
Notes	Delivered lumens based on 17D optic with SBL lens, (see page 2)		

FEATURES

- 3/8" bezel regress with 1/16" micro flange
- 17° - 60° optical beam control
- UGR < 19
- Up to 123 LPW
- Glare control, specialty optics, trim options, and custom finishes available
- Microban® antimicrobial finish available on all exposed painted surfaces

DIMMING AND CONTROLS

- eldoLED flicker free 0-10V dimming to 0% and 1%
- eldoLED flicker free DALI 2 dimming to 0% and 1%
- Lutron Hi-lume Eco System dimming to 0.1% and 1.%
- Leading & trailing edge (Triac/ELV) dimming to 1%
- All driver offerings are remote with above ceiling access, see page 3 for details.
- Refer to DX remote panels for additional options.

CONSTRUCTION

- High-grade die-cast and cold forged aluminum alloy assembly that has superior thermal and corrosion resistance properties.
- Shatter proof acrylic bezel lens
- Electrocoated 16-gauge cold-rolled steel construction
- Accommodates ceiling thickness from 1/8" to 1-1/2", On-field thick ceiling adjustment

LED

- 90 CRI: SDCM = 2-step MacAdam Ellipse, Lumen Maintenance: L_{70} > 66,000 hrs
- 80 CRI: SDCM = 2-step MacAdam Ellipse, Lumen Maintenance: L_{70} > 66,000 hrs

LISTING


- ULus Listed to UL1598 & UL2108; cUL Listed to CSA C22.2 #250.0
- IP65 with lens - Suitable for wet locations with lens - Suitable for damp locations without lens
- NSF/ANSI-2 with lens (Non-Food and Splash Zones)
- **Declare.** - LBC Red List Approved
- 5 Year Limited warranty

ELECTRICAL


- Low voltage luminaire: 36Vdc nominal
- 07LM - 150mA
- 10LM - 200mA
- 15LM - 300mA

FIXTURE HEIGHT - TRIMMED/TRIMLESS


LED LIGHT ENGINE: 07LM - 15LM




FIXTURE HEIGHT - MILLWORK




TRIMMED



TRIMLESS



MILLWORK



alphabet

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

ORDERING CODE

SERIES	**NU1**	NU1
TYPE	**RD**	round downlight
	RDT	round downlight trimless
	RDTMW	round downlight trimless millwork
LED	**SW**	standard white
DELIVERED LUMENS	**07LM**	690 lm
	10LM	890 lm
	15LM	1280 lm
	Standard Configuration: 3000K 80CRI 60D, **NL**	
	Calculated Delivered Lumens = [Delivered Lumen Value] x [CCT Multiplier] x [Optic Multiplier] x [Lens Multiplier]	
CCT	**27K**	2700K
	30K	3000K
	35K	3500K
	40K	4000K

CCT	2700K		3000K		3500K		4000K	
CRI	80+	90+	80+	90+	80+	90+	80+	90+
CCT MULTIPLIER FOR LUMEN OUTPUT	0.96	0.81	1.00	.85	1.03	.88	1.06	.91

CRI	**80**	80 CRI
	90	90 CRI
OPTIC & LM MULTIPLIER SEE PAGE 6	**17D**[1, 2, 3]	17 degrees (0.88)
	22D[2, 3]	22 degrees (0.91)
	30D	30 degrees (0.97)
	40D	40 degrees (0.95)
	60D	60 degrees (1.00)
BEZEL LENS SEE PAGE 5	**NL**[4]	no lens (1.00)
	CL	clear lens (0.95)
	DL	diffused lens (0.86)
	E[5]	elliptical beam spread (0.85)
	HCL	honeycomb louver (0.65)
	HET	high efficiency textured lens, similar to Solite™ (0.92)
	SBL	smoothing beam lens (0.92)
	Maximum 2pcs of media per fixture.	
TRIM COLOR SEE PAGE 5	**BK**	black
	WH	white
	MC	matte chrome
	BZ	bronze
	CC[6]	custom color, consult factory for details
	Antimicrobial finish, add **AM** to black, white or matte chrome i.e. BKAM.	
	Not applicable to trimless option. Do not include in trimless ordering code.	
BEZEL COLOR SEE PAGE 5	**BK**	black (0.98)
	WH	white (1.00)
	MC	matte chrome (0.99)
	BZ	bronze (0.98)
	CC[6]	custom color, consult factory for details
	Antimicrobial finish, add **AM** to black, white or matte chrome i.e. BKAM.	

ORDERING CODE

MOUNTING OPTIONS SEE PAGE 8, 9	**NC**	new construction plate
	NCINH[7]	new construction with ceiling fitting plate, IC rated, inherently protected
	IC[8, 9]	insulation contact housing
	ICAT[8, 9]	insulation contact/airtight housing
	CP[8, 9]	chicago plenum housing
	RET	retrofit, no ceiling plate
	RETINH[7]	retrofit, no ceiling fitting plate, IC rated, inherently protected
	remote driver only	
VOLTAGE	**LVL**	low voltage luminaire
DIMMING	**ND**	No driver included. See page 3 for remote driver options.

YOUR COMPLETED ORDERING CODE

Follow the steps to specify your fixture, example:

NU1 - RD - SW - 10LM - 35K - 90 - 30D - HET - WH - WH - NC - LVL - ND

NOTES

1. 17D available in 07LM.
2. 17D & 22D not available in NL and CL options.
3. 17D & 22D includes SBL lens as standard. One additional media may be used.
4. NL option does not meet requirements for AT/WET/NSF listings.
5. Elliptical lens not available with 17D optic options. Actual beam distributions [22D= 20° x 25° , 30D= 45° x 65° , 40D= 50° x 65° , 55D= 60° x 75°]
6. Custom set up fee plus minimum quantity required per color.
7. NCINH, RETINH available in 07LM.
8. IC/ICAT/CP not available in 15LM.
9. IC/ICAT/CP not available in RDTMW.

alphabet

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

REMOTE DRIVER - ORDERING CODE		
SERIES	DX-C	compact driver box
NUMBER OF DRIVERS	1-5	number of drivers, 1-5
CURRENT	150	150mA
	200	200mA
	300	300mA
VOLTAGE	120	120V
	UNV	120V-277V
DIMMING	DIM10	eldoLED flicker free 0-10V dim to 1%
	DIM10Z	eldoLED flicker free 0-10V dim 0.1%
	DALI	eldoLED flicker free DALI-2 dim to 1%
	DALIZ	eldoLED flicker free DALI-2 dim to 0.1%
	DMX-RJ45[1]	DMX control dimming to 0.1% with RJ45 connection
	DMX-WL[1]	DMX-512/RDM dim to 0% with lead wire input
	DMX-XLR[1]	DMX-512/RDM dim to 0% with XLR input
	LUT	Lutron Hi-lume Ecosystem dimming to 1%, Soft-on & Fade-to-Black
	LUTP	Lutron Hi-Lume Eco (fade) dim to 0.1%
	ELV1[2]	leading edge & trailing edge (Triac/ELV) dim to 1%
	NLT	nLight control interface: Cat-5/RJ45, dim to off
	CAS[3]	Casambi control with flicker free 1% dimming
	AWNR[4]	lutron athena wireless node
ELECTRICAL OPTIONS	EM7[5]	remote emergency battery backup, 90 minutes at 7 watts to LED, Remote TS

YOUR COMPLETED ORDERING CODE
Follow the steps to specify your fixture, example:
DX-C - 1 - 300 - UNV - DIM10 - EM7

NOTES

1. DMX available only in DX-C-1.
2. ELV available in 120V.
3. All drivers on single Casambi dimming circuit.
4. AWNR reference page 11 for product specification on Athena wireless node.
5. EM available only with DX-C-1. Box size same as DX-C-2, with one driver and one battery.

* EldoLED uses logarithmic dimming curve as standard. For linear dimming curve, add "LIN" after dimming code, i.e. DIM10LIN.

22° - 60° BEAM
(Note: Specifications are subject to change without notice)

6mm COB PERFORMANCE DATA

LED LIGHT ENGINE	NOMINAL DELIVERED LUMENS	SYSTEM WATTAGE
07LM	690LM @30K/80CRI	7W
10LM	890LM @30K/80CRI	9W
15LM	1280LM @30K/80CRI	14W
07LM	590LM @30K/90CRI	7W
10LM	760LM @30K/90CRI	9W
15LM	1090LM @30K/90CRI	14W
Notes	Delivered lumens based on 60D optic with no lens	

17° BEAM
(Note: Specifications are subject to change without notice)


4.2mm COB PERFORMANCE DATA

LED LIGHT ENGINE	NOMINAL DELIVERED LUMENS	SYSTEM WATTAGE
07LM	610LM @30K/80CRI	8W
07LM	520LM @30K/90CRI	8W
Notes	Delivered lumens based on 17D optic with SBL lens	


ELECTRICAL/CONTROLS

- 120V-277V, 120 only Triac / ELV
- Power factor ≥ 0.9
- 2kV driver input surge protection
- Remote emergency test switch
- 7W, 10W (T20 CEC) and 12W EM 90min battery
- Max. ambient installation temperature 95°F (35°C)
- Minimum wire gauge approved mounting distance 18 AWG, 330 feet
- Maximum Remote mounting distance of EM driver shall be 50 feet


REMOTE SINGLE DRIVER BOX



REMOTE 2 TO 3 DRIVER BOX (2 Drivers for DIM10Z/DALI/DALIZ/LUT/LUTP) (1 Driver + EM)



REMOTE 4 TO 5 DRIVER BOX (3 Drivers for DIM10Z/DALI/DALIZ/LUT/LUTP)




101188

In a continuing effort to offer the best product possible we reserve the right to change, without notice, specifications or materials that in our opinion will not alter the function of the product.


PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

DRIVER BOXES


REMOTE SINGLE DRIVER BOX



REMOTE 2 TO 3 DRIVER BOX (2 Drivers for DIM10Z/DALI/DALIZ/LUT/LUTP)



REMOTE 4 TO 5 DRIVER BOX (3 Drivers for DIM10Z/DALI/DALIZ/LUT/LUTP)



101188

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

TRIM OPTIONS

TRIM/BEZEL COLORS



WH



MC



BK



BZ

OPTICAL OPTIONS

- UGR calculation based on CIE 117-1995; room size: 4H X 8H, reflectance: 70/50/20;
- UGR calculation based on 15LM fixtures, unless otherwise noted.

HCL

Honeycomb Louver



OPTIC	BEAM ANGLE	UGR
17D	17	5
22D	20	8.2
30D	27	11.3
40D	35	13.8
60D	45	19.7

NL

No Lens



OPTIC	BEAM ANGLE	UGR
30D	29	15.7
40D	39	18.3
60D	56	24.8

CL

Clear Lens



OPTIC	BEAM ANGLE	UGR
30D	30	15
40D	40	18.1
60D	55	24.4

DL

Diffused Lens



OPTIC	BEAM ANGLE	UGR
22D	40	20.2
30D	45	21.6
40D	50	23.2
60D	62	26.1

HET

High Efficiency Textured Lens



OPTIC	BEAM ANGLE	UGR
17D	21	10.3
22D	25	15.7
30D	32	17.1
40D	41	19.4
60D	55	24.6

SBL

Smoothing Beam Lens



OPTIC	BEAM ANGLE	UGR
17D	18	8.4
22D	22	11.5
30D	31	16.2
40D	40	18.6
60D	55	24.3

E

Elliptical Lens



OPTIC	BEAM ANGLE	UGR
22D	57x38	24x19
30D	63x43	25x20
40D	66x48	26x22
60D	75x59	28x25


GLARE CONTROL

CUT-OFF ANGLE

Visual comfort is achieved with a lower cut-off angle due to improved glare control. The smaller the cut-off angle, the easier it is on the eye.

Alphabet downlights have been thoughtfully engineered to eliminate glare while still delivering functional illumination.

- Cutoff angle of NL and CL is 60 degrees;



alphabet

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			


PHOTOMETRIC DATA

07LM CCT MULTIPLIERS

	80CRI	90CRI
2700K	0.96	0.81
3000K	1	0.85
3500K	1.03	0.88
4000K	1.06	0.91

FC Formula = CBCP / Distance^2


22D 22° WITH SBL LENS



WATTS: 5.5	LPW: 105.2
LUMENS: 579	CCT: 3000K

INTENSITY	
DEGREE	CANDELA
0	2797
5	2432
15	788
25	213
35	37
45	17


30D 31° WITH NO LENS



WATTS: 5.5	LPW: 115.5
LUMENS: 635	CCT: 3000K

INTENSITY	
DEGREE	CANDELA
0	1772
5	1640
15	908
25	323
35	71
45	25


40D 40° WITH NO LENS



WATTS: 5.5	LPW: 110.7
LUMENS: 609	CCT: 3000K

INTENSITY	
DEGREE	CANDELA
0	1165
5	1126
15	817
25	361
35	94
45	33

60D 57° WITH NO LENS



WATTS: 5.5	LPW: 116.3
LUMENS: 639	CCT: 3000K


INTENSITY	
DEGREE	CANDELA
0	680
5	666
15	568
25	394
35	214
45	80

15LM CCT MULTIPLIERS

	80CRI	90CRI
2700K	0.96	0.81
3000K	1	0.85
3500K	1.03	0.88
4000K	1.06	0.91

FC Formula = CBCP / Distance^2


22D 22° WITH SBL LENS



WATTS: 11	LPW: 96.8
LUMENS: 1065	CCT: 3000K

INTENSITY	
DEGREE	CANDELA
0	5146
5	4474
15	1451
25	392
35	69
45	31


30D 31° WITH NO LENS



WATTS: 11	LPW: 106.2
LUMENS: 1169	CCT: 3000K

INTENSITY	
DEGREE	CANDELA
0	3261
5	3017
15	1671
25	594
35	130
45	46


40D 40° WITH NO LENS



WATTS: 11	LPW: 101.8
LUMENS: 1120	CCT: 3000K

INTENSITY	
DEGREE	CANDELA
0	2143
5	2072
15	1503
25	665
35	173
45	61

60D 57° WITH NO LENS



WATTS: 11	LPW: 107
LUMENS: 1176	CCT: 3000K


INTENSITY	
DEGREE	CANDELA
0	1251
5	1226
15	1045
25	726
35	393
45	148

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

PHOTOMETRIC DATA

07LM CCT MULTIPLIERS		
	80CRI	90CRI
2700K	0.96	0.81
3000K	1	0.85
3500K	1.03	0.88
4000K	1.06	0.91
FC Formula = CBCP / Distance^2		

17D
17° WITH SBL LENS




WATTS: 5.5	LPW: 109
LUMENS: 600	CCT: 3000K
INTENSITY	
DEGREE	CANDELA
0	4553
5	3627
15	780
25	119
35	21
45	7

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

MOUNTING OPTIONS

FIXTURE HEIGHT


07LM - 15 LM LOW LUMENS




TRIMMED, TRIMLESS & MILLWORK

NC - NEW CONSTRUCTION

TRIM




TRIM




ADDITIONAL MOUNTING INFO	
New Construction Bar Hangers (included)	Mounting Length: 14-3/4" to 26"
Extension Kit p/n: K20266 (ordered separately, 1 per fixture)	*Extends a pair of Bar Hangers* Total Mounting Length: 29" to 48"


TRIMLESS



TRIMLESS




TRIMLESS/MILLWORK




PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

MOUNTING OPTIONS

RET - RETRO
TRIM/TRIMLESS



IC - INSULATION CONTACT HOUSING
ICAT - INSULATION CONTACT / AIR TIGHT
CP - CHICAGO PLENUM




BOX SIZE	L 1	L 2	W	H
A	15 - 7/16"	11 - 3/4"	8 - 1/2"	6 - 3/4"

RATINGS / CERTIFICATIONS	NC	RET	RET	ICAT	CP	NCIC	RETIC
TYPE NON-IC	✔	✔					
TYPE IC			✔	✔	✔	✔	✔
CHICAGO PLENUM (CCEA)					✔		
SUITABLE FOR AIR HANDLING PLENUMS	✔	✔	✔	✔	✔	✔	✔
REDUCED AIRFLOW ASTM E283				✔	✔		

BOX TYPE / LUMEN OUTPUT - STANDARD BEAMS (14°-60°)			
LUMEN OUTPUT	BOX - A		
	CP	IC	ICAT
07LM	✔	✔	✔
10LM	✔	✔	✔
15LM			

CEILING THICKNESS			
FIXTURE TYPE	MOUNTING TYPE		
	NC, IC, ICAT, CP, RET	NC, IC, ICAT, CP, RET	NC, IC, ICAT, CP, RET
	STANDARD CEILING THICKNESS	THICK CEILING THICKNESS	CEILING CUTOUT
TRIM	1/8" to 1.0"	1.0" to 1 1/2"	1-3/4" round
TRIMLESS	1/8" to 1.0"	1.0" to 1 1/2"	1-3/4" round
MILLWORK (TRIMLESS)	1/8" to 1.0"	1.0" to 1 1/2"	1-7/16" round



1/8" to 1" thick ceiling

1" to 1-1/2" thick ceiling

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

BATTERY OPTIONS

EMERGENCY BATTERY

IOTA's ILB Battery Backups are UL Listed LED emergency drivers that allow the same LED fixture to be used for both normal and emergency operation. In the event of a power failure, the ILB switches to the emergency mode and operates the existing fixture for 90 minutes. The unit contains a battery, charger, and converter circuit in a single can. The Constant Power design of the ILB maintains the output wattage to the LED array even as the system voltage diminishes. UL 924 Listed for U.S. and Canada. UL 1310 Certified, Output Class 2 Compliant. Includes single-piece TBTS test switch and charge indicator accessory kit. For use with switched and unswitched fixtures, and includes Two-wire universal AC input. Meets or exceeds all National Electric Code and Life Safety Code Emergency Lighting Requirements. Rated for use in Plenum, Damp Location, Recessed Type IC, and Enclosed and Gasketed Luminares.

REMOTE TEST SWITCH


The Remote Test Switch may be mounted adjacent to the LED Fixture by others.

EMERGENCY BATTERY ACCESS

Above ceiling access is recommended for ease of service, but LED Fixture Sizes of 4" and Larger are capable of below ceiling access. IC/ICAT/CP Box and ITS option require an access panel in the ceiling (or other form of access) adjacent to the installation location of the Emergency Battery.

REMOTE LOCATION


Maximum remote mounting distance of the emergency driver shall be 50 feet. Remote location wiring provided by others. Follow all Local and National Electric/ Building Codes.



Remote Test Switch


EM MODE OUTPUT (DELIVERED LUMENS)	
LUMEN ORDERING CODE	EM7
ALL OPTIONS (07LM TO 13LM)	650
Notes: Based on 30K, 80CRI	

REMOTE EM BATTERY (REMOTE TEST SWITCH)



Accessory

76066 Optional T-Grid Mounting Kit[1]



1. Can be used with any of the Emergency Battery Backups. Must be ordered as a separate line item.

In a continuing effort to offer the best product possible we reserve the right to change, without notice, specifications or materials that in our opinion will not alter the function of the product.

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

AWNR OPTIONS

Athena Wireless Node

The Athena wireless node is a radio frequency (RF) device that enables simple, digital control of individual light fixtures in an Athena control system.



Athena Wireless Node RF

OEM ADVANTAGE LUTRON

AWNR

Plenum rated and can be installed above the ceiling for wireless control of a fixture without any impact on fixture aesthetics.

FEATURES

- Enables individual, wireless control of each fixture in an Athena control system. Accommodates zone and control changes without rewiring.
- Installed at factory – no wiring required on-site. Fixture is ready to communicate wirelessly once power is connected.
- All drivers on the link are controlled as a single zone.

REGULATORY APPROVALS

- cULus Listed (UL916)
- Complies with requirements for use in other spaces used for environmental air (plenums) per NEC® 2014 300.22(C)(3).
- FCC compliant with the limits for a Class B digital device.
- IC (Industry Canada)
- ANSI C137.1 0–10 V- Electronic Off

POWER / LOAD

- IEC SELV/NEC® Class 2
- 1 Watt

ENVIRONMENTAL

- Ambient operating temperature (immediate vicinity of Athena wireless node): **32 °F to 131 °F** (0 °C to 55 °C), 0% to 90% humidity.

BATTERY OPTIONS

- For EM options please consult factory.

Note: Default behavior prior to programming

- Light level 100%
- Athena wireless node performs an unprogrammed startup sequence on every power up until the device is added to an Athena system.
- Each Athena wireless node should be installed within 25 ft (7.62 m) of two or more Athena wireless nodes or other Clear Connect – Type X devices.
- For Chicago plenum installations, the Athena wireless node may not be installed in the plenum space. It must be installed in the occupied space.

For servicing the driver/j-box, access above ceiling is required. (NC Mounting)

IC/ICAT/CP not available in AWNR.