
alphabet

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

NU3

3" Round Wall Wash Tunable White

NSF · AT airtight · DF dead-front · PR plenum rated · wet rated



WW BEAM (Note: Specifications are subject to change without notice)		
14mm COB PERFORMANCE DATA		
LED LIGHT ENGINE	NOMINAL DELIVERED LUMENS	SYSTEM WATTAGE
10LM	1000LM @35K/95CRI	16W
Notes	Delivered lumens based on wall wash optic, (see page 2)	

FEATURES

- An asymmetric reflector with highly efficient BrightView angle bending lens produces excellent wall washing with no scalloping
- 3/4" bezel regress with 1/16" micro flange
- Custom finishes available
- Microban® antimicrobial finish available on all exposed painted surfaces

DIMMING AND CONTROLS

- eldoLED flicker free 0-10V dimming to 0%
- eldoLED flicker free DALI dimming to 0%
- DMX-512/RDM dim to 0%
- Wireless control options, dim to 1% (see page 11)

CONSTRUCTION

- Lexan™ (PC) highly resistant to impact and heat (240°F)
- Optimal material for wireless signal connectivity
- Shatter proof acrylic bezel lens
- Electrocoated 16-gauge cold-rolled steel construction
- Accommodates ceiling thickness from 1/8" to 5/8"
- **CUTOUT DIMENSION:**
  Trimmed - 3-3/8"
  Millwork - 3-3/8"
  Trimless - 3-1/2"

LED

- Luminus tunable white COB: 95 CRI, R9 > 70: SDCM = 4-step MacAdam Ellipse; Lumen Maintenance: L_{70} > 54,000 hrs


LISTING

- ULus Listed to UL1598 & UL2108; cUL Listed to CSA C22.2 #250.0
- IP65 with lens - Suitable for wet locations with lens - Suitable for damp locations without lens
- Non-conductive, dead-front construction (shower approved)
- NSF/ANSI-2 with lens (Non-Food and Splash Zones)
- **Declare.** - LBC Red List Approved
- 5 Year Limited warranty


ELECTRICAL

- Power factor ≥ 0.9
- 2kV driver input surge protection
- Max. ambient installation temperature 95°F (35°C)

TRIM OPTIONS



Trimmed




Trimless



Trimless Millwork

BEAM SPREADS



89˚

alphabet

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

ORDERING CODE

SERIES	**NU3**	NU3
TYPE	**RW**	round wall wash
	RWT	round wall wash trimless
	RWTMW	round wall wash trimless millwork
LED	**TW**	tunable white (Luminus)
DELIVERED LUMENS	**10LM**	1003 lm
	Standard Configuration: 3500K 95CRI **WW OPTIC**	
	Calculated Delivered Lumens = [Delivered Lumen Value] x [CCT Multiplier]	
CCT	**1840**	1800K to 4000K tunable white

CCT	1800K	2000K	2400K	2700K	3000K	3500K	4000K
CCT MULTIPLIER FOR LUMEN OUTPUT	0.74	0.76	0.83	0.88	0.96	1	1.09
EML RATIO	0.21	0.33	0.46	0.54	0.6	0.69	0.73

2765 — 2700K to 6500K tunable white

CCT	2700K	3000K	3500K	4000K	5000K	5700K	6500K
CCT MULTIPLIER FOR LUMEN OUTPUT	0.96	0.97	1	1.01	1.04	1.06	1.09
EML RATIO	0.52	0.62	0.76	0.83	0.96	1.02	1.07

CRI	**95**	95 typical, 90 minimum
OPTIC & LM MULTIPLIER	**WW**	wall wash with diffused angle bending lens
TRIM COLOR	**BK**	black
	WH	white
	MC	matte chrome
	BZ	bronze
	CC[1]	custom color, consult factory for details
	Antimicrobial finish, add **AM** to black, white or matte chrome i.e. BKAM.	
	Not applicable to trimless option. Do not include in trimless ordering code.	
BEZEL COLOR	**BK**	black (0.98)
	WH	white (1.00)
	MC	matte chrome (0.99)
	BZ	bronze (0.98)
	CC[1]	custom color, consult factory for details
	Antimicrobial finish, add **AM** to black, white or matte chrome i.e. BKAM.	

ORDERING CODE

MOUNTING OPTIONS	**NC**	new construction plate
	NC-F	new construction plate, fixed driver
	IC	insulation contact housing
	ICAT	insulation contact/airtight housing
	CP	chicago plenum housing
	RET	retrofit, no ceiling plate
VOLTAGE	**UNV**	120V-277V
	LVL[2,3]	low voltage luminaire
DIMMING	**DIM10Z**[4]	eldoLED flicker free 0-10V dim 0.1%
	DALIZ-DT6	flicker free DALI-2, DT6, dim to 0%
	DALIZ-DT8	flicker free DALI-2, DT8, dim to 0%
	DMX-RJ45	DMX control dimming to 0.1% with RJ45 connection
	DMXZ-RJ45	DMX-512/RDM dim to 0% with RJ45 input
	DMX-WL	DMX-512/RDM dim to 0% with lead wire input
	DMX-XLR	DMX-512/RDM dim to 0% with XLR input
	NLT	nLight control interface: Cat-5/RJ45, dim to off
	REMOTE DX COMPACT DRIVER (ref. page 10 for available options)	
	WIRELESS (ref. page 11 for available options)	

YOUR COMPLETED ORDERING CODE

Follow the steps to specify your fixture, example:

NU3 - RW - TW - 10LM - 2765 - 95 - WW - WH - WH - NC - UNV - DIM10Z

NOTES


1. Custom set up fee plus minimum quantity required per color.
2. Available with NC or RET mounting options only
3. Must select DX dimming with LVL.
4. Requires 2 wall controllers (see wiring diagram).

*EML = equivalent melanopic lux. To calculate EML, multiply the measured photopic lux by the EML ratio for the given CCT. Example: 254 lux x 0.79 = 200 melanopic lux at 4000K.

alphabet

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

PHOTOMETRIC DATA DIAGRAM




TUNABLE WHITE WALL WASH 10LM 95CRI 3500K																		
MOUNTING DISTANCE	2' FROM WALL						3' FROM WALL						4' FROM WALL					
FIXTURE SPACING	2' ON CENTER		3' ON CENTER		4' ON CENTER		2' ON CENTER		3' ON CENTER		4' ON CENTER		3' ON CENTER		4' ON CENTER		6' ON CENTER	
DISTANCE FROM CEILING	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT
1'	10.8	10.1	8.3	6.2	7.5	3.6	2.7	2.4	2.3	1.7	2	0.8	1.2	1.1	1	0.9	0.8	0.5
2'	37.5	37.7	25.9	25.9	21.6	17.2	8.3	8	6.7	5.9	5.6	3	3.4	3.3	2.7	2.5	2.1	1.5
3'	42.5	42.9	30.7	29.7	23.6	22.3	16.7	16.8	12.7	12.9	9.6	7.6	7.8	7.5	6.1	5.9	4.5	3.8
4'	34.7	35.4	26	25.7	20.4	19.4	19.4	19.2	15.1	14.8	10.6	10	11.9	11.8	9.4	9.4	6.5	6.5
5'	25.6	26.2	19.9	20.1	15.8	15.5	18	18.3	14.6	14.2	10.1	9.6	13.1	13.3	10.8	10.7	7.5	7.4
6'	18.4	18.8	14.7	15	11.9	12	15.4	15.7	12.6	12.7	9.1	8.6	12.7	13	10.6	10.7	7.7	7.4
7'	13.2	13.5	10.9	11.2	9	9.2	12.7	12.9	10.6	10.7	7.7	7.4	11.6	11.7	9.8	10	7.2	7
8'	9.7	9.9	8.2	8.4	6.9	7	10.2	10.4	8.7	8.8	6.4	6.3	10.1	10.2	8.7	8.8	6.5	6.4
9'	7.2	7.3	6.2	6.4	5.3	5.4	8.2	8.4	7.1	7.2	5.3	5.3	8.6	8.7	7.5	7.7	5.7	5.7
10'	5.4	5.5	4.8	4.9	4.2	4.3	6.6	6.7	5.7	5.9	4.4	4.5	7.3	7.4	6.4	6.5	5	5

alphabet

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			


TRIM OPTIONS


TRIM/BEZEL COLORS




WH MC BK BZ CC

TRIMMED










ceiling cutout
3-3/8" diameter

ceiling thickness
1/8" to 1-1/4"

MILLWORK










ceiling cutout
3-3/8" diameter

ceiling thickness
1/2" to 1-3/8"

TRIMLESS







ceiling cutout
3-1/2" diameter

ceiling thickness
3/8" to 1-3/8"


PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

MOUNTING OPTIONS


RATINGS / CERTIFICATIONS	NC	RET	IC	ICAT	CP
TYPE NON-IC	✔	✔			
TYPE IC			✔	✔	
CHICAGO PLENUM (CCEA)					✔
SUITABLE FOR AIR HANDLING PLENUMS	✔	✔	✔	✔	✔
REDUCED AIRFLOW (WITH LENS) ASTM E283	✔	✔	✔	✔	✔


MOUNTING TYPE	STANDARD CEILING THICKNESS	STANDARD CEILING CUTOUT
TRIM	1/8" to 1-1/4"	3-3/8"
TRIMLESS	3/8" to 1-3/8"	3-1/2"
MILLWORK (TRIMLESS)	1/2" to 1-3/8	3-3/8"

PLENUM HEIGHT



NEW CONSTRUCTION - NC







ADDITIONAL MOUNTING INFO	
New Construction Bar Hangers (included)	Mounting Length: 14-3/4" to 26"
Extension Kit p/n: K20266 (ordered separately, 1 per fixture)	*Extends a pair of Bar Hangers* Total Mounting Length: 29" to 48"

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			


MOUNTING OPTIONS


10LM (DIM10Z / DALIZ-DT6 / DALIZ-DT8)
(BELOW CEILING ACCESSIBLE)





10LM (DIM10Z / DALIZ - DT6 / DALI - DT8) - FIXED
(ABOVE CEILING ACCESS REQUIRED)






In a continuing effort to offer the best product possible we reserve the right to change, without notice, specifications or materials that in our opinion will not alter the function of the product.


PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

MOUNTING OPTIONS

10LM (DMX-WL / DMX-XLR / DMX -RJ45)


(ABOVE CEILING ACCESS REQUIRED)





10LM (NLT)


(ABOVE CEILING ACCESS REQUIRED)





PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			


MOUNTING OPTIONS

IC - INSULATION CONTACT | ICAT - INSULATION CONTACT / AIR TIGHT | CP - CHICAGO PLENUM
(DIM10Z / DALIZ-DT6 / DALIZ-DT8)











BOX SIZE	L 1	L 2	W	H
A	15 - 7/16"	11 - 3/4"	8 - 1/2"	6 - 3/4"


BOX TYPE / LUMEN OUTPUT - WW BEAM			
LUMEN OUTPUT	BOX-A		
	CP	IC	ICAT
10LM	✔	✔	✔

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

RETRO OPTIONS







NU3 SERIES - Goof Ring, Round

PRODUCT	ROUND CEILING HOLE CUTOUT RANGE[1]	GOOF RING SIZE	ORDERING CODE
NU3-RD NU3-RA NU3-RW	3.38" to 3.88"	OD = 6.0"	GF-3R-1-XX[2]
	3.89" to 4.5"		GF-3R-2-XX[3]
	4.51" to 5.0"		GF-3R-3-XX[3]
	5.01" to 5.5"	OD = 7.0"	GF-3R-4-XX[3]
	5.51" to 6.0"		GF-3R-5-XX[3]

1. Choose the appropriate range only if your ceiling cutout measurement falls within that range.
   Example: - If your ceiling cutout is 4.75" inches, choose the range 4.51" to 5.0".
   - If your ceiling cutout is 5.5" inches, choose the range 5.01" to 5.5".
2. Upper goof ring not included.
3. Upper goof ring included.

*XX - Indicates finish color. Only available in WH or BK. Complete ordering code by adding WH or BK to ordering code.
Example: GF-3R-1-WH


*Accommodates max ceiling thickness up to 1 1/4" for RD, RA and up to 5/8" for RW.


PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

REMOTE COMPACT DRIVER

REMOTE COMPACT DRIVER (DIMMING)

DX ORDERING OPTIONS	
DIM10Z-DX	remote compact eldoLED flicker free 0-10V dim 0.1% driver
DALIZ-DT6-DX	remote compact eldoLED flicker free DALI-2, DT6, dim to 0.1% driver
DALIZ-DT8-DX	remote compact eldoLED flicker free DALI-2, DT8, dim to 0.1% driver
DMX-RJ45-DX	remote compact DMX-512/RDM dim to 0% with RJ45 input driver






*Remote DX can power LEDs up to 330FT (18 AWG).
Customer will recieve a single remote compact driver per fixture.


PLENUM HEIGHT

(NC-LVL-DX) NEW CONSTRUCTION REMOTE DX DRIVER



NOMINAL LED VOLTAGE: 36VDC


Customer to order CC Remote Driver separately or POE Node by others.




PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

WIRELESS OPTIONS

NC - NEW CONSTRUCTION (10LM)
PLENUM SIDE




NC - NEW CONSTRUCTION (10LM)
DX REMOTE



Customer must verify system design and installation with their controls provider (e.g., Lutron). Wireless signal strength, reliability, performance, and commissioning are the responsibility of the customer. Remote DX can power LEDs up to 330FT (18 AWG), but adequate wireless signal is customers responsibility.

YOUR COMPLETED ORDERING CODE
Follow the steps to specify your fixture, example:
NU3 - RW - TW - 10LM - 2765 - 95 - WW - WH - WH - NC - UNV - DIM10Z - AWND
NU3 - RW - TW - 10LM - 2765 - 95 - WW - WH - WH - NC - LVL - DIM10Z - AWND - DX

RET - RETRO 10LM
PLENUM SIDE



LUTRON Athena

ORDERING CODE

AWND.....athena wireless node (DALI2 Driver) - integrated / above ceiling

AWND-DX..athena wireless node (DALI2 Driver) - remote DX Compact Driver



MODEL NUMBER

athena node model #: A-WN-D01-RF

POWER SUPPLY

(DALI2 Driver): Moons D4i DALI2 LED driver with DALI Bus Power, Dim-to-off

legrand WATTSTOPPER® PLUS

ORDERING CODE

CLMD .....connected lighting module (DALI2 Driver) - integrated / above ceiling

CLMD-DX...connected lighting module (DALI2 Driver) - remote DX Compact Driver



MODEL NUMBER

CLM model #: ZBHA-CLM-DIM

POWER SUPPLY

(DALI2 Driver): Moons D4i DALI2 LED driver with DALI Bus Power, Dim-to-off