
alphabet

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

NU4

4" Round Wall Wash Tunable White

NSF AT airtight DF dead-front PR plenum rated wet rated



WW BEAM (Note: Specifications are subject to change without notice)		
14mm COB PERFORMANCE DATA		
LED LIGHT ENGINE	NOMINAL DELIVERED LUMENS	SYSTEM WATTAGE
10LM	980LM @35K/95CRI	17W
15LM	1460LM @35K/95CRI	25W
20LM	1830LM @35K/95CRI	31W
Notes	Delivered lumens based on wall wash optic, (see page 2)	

FEATURES

- An asymmetric reflector with highly efficient BrightView angle bending lens produces excellent wall washing with no scalloping
- 3/4" bezel regress with 1/16" micro flange
- UGR <18
- Custom finishes available
- Microban® antimicrobial finish available on all exposed painted surfaces

DIMMING AND CONTROLS

- eldoLED flicker free 0-10V dimming to 0% and 1%
- eldoLED flicker free DALI dimming to 0% and 1%
- DMX-512/RDM dim to 0%
- Wireless control options, dim to 1% (see page 10)

CONSTRUCTION

- Lexan™ (PC) highly resistant to impact and heat (240°F)
- Optimal material for wireless signal connectivity
- Shatter proof acrylic bezel lens
- Electrocoated 16-gauge cold-rolled steel construction
- Accommodates ceiling thickness from 1/8" to 1-1/4"

LED

- Luminus tunable white COB: 95 CRI, R9 > 70: SDCM = 3-step MacAdam Ellipse; Lumen Maintenance: L_{70} > 54,000 hrs


LISTING

- ULus Listed to UL1598 & UL2108; cUL Listed to CSA C22.2 #250.0
- IP65 with lens - Suitable for wet locations with lens - Suitable for damp locations without lens
- Non-conductive, dead-front construction (shower approved)
- NSF/ANSI-2 with lens (Non-Food and Splash Zones)
- **Declare.** - LBC Red List Approved
- 5 Year Limited warranty


ELECTRICAL

- Power factor ≥ 0.9
- 2kV driver input surge protection
- Max. ambient installation temperature 95°F (35°C)

TRIM OPTIONS



Trimmed




Trimless



Trimless Millwork

BEAM SPREADS



100˚

alphabet

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

ORDERING CODE		
SERIES	NU4	NU4
TYPE	RW	round wall wash
	RWT	round wall wash trimless
	RWTMW	round wall wash trimless millwork
LED	TW	tunable white (Luminus)
DELIVERED LUMENS	10LM	980 lm
	15LM	1460 lm
	20LM	1830 lm
	Standard Configuration: 3500K 95CRI **WW**	
	Calculated Delivered Lumens = [Delivered Lumen Value] x [CCT Multiplier]	
CCT	1840	1800K to 4000K tunable white
	2765	2700K to 6500K tunable white
CRI	95	95 typical, 90 minimum
OPTIC & LM MULTIPLIER	WW	wall wash with diffused angle bending lens
TRIM COLOR	BK	black
	WH	white
	MC	matte chrome
	BZ	bronze
	CC[1]	custom color, consult factory for details
	Antimicrobial finish, add **AM** to black, white or matte chrome i.e. BKAM.	
	Not applicable to trimless option. Do not include in trimless ordering code.	
BEZEL COLOR	BK	black (0.98)
	WH	white (1.00)
	MC	matte chrome (0.99)
	BZ	bronze (0.98)
	CC[1]	custom color, consult factory for details
	Antimicrobial finish, add **AM** to black, white or matte chrome i.e. BKAM.	

1840

CCT	1800K	2000K	2400K	2700K	3000K	3500K	4000K
CCT MULTIPLIER FOR LUMEN OUTPUT	0.67	0.74	0.8	0.85	0.88	0.95	1.01
EML RATIO	0.21	0.33	0.46	0.53	0.59	0.67	0.73

2765

CCT	2700K	3000K	3500K	4000K	5000K	5700K	6500K
CCT MULTIPLIER FOR LUMEN OUTPUT	0.91	0.98	1.00	0.99	1.00	1.01	1.02
EML RATIO	0.49	0.57	0.68	0.79	0.96	1.04	1.12

ORDERING CODE		
MOUNTING OPTIONS	NC	new construction plate
	IC[2]	insulation contact housing
	ICAT[2]	insulation contact/airtight housing
	CP[2]	chicago plenum housing
VOLTAGE	UNV	120V-277V
	LVL[3,4]	low voltage luminaire
DIMMING	DIM10Z[5]	eldoLED flicker free 0-10V dim 0.1%
	DALIZ-DT6	eldoLED flicker free DALI-2, DT6, dim to 0.1%
	DALIZ-DT8	eldoLED flicker free DALI-2, DT8, dim to 0.1%
	DMXZ-RJ45	DMX-512/RDM dim to 0% with RJ45 input
	DMX-WL	DMX-512/RDM dim to 0% with lead wire input
	DMX-XLR	DMX-512/RDM dim to 0% with XLR input
	NLT	nLight control interface: Cat-5/RJ45, dim to off
	WIRELESS (ref. page 10 for available options)	
	REMOTE DX COMPACT DRIVER (ref. page 9 for available options)	

YOUR COMPLETED ORDERING CODE
Follow the steps to specify your fixture, example:
NU4 - RW - TW - 10LM - 2765 - 95 - WW - WH - WH -NC-UNV-DIM10Z

NOTES

1. Custom set up fee plus minimum quantity required per color.
2. IC/ICAT/CP not available in 20LM.
3. Available with NC mounting option only.
4. Must select DX dimming with LVL.
5. Requires 2 wall controllers.


* EML = equivalent melanopic lux. To calculate EML, multiply the measured photopic lux by the EML ratio for the given CCT. Example: 254 lux x 0.79 = 200 melanopic lux at 4000K.

* EldoLED uses logarithmic dimming curve as standard. For linear dimming curve, add "LIN" after dimming code, i.e. DIM10LIN.

alphabet

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

PHOTOMETRIC DATA DIAGRAM



PHOTOMETRIC DATA CHARTS

FOOT CANDLE MEASUREMENT

TUNABLE WHITE WALL WASH 20LM 95CRI 3500K																		
MOUNTING DISTANCE	2' FROM WALL						3' FROM WALL						4' FROM WALL					
FIXTURE SPACING	2' ON CENTER		3' ON CENTER		4' ON CENTER		2' ON CENTER		3' ON CENTER		4' ON CENTER		3' ON CENTER		4' ON CENTER		6' ON CENTER	
DISTANCE FROM CEILING	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT
1'	37.3	33.8	31.4	17.6	29.4	9	7.8	7.1	6.4	5.1	5.4	2.7	3.3	3	2.8	2.4	2.5	1.9
2'	128.9	131.9	89.1	87.5	77.3	54.2	34.7	34.4	28.5	24.5	26.1	9.3	9.3	8.5	8.3	6.2	7.9	4.4
3'	104.2	105.7	72.7	73.6	56.9	54	57.3	58.6	43.4	45	34.4	24.1	24.5	24.5	20.1	19.6	18.3	14.8
4'	64.6	66.2	47.5	48.4	36.8	36.9	52.6	52.9	40.1	41.3	28.7	26.2	32.2	33	25.8	26.9	22.3	21.9
5'	39.6	40.6	30.6	31.4	24.1	24.6	39.8	40.7	31.5	32.1	21.9	21.3	31	31.2	24.9	25.7	21.1	21.5
6'	25.2	25.8	20.4	20.9	16.4	16.9	28.7	29.4	23.2	23.9	16.3	16.4	26.1	26.4	21.5	21.9	18.2	18.4
7'	16.8	17.2	14.1	14.4	11.7	12	20.7	21.2	17.2	17.6	12.3	12.5	20.7	21.2	17.3	17.7	14.8	15
8'	11.6	11.9	10	10.3	8.5	8.8	15.1	15.5	12.8	13.2	9.4	9.6	16.1	16.5	13.7	14.1	11.9	12.1
9'	8.3	8.5	7.4	7.6	6.4	6.6	11.2	11.5	9.7	10	7.3	7.5	12.6	12.9	10.9	11.2	9.5	9.7
10'	6.2	6.2	5.5	5.7	4.9	5	8.5	8.7	7.5	7.7	5.8	6	9.9	10.2	8.7	8.9	7.6	7.8

NOTE

1. Performance based on typical reflectance values and room dimensions. IES files available at ledrabrands.com

alphabet

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

PHOTOMETRIC DATA CHARTS

FOOT CANDLE MEASUREMENT

TUNABLE WHITE WALL WASH 15LM 95CRI 3500K																		
MOUNTING DISTANCE	2' FROM WALL						3' FROM WALL						4' FROM WALL					
FIXTURE SPACING	2' ON CENTER		3' ON CENTER		4' ON CENTER		2' ON CENTER		3' ON CENTER		4' ON CENTER		3' ON CENTER		4' ON CENTER		6' ON CENTER	
DISTANCE FROM CEILING	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT
1'	29.8	27.1	25.1	14.1	23.5	7.2	6.2	5.7	5.1	4.1	4.3	2.1	2.6	2.4	2.2	2	2	1.5
2'	103.1	105.6	71.3	70	61.9	43.4	27.8	27.5	22.8	19.6	20.9	7.4	7.5	6.8	6.7	5	6.3	3.5
3'	83.4	84.5	58.1	58.9	45.5	43.2	45.8	46.9	34.7	36	27.5	19.3	19.6	19.6	16.1	15.7	14.6	11.9
4'	51.7	52.9	38	38.7	29.4	29.5	42.1	42.3	32.1	33	23	21	25.8	26.4	20.7	21.5	17.8	17.5
5'	31.7	32.5	24.5	25.1	19.3	19.7	31.9	32.5	25.2	25.7	17.6	17.1	24.8	24.9	20	20.6	16.8	17.2
6'	20.2	20.7	16.3	16.7	13.2	13.5	23	23.5	18.6	19.1	13.1	13.1	20.8	21.1	17.2	17.5	14.5	14.7
7'	13.4	13.7	11.3	11.5	9.3	9.6	16.5	16.9	13.7	14.1	9.8	10	16.5	16.9	13.9	14.2	11.9	12
8'	9.3	9.5	8	8.2	6.8	7	12.1	12.4	10.3	10.5	7.5	7.7	12.9	13.2	11	11.3	9.5	9.7
9'	6.7	6.8	5.9	6	5.1	5.3	9	9.2	7.8	8	5.8	6	10.1	10.3	8.7	9	7.6	7.8
10'	4.9	5	4.4	4.5	3.9	4	6.8	7	6	6.2	4.6	4.8	7.9	8.1	7	7.1	6.1	6.3

TUNABLE WHITE WALL WASH 10LM 95CRI 3500K																		
MOUNTING DISTANCE	2' FROM WALL						3' FROM WALL						4' FROM WALL					
FIXTURE SPACING	2' ON CENTER		3' ON CENTER		4' ON CENTER		2' ON CENTER		3' ON CENTER		4' ON CENTER		3' ON CENTER		4' ON CENTER		6' ON CENTER	
DISTANCE FROM CEILING	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT	CENTER	MID POINT
1'	19.9	18.1	16.8	9.4	15.7	4.8	4.2	3.8	3.4	2.7	2.9	1.4	1.8	1.6	1.5	1.3	1.3	1
2'	68.8	70.4	47.6	46.7	41.3	28.9	18.5	18.4	15.2	13.1	13.9	4.9	5	4.5	4.4	3.3	4.2	2.3
3'	55.6	56.4	38.8	39.3	30.3	28.8	30.6	31.3	23.2	24	18.3	12.9	13.1	13.1	10.7	10.5	9.8	7.9
4'	34.5	35.3	25.3	25.8	19.6	19.7	28.1	28.2	21.4	22	15.3	14	17.2	17.6	13.8	14.4	11.9	11.7
5'	21.1	21.7	16.3	16.8	12.9	13.1	21.3	21.7	16.8	17.1	11.7	11.4	16.6	16.6	13.3	13.7	11.2	11.5
6'	13.5	13.8	10.9	11.2	8.8	9	15.3	15.7	12.4	12.7	8.7	8.7	13.9	14.1	11.5	11.7	9.7	9.8
7'	9	9.2	7.5	7.7	6.2	6.4	11	11.3	9.2	9.4	6.6	6.7	11	11.3	9.2	9.5	7.9	8
8'	6.2	6.3	5.4	5.5	4.6	4.7	8	8.2	6.8	7	5	5.1	8.6	8.8	7.3	7.5	6.3	6.5
9'	4.5	4.5	3.9	4	3.4	3.5	6	6.1	5.2	5.3	3.9	4	6.7	6.9	5.8	6	5.1	5.2
10'	3.3	3.3	3	3	2.6	2.7	4.5	4.6	4	4.1	3.1	3.2	5.3	5.4	4.6	4.8	4.1	4.2


NOTE

1. Performance based on typical reflectance values and room dimensions. IES files available at ledrabrands.com

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			


TRIM OPTIONS


TRIM/BEZEL COLORS




WH MC BK BZ CC

TRIMMED










ceiling cutout
4-3/8" diameter
ceiling thickness
1/8" to 1-1/4"

MILLWORK










ceiling cutout
4-3/8" diameter
ceiling thickness
1/2" to 1-1/4"

TRIMLESS







ceiling cutout
4-1/2" diameter
ceiling thickness
3/8" to 1-1/4"

alphabet


PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

MOUNTING OPTIONS


RATINGS / CERTIFICATIONS	NC	RET	IC	ICAT	CP
TYPE NON-IC	✔	✔			
TYPE IC			✔	✔	
CHICAGO PLENUM (CCEA)					✔
SUITABLE FOR AIR HANDLING PLENUMS	✔	✔	✔	✔	✔
REDUCED AIRFLOW (WITH LENS) ASTM E283	✔	✔	✔	✔	✔


MOUNTING TYPE	STANDARD CEILING THICKNESS	STANDARD CEILING THICKNESS
TRIM	1/8" to 1-5/8"	4-1/2"
TRIMLESS	1/8" to 1-5/8"	4-1/2"
MILLWORK (TRIMLESS)	1/8" to 1-5/8"	4-3/8"

PLENUM HEIGHT



NEW CONSTRUCTION - NC







ADDITIONAL MOUNTING INFO	
New Construction Bar Hangers (included)	Mounting Length: 14-3/4" to 26"
Extension Kit p/n: K20266 (ordered separately, 1 per fixture)	*Extends a pair of Bar Hangers* Total Mounting Length: 29" to 48"

PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			


MOUNTING OPTIONS


10LM-20LM (DIM10Z / DALIZ-DT6 / DALIZ-DT8)
(BELOW CEILING ACCESSIBLE)






10LM-20LM (DMXZ)
(BELOW CEILING ACCESSIBLE)





10LM-20LM NLT HOUSING - (NLT)





In a continuing effort to offer the best product possible we reserve the right to change, without notice, specifications or materials that in our opinion will not alter the function of the product.


PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			


MOUNTING OPTIONS

IC - INSULATION CONTACT | ICAT - INSULATION CONTACT / AIR TIGHT | CP - CHICAGO PLENUM
(DIM10Z / DALIZ-DT6 / DALIZ-DT8)









BOX SIZE	L 1	L 2	W	H
A	18 - 1/4"	14 - 7/8"	12 - 1/8"	11 - 1/4"


BOX TYPE / LUMEN OUTPUT - WW BEAM			
LUMEN OUTPUT	BOX-A		
	IC	ICAT	CP
10LM	✔	✔	✔
15LM	✔	✔	✔
20LM			


PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

REMOTE COMPACT DRIVER

REMOTE COMPACT DRIVER (DIMMING)

DX ORDERING OPTIONS	
DIM10Z-DX	remote compact eldoLED flicker free 0-10V dim 0.1% driver
DALIZ-DT6-DX	remote compact eldoLED flicker free DALI-2, DT6, dim to 0.1% driver
DALIZ-DT8-DX	remote compact eldoLED flicker free DALI-2, DT8, dim to 0.1% driver
DMX-RJ45-DX	remote compact DMX-512/RDM dim to 0% with RJ45 input driver






*Remote DX can power LEDs up to 330FT (18 AWG).
Customer will recieve a single remote compact driver per fixture.


PLENUM HEIGHT

(NC-LVL-DX) NEW CONSTRUCTION REMOTE DX DRIVER



NOMINAL LED VOLTAGE: 36VDC


Customer to order CC Remote Driver separately or POE Node by others.




PROJECT INFORMATION			
JOB NAME		TYPE	
ORDERING CODE			

WIRELESS OPTIONS

NC - NEW CONSTRUCTION (10LM)
PLENUM SIDE



NC - NEW CONSTRUCTION (10LM)
DX REMOTE



Customer must verify system design and installation with their controls provider (e.g., Lutron).
Remote DX can power LEDs up to 330FT (18 AWG), but adequate wireless signal is customers responsibility.

LUTRON Athena

ORDERING CODE

AWND.....athena wireless node (DALI2 Driver) - integrated / above ceiling

AWND-DX..athena wireless node (DALI2 Driver) - remote DX Compact Driver



MODEL NUMBER

athena node model #: A-WN-D01-RF

POWER SUPPLY

(DALI2 Driver): Moons D4i DALI2 LED driver with DALI Bus Power, Dim-to-off

legrand WATTSTOPPER® PLUS

ORDERING CODE

CLMD .....connected lighting module (DALI2 Driver) - integrated / above ceiling

CLMD-DX...connected lighting module (DALI2 Driver) - remote DX Compact Driver



MODEL NUMBER

CLM model #: ZBHA-CLM-DIM

POWER SUPPLY

(DALI2 Driver): Moons D4i DALI2 LED driver with DALI Bus Power, Dim-to-off