Catalog # : _____ Project : _____ Type : _____

Prepared By : _____ Date : _____

4" LED Commercial Downlight (LCD4)

New Construction



OVERVIEW	
Lumen Package (lm)	1,050 - 2,500
Wattage Range (W)	14 - 22
Efficacy Range (LPW)	93 - 112
Weight lbs (kg)	7.5 (3.4)

QUICK LINKS

Ordering Guide | Performance | Photometrics | Dimensions

FEATURES & SPECIFICATIONS

Construction

- Designed for use in non-insulated ceiling where insulation must be kept a minimum of 3" from the fixture.
- Junction box listed for (8) #12 AWG (four in, four out) 90°C conductors and thru branch wiring.
- Junction box contains (5) 1/2" knockouts with trade pry-out slots and (4) Romex cable clamp knockouts.
- Frame accomodates up to 1/2" ceiling thickness. Standard 24" nailer bars ship with each unit and field installed.

Optical System

- LED source provides superior lumen output with maximum visual comfort.
- Tailored spot, narrow flood, flood and wide flood beam optics designed for glare free illumination.
- Choice of flanged or flangeless spun reflector utilizing heavy gauge highly reflective diffuse anodized aluminum to deliver low glare, even illumination of the space.
- Reflectors are retained with three retention clips holding the flange tight to the finished ceiling surface.
- Minimum CRI of 80.

Electrical

- High-performance driver features over-voltage, under voltage, short-circuit and over temperature protection.
- 0-10 volt dimming (1% - 100%) standard.
- Standard Universal Voltage (120-277 Vac) Input 50/60 Hz.
- L70 Calculated Life: > 50k Hours projected @ 25°C per IESNA TM-21-11.
- Total harmonic distortion: <20%
- Power factor: >.90
- Input power stays constant over life.
- High-efficacy LEDs with integrated circuit board mount directly to an extruded aluminum heatsink to maximize heat dissipation and promote long life.
- Remote Emergency Battery (120-277V) field installed is available to meet critical life safety lighting requirements. The 90-minute battery provides 7.8 watts constant power to the LED system, ensuring code compliance.To calculate light output during emergency mode(EM battery 7.8 watts x LPW of fixture being powered - see spec sheet). Detailed wiring diagram and installation instructions located on website.

Installation

- Accommodates ceiling thickness up to 0.5".
- 24" nailer bars provide stability and support for installation on joists, T-Grid and suspended ceilings.
- Housings can be positioned at any point within the 24" joist span.
- Score lines allow adjustments for 12" joists without tools.
- New construction rough-in kits available. See Accessory ordering information.

Warranty

- LSI luminaires carry a 5-year limited warranty. Refer to https://www.lsicorp.com/resources/terms-conditions-warranty/ for more information.
- 1 year warranty on optional Emergency Battery. Test regularly in accordance with local codes.

Listings

- CSA Listed to UL 1598 and UL 8750 standards for 25°C Ambient applications
- RoHS Compliant.
- EMI/RFI compliant with FCC 47CFR Part 15 Class B Consumer limits and Class A Commercial & Industrial.
- Damp location rated
- Title 24 Compliant.

©LSI Industries Inc. All Rights Reserved. Specifications and dimensions subject to industry standard tolerances. Specifications subject to change without notice.

4" LED Commercial Downlight (LCD4) New Construction

Type : _____

Have questions? Call us at (800) 436-7800

ORDERING GUIDE

Back to Quick Links

TYPICAL ORDER EXAMPLE: LCD4 LED 24L UNV DIM1 35 NF TR4R HAZ

Prefix	Light Source	Lumen Package	Voltage	Driver	Color Temperature	CRI[2]	Beam Optics[3]
LCD4 - 4" New Construction[1]	**LED**	**14L** - 1,400 Lumens **24L** - 2,400 Lumens	**UNV** - 120 - 277V	**DIM1** - Dims to 1% (0-10V dimming)	**35** - 3500K **40** - 4000K	**Blank** - 80 min.	**SP** - Spot **NF** - Narrow Flood **FL** - Flood **WF** - Wide Flood

	Reflector	Finish
Self-flanged	**TR4R** - Open Reflector	**SF HAZ** - Haze semi- diffused
		SF SPC - Specular clear
	TR4RWW - Wall Wash[4]	**SF HAZ** - Haze semi-diffused
Flangeless (Ships standard w/ white plastic trim ring)	**TR4R** - Open Reflector	**HAZ** - Haze semi-diffused, white trim ring
		SPC - Specular clear, white trim ring
	TR4RWW - Wall Wash[4]	**HAZ** - Haze semi-diffused wall wash reflector, white trim ring
	TR4RL - Regressed Lens[6]	**HAZ** - Haze semi-diffused reflector w/ specular clear regressed lens and white trim ring
		SPC - Specular clear refector w/ specular clear regressed lens and white trim ring

Need more information?
Click here for our glossary

Have additional questions?
Call us at (800) 436-7800

ACCESSORY ORDERING INFORMATION

Part Number	Description
616105	WH - White metal trim ring (only compatible with flangeless trims)
778196	Remote Mount Battery
786277	Remote Battery with Grid Mount Kit
640192	New Construction Rough-in Kit 1-pack
640191	New Construction Rough-in Kit 1-pack

CONTROLS INFORMATION

Click here to learn more details about AirLink Blue

PERFORMANCE

Back to Quick Links

Delivered Lumens*

Lumen Package	Distribution	3500K		4000K		Wattage
		Delivered Lumens	Efficacy	Delivered Lumens	Efficacy	
14L	SP	1414	101	1414	101	14
	NF	1401	100.1	1401	100.1	
	FL	1386	99	1386	99	
	WF	1304	93.1	1304	93.1	
24L	SP	2455	111.6	2455	111.6	22
	NF	2432	110.5	2432	110.5	
	FL	2407	109.4	2407	109.4	
	WF	2264	102.9	2264	102.9	

* LED Chips are frequently updated therefore values may change. Data is based on Haze Reflector.

Electrical Data - Current Draw AMPS*

Lumen Package	120V	208V	240V	277V
14L	0.12	0.07	0.06	0.05
24L	0.18	0.11	0.09	0.08

* Electrical Data at 25C (77F)/ Actual Wattage may differ +/-10%.

1 Regressed lens trims are wet location listed. All other trims are rated for damp location.
2 TR4RWW wall wash reflector comes with 40° integrated optic; additional beam optics not compatible.

©LSI Industries Inc. All Rights Reserved. Specifications and dimensions subject to industry standard tolerances. Specifications subject to change without notice.

4" LED Commercial Downlight (LCD4) New Construction

Type : _____

Have questions? Call us at (800) 436-7800

PHOTOMETRICS

Back to Quick Links

Luminaire photometry has been conducted by a NVLAP accredited testing laboratory in accordance with IESNA LM-79-08. As specified by IESNA LM-79-08 the entire luminaire is tested as the source resulting in a luminaire efficiency of 100%.

See the individual product page on https://www.lsicorp.com/ for detailed photometric data.


LCD4-LED-24L-35-SP-TR4R-SF-HAZ

Lumens: 2,455
Watts: 22.2
Efficacy: 111


ZONAL LUMEN SUMMARY		
Zone	**Lumens**	**%Fixture**
0-10	803	32.7%
10-20	892	36.3%
20-30	569	23.2%
30-40	129	5.2%
40-50	43	1.7%
50-60	14	0.6%
60-70	3	0.1%
70-80	1	0.1%
80-90	0	0.0%
90-100	0	0.0%
0-180	2,455	100.0%

CANDELA TABLE	
Degree Vertical	**Candela**
0	11,431
5	9,951
10	5,678
15	3,013
20	1,925
25	1,332
30	523
35	172
40	84
45	54
50	33
55	14
60	5
65	3
70	2
75	1
80	0
85	0
90	0

Polar Candela Distribution



Illuminance at a Distance




LCD4-LED-24L-35-NF-TR4R-SF-HAZ

Lumens: 2,432
Watts: 22.2
Efficacy: 110


ZONAL LUMEN SUMMARY		
Zone	**Lumens**	**%Fixture**
0-10	497	20.4%
10-20	949	39.0%
20-30	710	29.2%
30-40	196	8.0%
40-50	60	2.5%
50-60	16	0.6%
60-70	3	0.1%
70-80	1	0.0%
80-90	0	0.0%
90-100	0	0.0%
0-180	2,432	100.0%

CANDELA TABLE	
Degree Vertical	**Candela**
0	5,756
5	5,523
10	4,611
15	3,473
20	2,446
25	1,609
30	685
35	275
40	136
45	76
50	39
55	15
60	5
65	3
70	2
75	1
80	0
85	0
90	0

Polar Candela Distribution



Illuminance at a Distance



©LSI Industries Inc. All Rights Reserved. Specifications and dimensions subject to industry standard tolerances. Specifications subject to change without notice.

4" LED Commercial Downlight (LCD4) New Construction

Type : _____

Have questions? Call us at (800) 436-7800

PHOTOMETRICS

Back to Quick Links


LCD4-LED-24L-35-FL-TR4R-SF-HAZ

Lumens: 2,407
Watts: 22.2
Efficacy: 108


ZONAL LUMEN SUMMARY		
Zone	**Lumens**	**%Fixture**
0-10	359	14.9%
10-20	884	36.7%
20-30	792	32.9%
30-40	265	11.0%
40-50	85	3.5%
50-60	18	0.7%
60-70	4	0.1%
70-80	1	0.1%
80-90	0	0.0%
90-100	0	0.0%
0-180	2,407	100.0%

CANDELA TABLE	
Degree Vertical	**Candela**
0	3,826
5	3,844
10	3,654
15	3,182
20	2,513
25	1,770
30	852
35	391
40	206
45	104
50	45
55	17
60	6
65	3
70	2
75	1
80	1
85	0
90	0

Polar Candela Distribution



Illuminance at a Distance



Vert. Spread: 47.9°
Horiz. Spread: 47.4°


LCD4-LED-24L-35-WF-TR4R-SF-HAZ

Lumens: 2,264
Watts: 22.2
Efficacy: 102


ZONAL LUMEN SUMMARY		
Zone	**Lumens**	**%Fixture**
0-10	237	
10-20	617	
20-30	722	
30-40	405	
40-50	219	
50-60	53	
60-70	9	
70-80	2	0.1%
80-90	0	0.0%
90-100	0	0.0%
0-180	2,264	100.0%

CANDELA TABLE	
Degree Vertical	**Candela**
0	3,826
5	3,844
10	3,654
15	3,182
20	2,513
25	1,770
30	852
35	391
40	206
45	104
50	45
55	17
60	6
65	3
70	2
75	1
80	1
85	0
90	0

Polar Candela Distribution



Illuminance at a Distance




Vert. Spread: 56.3°
Horiz. Spread: 56.1°

©LSI Industries Inc. All Rights Reserved. Specifications and dimensions subject to industry standard tolerances. Specifications subject to change without notice.

PRODUCT DIMENSIONS

Back to Quick Links



4" RECESSED DOWNLIGHT REFLECTORS

Back to Quick Links



TR4R - Open Reflector
Self-Flange or Flangeless
HAZ - Haze semi-diffused
SPC - Specular clear



TR4RWW - Wall Wash w/ Kicker Reflector
Self-Flange or Flangeless
HAZ - Haze semi-diffused



TR4RL - Regressed Lens w/ Specular Clear Reflector
Flangeless
HAZ - Haze semi-diffused
SPC - Specular clear
Wet Location Listed

©LSI Industries Inc. All Rights Reserved. Specifications and dimensions subject to industry standard tolerances. Specifications subject to change without notice.