prescolite

LFCR-4RD-R

LITEFRAME COMMERCIAL 4" ROUND
REMODEL DOWNLIGHT

DATE:	LOCATION:
TYPE:	PROJECT:
CATALOG #:	

LITEFRAME Commercial




FEATURES

- 4" LED downlight delivering 500–5000 lumens
- Narrow, Medium or Wide Beam Distribution
- 2700K–5000K, 90+ CRI (2 SDCM)
- Dimming protocols include 0–10V, Phase, DMX, DALI
- NX Lighting Controls wired and wireless controls capability available
- TriGain® technology is standard and delivers 90 CRI (50+ R9) color rendition without efficacy compromise

C US WET LOCATION TriGain® technology

SERVICE PROGRAMS

tradeSELECT QS10



Typical Dimensions and Weights				
Lumen Package	Aperture Inches (mm)	"A" Diameter Inches (mm)	"B" Height Inches (mm)	Weight lbs (kg)
05L–15L	4.0 (101.6)	5.25 (133.4)	3.9 (99.1)	1.9 (0.9)
20L–30L			5.2 (132.1)	2.1 (1.0)
35L–50L			6.8 (172.7)	2.4 (1.1)

See DIMENSIONS section for complete details

CONTROLS TECHNOLOGY

NX WIRELESS NX WIRED

SPECIFICATIONS

CONSTRUCTION

- Fixture Module designed for Non-IC, direct install construction
- Die cast aluminum fixture module with spring steel clips for secure mounting to ceiling
- Junction box allows for both installation and service from below ceiling
- Light engine connections use plenum rated (CMP) cable
- Quick disconnects standard for ease of installation

OPTICS

- High purity spun aluminum reflector, self-flanged
- 55° visual cutoff to source image and 55° cutoff to source
- Specular, semi-specular, or Softglow (diffuse) anodized finishes. White and black painted cone reflector colors also available.
- Painted flange options in white or black

ELECTRICAL

- Chip-on-board LED with 2 SDCM
- TriGain® is a patented narrow-band potassium fluorosilicate (PFS) phosphor technology which provides improved color rendition without compromise to LED efficacy
- 2700K, 3000K, 3500K, 4000K, 5000K CCTs, 90+ CRI

ELECTRICAL (CONTINUED)

- Long LED life: L80 / >66,000 hours (TM-21)
- Universal voltage 120–277V driver, 347V optional
- UL Class 2, inherent short circuit and overload protection
- Flicker-free dimming options in a wide range of protocols from 1% to <0.1% performance
- 0–10V, phase (forward/reverse) DMX, DALI, and Lutron options
- NX Lighting Controls provides options for standalone and networked functionality with wired or wireless connectivity for NX system deployments
- Integral and remote emergency battery options available

INSTALLATION

- Accommodates ceiling thickness from 0.50" to 3.00"
- Fixture module including driver fully accessible from above or below the ceiling

CERTIFICATIONS

- cCSAus certified to UL 1598
- For 45L–50L: Marked spacing required (24" fixture center to center; 24" fixture center to building member; 0.5" above fixture)
- Downlight suitable for wet locations, covered ceiling. Wall wash suitable for damp locations

CERTIFICATIONS (CONTINUED)

- Shower trim is IP65 rated (room side) when properly installed per installation instructions
- EM/EMR: Certified under UL 924 standard for emergency lighting and power equipment
- EM/EMR: Emergency battery packs are California Energy Commission (CEC) Title 20 Compliant
- Approved for 8 (4 in/4 out) No. 12AWG conductors rated for 90°C through wiring
- Suitable for -20°C to 25°C standard, High Ambient (HA) option available, up to 40°C

WARRANTY

- 5 year warranty

KEY DATA	
Lumen Range	500–5000
Wattage Range	5.9–52.1
Efficacy Range (LPW)	94–129
Reported Life (Hours)	L80 / >66,000

*Based on Specular, 35K, 90 CRI

© 2026 HLI Solutions, Inc. All rights reserved. Information and specifications subject to change without notice. All values are design or typical values when measured under laboratory conditions.

prescolite

DATE: | LOCATION:

TYPE: | PROJECT:

CATALOG #:

LFCR-4RD-R

LITEFRAME COMMERCIAL 4" ROUND REMODEL DOWNLIGHT

Gray Shading = Service Program

tradeSELECT QS10 Limit of 150 Luminaries

ORDERING GUIDE

Example: LFCR-4D-MR-10L35K9-WD-DM1 / LFCR-4RD-T-WD-S

CATALOG #

FIXTURE MODULE (Ships separately)

LFCR-4D-MR – [ ] [ ] 9 – [ ] – [ ] [ ] – [ ]

Ap/Shp/Funct	Lumen Output	CCT	CRI
LFCR-4D-MR 4" Downlight Fixture Module, Remodel	**05L** 500	**27K** 2700K	**9** 90+
	10L 1000	**30K** 3000K	
	15L 1500	**35K** 3500K	
	20L 2000	**40K** 4000K	
	25L 2500	**50K** 5000K	
	30L 3000		
	35L 3500		
	40L 4000		
	45L 4500 [1]		
	50L 5000 [1]		

Distribution	Driver Options	Control Options	Module Options [2]
NR Narrow (35°/0.5 SC)[16]	**120–277V Options**	**NX Lighting Controls**	**EM** 10W Emergency Battery Pack with Integral Test Switch
MD Medium (50°/0.7 SC)[16]	**DM1** 0–10V Dimming to 1%	Networked Wireless	**EMR** 10W Emergency Battery Pack with Remote Test Switch
WD Wide (65°/1.0 SC)	**DM01** 0–10V Dimming to < 1% [3]	**NXW** NX Networked Wireless Radio Module NXRM2 and Bluetooth Programming, without Sensor [7]	**DTS** Device Transfer Switch with Dimming Bypass [9, 10]
	PDM Phase (Forward/Reverse) Dimming to 1% [4]	Networked Wired	**F** Fuse
	DALI DALI Dimming to 1% [3]	**NXE** NX Wired Dual RJ45 SmartPORTS, without Sensor [7]	**HA** High Ambient Option (40°C) [11]
	DMX1 DMX with RDM Dimming to 1%	**Other Lighting Controls**	
	347V Option	Networked Wireless	
	DM34 0–10V Dimming to 1% (347V input) [5, 6]	**AWNR** Lutron Athena Enabled [8]	

TRIM (Ships separately)

LFCR-4RD-T – [ ] – [ ] [ ]

Aperture/Shape/Function	Style [15]	Trim Type	Reflector Finish	Flange Color Options [14]	Trim Options
LFCR-4RD-T 4" Round Downlight Trim Assembly	*Do not specify trim style for standard trim*	**WD** Standard Downlight Reflector (used with NR, MD, and WD distributions from fixture module)	*Do not specify reflector finish for SH Trim Style*	*Standard matches reflector color*	**EM** Pre-punched reflector for EM integral test switch and indicator
	SH Non-Conductive Shower Trim with Acrylic, Micro-prism Lens	**WW** Wall Wash	**S** Specular	**WT** White Flange	**AM** Antimicrobial Coating [12, 13]
			SS Semi-Specular	**BT** Black Flange	
			VS Softglow		
			WC Painted White Cone		
			BC Painted Black Cone		

Accessories

- ☐ **LF-MOR4-R-WH** Metal Oversized Ring, 4" Round, White (8.3" outside diameter)
- ☐ **LF-MOR4-R-BL** Metal Oversized Ring, 4" Round, Black (8.3" outside diameter)
- ☐ **LFR-SCA4-__** Sloped Ceiling Adapter, 4" White

  Specify slope angle 5°–35° in 5° increments. Not available with EM options

Notes:

1. Lumen outputs 45L–50L require marked spacing with dims (24" x 24" x ½" above fixture)
2. Module options EM/EMR/DTS not available in combination
3. DM01 & DALI available 05L–45L
4. PDM available 10L–45L
5. DM34 available 05L–35L
6. DM34 not available with EM, EMR, DTS, or F fixture module options
7. NXW/NXE control options require DM1 or DM34 driver option
8. AWNR control option requires DM00 driver option (DM00 only available in combination with AWNR)
9. Consult factory for DTS with control options
10. DTS requires driver options DM1, DM01 or DALI
11. HA option available 05L–25L
12. AM available with WC or Specular Clear (S or SWT), also available with WT for SH trim
13. AM not available with WW or EM
14. WT not available for WC, BT not available for BC
15. SH not available with WW or EM, requires WT or BT- reflector finish not applicable, available with lumen output 05L–30L
16. NR and MD available 05L–35L

© 2026 HLI Solutions, Inc. All rights reserved. Information and specifications subject to change without notice. All values are design or typical values when measured under laboratory conditions.

prescolite

LFCR-4RD-R

LITEFRAME COMMERCIAL 4" ROUND
REMODEL DOWNLIGHT

DATE: | LOCATION:

TYPE: | PROJECT:

CATALOG #:

NX LIGHTING CONTROLS

	Control Option Ordering Logic & Description		Control Option Functionality								Control Option Components	
			Networkable	Grouping	Scheduling	Occupancy/ Motion	Daylight Harvesting	0–10V Dimming	On/Off Control	Bluetooth App Programming		
NX Wireless	NXW	NX Networked Wireless Radio Module NXRM2 and Bluetooth® Programming, without Sensor	✓	✓	✓	–	–	✓	✓	✓		NXRM2-H
NX Wired	NXE	NX Wired Dual RJ45 SmartPORTS, without Sensor	✓	✓	✓	–	–	✓	✓	✓[1]		NXFSP

1 Requires NXBTC, order separately.

NX LIGHTING CONTROLS APP



The NX Lighting Controls App is a free to use mobile application for programming both an NX Lighting Controls System or Standalone Bluetooth Sensors. The mobile app allows you to configure devices, discover and setup wireless enabled luminaires and program your NX system settings.

Android

Apple iOS

OTHER LIGHTING CONTROLS

	Control Option Ordering Logic & Description		Control Option Functionality								Control Option Components	
			Networkable	Grouping	Scheduling	Occupancy/ Motion	Daylight Harvesting	0–10V Dimming	On/Off Control	Bluetooth App Programming		
Other	AWNR	The Athena wireless node is a radio frequency (RF) device that enables simple, digital control of individual light fixtures in an Athena control system.[1]	✓	✓	-	-	-	✓	✓	-		A-WN-D01-RF-WH

1 Lutron Athena Hub required to enable Networking, Grouping and Scheduling.

© 2026 HLI Solutions, Inc. All rights reserved. Information and specifications subject to change without notice. All values are design or typical values when measured under laboratory conditions.

prescolite

LFCR-4RD-R

LITEFRAME COMMERCIAL 4" ROUND
REMODEL DOWNLIGHT

DATE: LOCATION:

TYPE: PROJECT:

CATALOG #:

PERFORMANCE DATA TABLE

Performance Data shown is 3500K 90+ CRI with Specular reflector.

Lumen Package	Nominal Lumens	Distribution	Delivered Lumens	Watts	LPW
05L	500	Narrow	672	5.9	114
		Medium	623	5.9	106
		Wide	552	5.9	95
		Wall Wash	572	5.9	97
10L	1000	Narrow	1293	11.2	115
		Medium	1199	11.2	107
		Wide	1062	11.2	94
		Wall Wash	1101	11.2	98
15L	1500	Narrow	1866	15.2	123
		Medium	1731	15.2	114
		Wide	1533	15.2	101
		Wall Wash	1589	15.2	105
20L	2000	Narrow	2476	21.9	113
		Medium	2297	21.9	105
		Wide	2034	21.3	95
		Wall Wash	2108	21.7	97
25L	2500	Narrow	3109	24.1	129
		Medium	2884	24.1	120
		Wide	2554	24.1	106
		Wall Wash	2647	24.1	110
30L	3000	Narrow	3727	29.8	125
		Medium	3458	29.8	116
		Wide	3062	29.8	103
		Wall Wash	3173	29.8	106
35L	3500	Wide	3597	36.8	98
		Wall Wash	3728	36.8	101
40L	4000	Wide	4053	41.6	97
		Wall Wash	4200	41.6	101
45L	4500	Wide	4566	45.3	101
		Wall Wash	4732	45.3	104
50L	5000	Wide	5065	52.1	97
		Wall Wash	5249	52.1	101

© 2026 HLI Solutions, Inc. All rights reserved. Information and specifications subject to change without notice. All values are design or typical values when measured under laboratory conditions.

prescolite

LFCR-4RD-R


LITEFRAME COMMERCIAL 4" ROUND
REMODEL DOWNLIGHT

DATE:	LOCATION:
TYPE:	PROJECT:
CATALOG #:	

DIMENSIONS


LFCR-4D-MR

Fixture Module consists of Light Engine and Driver J-Box assemblies.
Overall dimensions for each are dependent upon configuration selected.
See the following pages for details.



Driver J-Box (DM1 shown)

Light Engine with Trim assembly installed



Side View Standard


DIMENSIONAL DATA	
Aperture	Ø4.00" (101.6mm)
Overall Width (Flange To Flange)	Ø5.25" (133.4mm)
Flange Width	0.63" (16mm)
Ceiling Cutout	Ø4.75" (121mm)
Ceiling Thickness	0.50" – 3.00" (13 – 76mm)


OVERALL LIGHT ENGINE HEIGHT * (All Lumen Outputs)	
Lumen Package	**Height ("A")**
05L–15L	3.9" (99.1mm)
20L–30L	5.2" (132.1mm)
35L–50L	6.8" (172.7mm)

* Note: Add ½" minimum plenum clearance above overall Light Engine Height.

** For 45L–50L: Marked spacing required 24" fixture center to center; 24" fixture center to building member; 0.5" above fixture.

*** Non-IC rating requires 3" from insulation and combustible materials.





ROUND LF-MOR4-R METAL OVERSIZED RING

(See LF-MOR Installation Instruction for more details)

© 2026 HLI Solutions, Inc. All rights reserved. Information and specifications subject to change without notice. All values are design or typical values when measured under laboratory conditions.

prescolite

LFCR-4RD-R

LITEFRAME COMMERCIAL 4" ROUND
REMODEL DOWNLIGHT


DATE: | LOCATION:

TYPE: | PROJECT:


CATALOG #:

DIMENSIONS (CONTINUED)


DRIVER J-BOX




DM1 / DM01 / DALI / PDM / DM34




DMX1 / DTS



NX* / AWNR CONTROLS OPTION



DM1 / DMO1 / DALI / PDM / DMX1 + EM/EMR



NX* / AWNR CONTROLS + EM/EMR OPTIONS

EM/EMR Driver J-Box Conduit (provided) connects to Driver J-Box
(see Driver J-Box for additional details)

OVERALL DRIVER J-BOX DIMENSIONS (ALL LUMEN OUTPUTS)					
Driver/Controls Options		"B" (Height)	"C" (Length)	"D" (Width)	Minimum J-Box Plenum Clearance
DM1 / DM01 / DALI / PDM		2.7" (68.6mm)	5.5" (139.7mm)	3.3" (83.8mm)	3.5" (88.9mm)
DMX1 / DTS		2.7" (68.6mm)	8.9" (226.1mm)	3.3" (83.8mm)	5.25" (133.4mm)
NX* / AWNR		2.7" (68.6mm)	8.9" (226.1mm)	3.3" (83.8mm)	5.25" (133.4mm)
EM/EMR		3.0" (76.2mm)	10.5" (266.7mm)	3.7" (94mm)	7.5" (32.9mm)
EM/EMR + NX* / AWNR	EM J-Box	3.0" (76.2mm)	10.5" (266.7mm)	3.7" (94mm)	7.5" (32.9mm)
	Driver Box	2.7" (68.6mm)	5.5" (139.7mm)	3.3" (83.8mm)	

© 2026 HLI Solutions, Inc. All rights reserved. Information and specifications subject to change without notice. All values are design or typical values when measured under laboratory conditions.

prescolite

LFCR-4RD-R

LITEFRAME COMMERCIAL 4" ROUND
REMODEL DOWNLIGHT

DATE: | LOCATION:

TYPE: | PROJECT:

CATALOG #:

PHOTOMETRY

LFCR-4D-MR-20L35K9-NR-DM1 / LFCR-4RD-T-WD-S


LUMINAIRE DATA

Test No.	**P26.00759**
Description	**2000 lm, Narrow, 3500K, 90 CRI**
Delivered Lumens	**2476**
Watts	**21.9W**
Efficacy	**113**
Mounting	**Recessed**
Spacing Criterion	**0.5**
Beam Angle (FWHM)	**34**

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
0–40	2440	98.6
0–60	2474	100.0
0–90	2476	100.0
0–180	2476	100.0

POLAR GRAPH



CANDELA DISTRIBUTION

Degree	Candela
0	6443
5	5908
15	3577
25	1682
35	222
45	37
55	1
65	1
75	0
85	0
90	0

LUMINANCE DATA*

Vertical Angle	Average
45°	6454
55°	215
65°	292
75°	0
85°	0

*Candela/Square Meter

LFCR-4D-MR-20L35K9-MD-DM1 / LFCR-4RD-T-WD-S


LUMINAIRE DATA

Test No.	**P26.00762**
Description	**2000 lm, Medium, 3500K, 90 CRI**
Delivered Lumens	**2297**
Watts	**21.9W**
Efficacy	**105**
Mounting	**Recessed**
Spacing Criterion	**0.8**
Beam Angle (FWHM)	**51**

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
0–40	2230	97.1
0–60	2296	99.9
0–90	2297	100.0
0–180	2297	100.0

POLAR GRAPH



CANDELA DISTRIBUTION

Degree	Candela
0	3415
5	3335
15	2879
25	1827
35	448
45	71
55	2
65	1
75	0
85	0
90	0

LUMINANCE DATA*

Vertical Angle	Average
45°	12385
55°	430
65°	292
75°	0
85°	0

*Candela/Square Meter

LFCR-4D-MR-20L35K9-WD-DM1 / LFCR-4RD-T-WD-S


LUMINAIRE DATA

Test No.	**P25.01118**
Description	**2000 lm, Wide, 3500K, 90 CRI**
Delivered Lumens	**2034**
Watts	**21.3W**
Efficacy	**95.3**
Mounting	**Recessed**
Spacing Criterion	**1.0**
Beam Angle (FWHM)	**68**

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
0–40	1895	93.2
0–60	2032	99.9
0–90	2034	100.0
0–180	2034	100.0

POLAR GRAPH



CANDELA DISTRIBUTION

Degree	Candela
0	1810
5	1810
15	1580
25	832
35	146
45	3
55	1
65	1
75	0
85	0
90	0

LUMINANCE DATA*

Vertical Angle	Average
45°	25468
55°	645
65°	292
75°	477
85°	0

*Candela/Square Meter

© 2026 HLI Solutions, Inc. All rights reserved. Information and specifications subject to change without notice. All values are design or typical values when measured under laboratory conditions.

LFCR-4RD-R

LITEFRAME COMMERCIAL 4" ROUND
REMODEL DOWNLIGHT

PHOTOMETRY (CONTINUED)

LFCR-4D-MR-20L35K9-WD-DM1 / LFCR-4RD-T-WW-S


LUMINAIRE DATA

Test No.	**26.00057**
Description	**2000 lm, Wall Wash, 3500K, 90 CRI**
Delivered Lumens	**2108**
Watts	**21.7W**
Efficacy	**126**
Mounting	**Recessed**
Spacing Criterion	**N/A**
Beam Angle (FWHM)	**N/A**

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
0–40	1844	87.5
0–60	2055	97.5
0–90	2108	100.0
0–180	1928	100.0

POLAR GRAPH



CANDELA DISTRIBUTION

Degree	Candela
0	1762
5	1737
15	1547
25	1255
35	734
45	297
55	152
65	103
75	53
85	14
90	0

LUMINANCE DATA*

Vertical Angle	Average
45°	51808
55°	32687
65°	876
75°	953
85°	1415

*Candela/Square Meter

LUMEN MULTIPLIER

Option	27K9	30K9	35K9	40K9	50K9
Multiplier	0.95	0.99	1.00	1.00	1.00


Photometrics are published below at a nominal 3500 Kelvin, 90+ CRI. This table may be used to approximate the lumen values at different Kelvin temperatures. Power consumption would stay the same.

REFLECTOR FINISH & COLOR MULTIPLIER

Option	Specular (S)	Semi-Specular (SS)	Softglow (VS)	White Cone (WC)	Black Cone (BC)
Multiplier	1.00	1.00	0.89	0.98	0.44

TM-30 DATA

COLOR VECTOR GRAPHIC
3500K, 90 CRI



TEST RESULTS - 3500K	
Value	90+ CRI
R_f	91
R_g	99
CCT (K)	3455
D_{UV}	0.0040
x	0.4122
y	0.4034
CIE R_a	92
CIE R_9	59

© 2026 HLI Solutions, Inc. All rights reserved. Information and specifications subject to change without notice. All values are design or typical values when measured under laboratory conditions.

prescolite

LFCR-4RD-R

LITEFRAME COMMERCIAL 4" ROUND
REMODEL DOWNLIGHT

DATE: | LOCATION:

TYPE: | PROJECT:

CATALOG #:

ELECTRICAL DATA

DRIVER DATA		
Input Voltage	120–277 V	347 V
Input Frequency	50/60 Hz	50/60 Hz
Power Factor	≥0.90	≥0.90
THD	<20%	<20%
EMI Filtering (FCC 47 CFR Part 15)	Class A	Class A

* Values for DM1 option shown, values for other dimming options may vary.

ADDITIONAL INFORMATION

Dimming Compatibility

For more details and recommended dimmer list, see Dimming Compatibility Information on currentlighting.com/prescolite.

DMX

See instruction sheet on currentlighting.com/prescolite for connection & installation information.

Central Inverters

For full fixture output in back-up mode, we recommend you visit currentlighting.com/dual-lite for your Central Lighting Inverter options.
Please contact your local Current representative for any assistance with proper sizing and loading of your inverter selection. Central lighting inverters must be ordered separately.

Lumen Output in Emergency Mode

To determine the lumen output in emergency mode, multiply the battery pack wattage by the fixture lumens per watt (LPW).
For example, 10W x 120 LPW = 1200 lumens in emergency mode.

© 2026 HLI Solutions, Inc. All rights reserved. Information and specifications subject to change without notice. All values are design or typical values when measured under laboratory conditions.