LAD-2G

Project Name:	
Type:	



APPLICATION
4" and 6" LED commercial frame-in is non-insulated ceiling design. Ideal for low to medium ceilings such as retails, hospitality, and commercial installations.

FEATURES:
- 4" and 6" nominal aperture steel die-formed housing.
- White smooth reflector standard.
- Field adjustable CCT (30/35/40K)
- Frosted polycarbonate lens for smooth light.

INSTALLATION:
- Spring clips clamp to existing frame.
- Optional frame kit and J-box available.

LED:
- Color Temperature: Field adjustable: 3000/3500/4000 (K).
- CRI 90+
- High luminous efficiency, 100 lm/W.
- Beam angle: 90°

ELECTRICAL:
- 0-10V dimming (5-100% dim to off) standard.
- 120-277Vac
- Power Factor > 0.9
- Flicker free.
- 2K surge protection.
- Operating Temperature Range: -4°F (-20°C) ~ 104°F (40°C).
- Operating hours : 50,000 hours.

LISTING:
- Energy Star Listed.
- ETL Listing.
- Suitable for Wet Location.
- 50,000 hours lifespan.
- Type: Non-IC
- 5 years limited warranty.

CONFIGURATIONS

Model	Size	LED Watts	Lumen Output	Lumen Efficiency
LAD4C-2G	4"	9W	900 lm	100 lm/W
		12W	1200 lm	
		15W	1500 lm	
LAD6C-2G	6"	12W	1200 lm	
		18W	1800 lm	
		24W	2400 lm	

ORDERING INFORMATION

EXAMPLE: *LAD4C-2G-3S-3T-UNV-DM-WW*

MODEL	LED		COLOR TEMP.		VOLTAGE		DIMMING		TRIM	
LAD4C-2G	**3S**	Selectable 9/12/15W LED	**-3T**	Selectable 30/35/40K	**UNV**	120-277V	**DM**	0-10V (Std.)	**WW**	White (Std.)
LAD6C-2G	**3S**	Selectable 12/18/24W LED	**27K**	Static 2700K Special Order						


OPTIONS	
FK	Frame kit with bar hangers
JB	J-box included
EM10	10W Emergency Battery Backup*
EMI8	8W Self-Diagnostic Emergency Battery Backup*
EMI15	15W Self-Diagnostic Emergency Battery Backup*
BAA	Buy American Act

*Requires FK and JB options

UTOPIA LIGHTING reserves the right to change specifications, drawings, dimensions without prior notice. Visit our website for the latest product information.

LAD-2G

DIMENSIONS



Specifications: LAD4C

A : 5.6 (142.3)
B : 3.74 (95)
D : 6 (152.4)
E : Ceiling Cutout minimum 4.4 (111.76)


Specifications: LAD6C

A : 7.75 (196.8)
B : 4.5 (114.2)
D : 6 (152.4)
E : Ceiling Cutout minimum 5.7 (144.78)

All dimensions are in inches.




LIGHT ENGINE
(with integrated LED driver)



FRAME KIT



Selectable Wattage & CCT by Dip Switches



With frame kit and J-box

UTOPIA LIGHTING reserves the right to change specifications, drawings, dimensions without prior notice. Visit our website for the latest product information.