
LED tape KWP-8KHDRGB-1920-24

Ref. KWP-8KHDRGB-1920-24



Dimensions: Width [W]: 10 mm | Height [H]: 4 mm | Max run length [L] : 5 m | Cut every [C]: 50 mm | LED spacing [D]: 8.3 mm

IP65 | Pb Hg | 24 V | c UL us LISTED | CE | UKCA | RoHS COMPLIANT | 4 YEARS WARRANTY

- Sealed LED strip, easily installed in and removed from dedicated extrusions ("KLIK" system)
- Instant and clean service of a sealed LED strip, without tools or adhesives
- UL Listed
- High light transmission of the silicone sleeve (over 93%)

APPLICATION

- for the construction of lighting fixtures operating in damp environments

MOUNTING

- to the profile, by pressing

ADDITIONAL INFORMATION

- NOTE! LED tapes in a silicone sleeve, with a degree of protection IP65 are made to the size specified by the customer only by KLUŚ - if you cut it yourself, the tape will become unsealed, which will result in the loss of the warranty
- the luminous flux applies to unsealed LED strip

RELATED ACCESSORIES > ELECTRONICS > CONTROLLERS

Name	IP protection rating	Ref.
Controller RGB+CCT, Wlightbox NEW	20	E60235
Controller LED MONO\CCT\RGB\RGBW\RGBW+CCT, 5w1, SR5 NEW	20	E62159

RELATED ACCESSORIES > ELECTRONICS > CASAMBI CONTROL SYSTEM

Name	IP protection rating	Ref.
Controller LED Casambi CBU-ASD	20	E62147
Controller LED Casambi CBU-PWM4	20	E62148