
LED tape KWP-SEBLUE-1210-24-8

Ref. KWP-SEBLUE-1210-24-8



Dimensions: Width [W]: 10 mm | Height [H]: 4 mm | Max run length [L] : 6 m | Cut every [C]: 100 mm | LED spacing [D]: 16.7 mm

IP65 | Pb Hg | 24 V | c UL us LISTED | CE | UKCA | RoHS COMPLIANT | 4 YEARS WARRANTY

- Side emitting LED strip
- UL Listed
- High light transmission of the silicone sleeve (over 93%)

ADDITIONAL INFORMATION

- NOTE! LED tapes in a silicone sleeve, with a degree of protection IP65 are made to the size specified by the customer only by KLUŚ - if you cut it yourself, the tape will become unsealed, which will result in the loss of the warranty
- the luminous flux applies to unsealed LED strip

TECHNICAL SPECIFICATIONS

IP protection rating	65	MacAdam's ellipse	3 SDCM
Sealing type	silicone sleeve	Number of LEDs per 1 m	60
LED color	BLUE	Number of LEDs per cut section	6 pcs
Lumen output	92 lm/m	Energy consumption	5 kWh/1000h
Working temperature	-20°C - 60°C	Does not contain mercury and lead	yes
Input voltage	24 V DC	Dimmable	yes
Power consumption	4.8 W/m	No UV IR radiation	yes
Beam angle	120°	Warranty [months]	48

RELATED ACCESSORIES > ELECTRONICS > CONTROLLERS

Name	IP protection rating	Ref.
Controller RGB+CCT, Wlightbox NEW	20	E60235
Controller LED MONO, Wlightboxs 120W IP20	20	E60228

RELATED ACCESSORIES > ELECTRONICS > CASAMBI CONTROL SYSTEM

Name	IP protection rating	Ref.
Controller LED Casambi CBU-ASD	20	E62147

LED tape KWP-SEBLUE-1210-24-8

Ref. KWP-SEBLUE-1210-24-8

Name	IP protection rating	Ref.
Controller LED Casambi CBU-PWM4	20	E62148