LED tape K-0500-24 5 W/m, IP20

Ref. K-0500-24

NEW



Dimensions: Width [W]: 8 mm | Height [H]: 1.2 mm | Max run length [L] : 8 m | Cut every [C]: 50 mm | LED spacing [D]: 7.14 mm

CRI 90+ | IP20 | 24 V | c UL us LISTED | CE | UKCA | RoHS COMPLIANT | 3 YEARS WARRANTY

TECHNICAL SPECIFICATIONS

IP protection rating	**20**
CRI	**90**
LxBy	**L80B50**
Lifetime	**60000 h**
Working temperature	**-20°C - 60°C**
Input voltage	**24 V DC**
Power consumption	**5 W/m**
MacAdam's ellipse	**3 SDCM**
Number of LEDs per 1 m	**140**
Number of LEDs per cut section	**7 pcs**
Warranty [months]	**36**

Color temperature	Lumen output	Efficiency	Ref
3000 K	665 lm/m	133 lm/W	**K-30-0500-24**
4000 K	695 lm/m	139 lm/W	**K-40-0500-24**

RELATED ACCESSORIES > RELATED LED > WHITE MONO

Name	IP protection rating	Power consumption	Ref.
LED tape KWP-0500-24 5 W/m, IP65 NEW	65	5 W/m	KWP-30-0500-24 KWP-40-0500-24
LED tape KWP-14K-0500-24 5 W/m, IP65 NEW	65	5 W/m	KWP-14K30-0500-24 KWP-14K40-0500-24
LED tape KWP-8K-0500-24 5 W/m, IP65 NEW	65	5 W/m	KWP-8K30-0500-24 KWP-8K40-0500-24