# LED tape KWP-8KCR-0960-24

Ref. KWP-8KCR-0960-24




Dimensions: Width [W]: 10 mm | Height [H]: 4 mm | Max run length [L] : 5 m | Cut every [C]: 50 mm | LED spacing [D]: 7.14 mm

IP65 | CRI 95+ | 24 V | LISTED | RoHS COMPLIANT | 4 YEARS WARRANTY

- CRI 95+
- Excellent color rendering
- For the construction of sealed lighting fixtures
- High light transmission of the silicone sleeve (over 93%)

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| IP protection rating | **65** |
| Sealing type | **silicone sleeve** |
| CRI | **95** |
| Working temperature | **-20°C - 60°C** |
| Input voltage | **24 V DC** |
| Power consumption | **9.6 W/m** |
| Beam angle | **120°** |
| MacAdam's ellipse | **3 SDCM** |
| Number of LEDs per 1 m | **140** |
| Number of LEDs per cut section | **7 pcs** |
| Energy consumption | **9.6 kWh/1000h** |
| Does not contain mercury and lead | **yes** |
| Dimmable | **yes** |
| No UV IR radiation | **yes** |
| Warranty [months] | **48** |

| Color temperature | Lumen output | Efficiency | Ref |
|---|---|---|---|
| 3500 K | 893 lm/m | 93 lm/W | **KWP-8K** |
| 4000 K | 944 lm/m | 98 lm/W | **KWP-8K** |
| 5000 K | 953 lm/m | 99 lm/W | **KWP-8K** |

## RELATED ACCESSORIES > ELECTRONICS > CONTROLLERS

| Name | IP protection rating | Ref. |
|---|---|---|
| Controller RGB+CCT, Wlightbox NEW | 20 | E60235 |

# LED tape KWP-8KCR-0960-24

## Ref. KWP-8KCR-0960-24

| Name | IP protection rating | Ref. |
|---|---|---|
| Controller LED MONO\CCT\RGB\RGBW\RGBW+CCT, 5w1, SR5 NEW | 20 | E62159 |
| Controller LED MONO, Wlightboxs 120W IP20 | 20 | E60228 |

**RELATED ACCESSORIES > ELECTRONICS > CASAMBI CONTROL SYSTEM**

| Name | IP protection rating | Ref. |
|---|---|---|
| Controller LED Casambi CBU-ASD | 20 | E62147 |
| Controller LED Casambi CBU-PWM4 | 20 | E62148 |