Profile OLIS-K
Ref. A04195



KEY FEATURES

- Illuminated, recessed skirting board
- Masking the expansion joints between the wall and the floor
- Masking gaps on uneven surfaces
- Recess easily accessible for robotic vacuum cleaners
- Space for cable management
- Easy assembly

APPLICATION

warning and decorative lighting
function of a standard skirting board

MOUNTING

recessed, with mounting adhesive

ADDITIONAL INFORMATION

- the use of a dedicated connection strip at the back of the profile prevents slits between individual sections of the profile and facilitates the routing of cables
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ
- characteristic visible lines along the profile are a normal phenomenon, resulting from the manufacturing process and are not a defect of the product

Standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)

IP PROTECTION RATING

IP20 | IP65

MOUNTING METHOD

Recessed

TECHNICAL DRAWING

1:2



AVAILABLE COLOURS

COLOR	LENGTH	REF
silver anodized	1000 mm	A04195A_1
	2005 mm	A04195A_2
	3010 mm	A04195A_3
white lacquered	1000 mm	A04195L10_1
	2005 mm	A04195L10_2
	3010 mm	A04195L10_3
black anodized	1000 mm	A04195A07_1
	2005 mm	A04195A07_2
	3010 mm	A04195A07_3

TECHNICAL SPECIFICATIONS

Material	aluminum
Possible fixture IP	20, 65
Possible fixture shapes	linear, polygonal
Width	24 mm
Height	90 mm
LED gluing width A	7 mm
Width of the glow	7.2 mm
Max power of a single KLUŚ LED strip	15.6 W/m
Building type	Residential, HoReCa object, Commercial, Obiekt kulturalno/rozrywkowy
Facility zone	communication routes and corridors, office, lobby / foyer, media rooms / av, conference room, stairs / hallways
The cover is cut to the length of the profile	yes
Can be easily connected into runs	yes
Decorative lighting	yes
Functional lighting	yes
Mounting to drywall	yes
Wire out back of extrusion	yes

Profile OLIS-K
Ref. A04195

RELATED ACCESSORIES > COVERS

NAME	KEY FEATURES	MATERIAL	MATERIAL TRANSMITTANCE	COLOR	REF.
Cover BENCO-7	- indoor use - perfect for bent profiles	silicon	53 %	frosted	B17069F
Cover PIKO-7	- For indoor and outdoor applications - Perfectly diffusing - UV resistant - Thin line of light	PMMA	17 %	black	B17001B
			43 %	satin	B17001S

RELATED ACCESSORIES > END CAPS

NAME	MATERIAL	COLOR	REF.
End cap OLIS-K-90Z 	ABS	black	C24482L07
		gray	C24482C02
		white	C24482L10
End cap OLIS-K-90W 	ABS	black	C24483L07
		gray	C24483C02
		white	C24483L10
End cap OLIS-K-L 	ABS	black	C24484L07
		gray	C24484C02
		white	C24484L10
End cap OLIS-K-P 	ABS	black	C24485L07
		gray	C24485C02
		white	C24485L10

RELATED ACCESSORIES > RELATED LED > WHITE MONO

NAME	IP PROTECTION RATING	POWER CONSUMPTION	REF.
LED tape K-1490-24 14.9 W/m, IP20 NEW	20	14.9 W/m	K-27-1490-24 K-30-1490-24 K-35-1490-24 K-40-1490-24 K-50-1490-24
LED tape K-BT-1490-24 14.9 W/m, IP20 NEW	20	14.9 W/m	K-BT27-1490-24 K-BT30-1490-24 K-BT35-1490-24 K-BT40-1490-24 K-BT50-1490-24

RELATED ACCESSORIES > RELATED LED > RGB / RGB-W / RGB-CCT

NAME	KEY FEATURES	IP PROTECTION RATING	POWER CONSUMPTION	REF.
LED tape K-RGB-1560-24	- RGB	20	15.7 W/m	K-RGB-1560-24

RELATED ACCESSORIES > RELATED LED > ADJUSTABLE WHITE / DIM TO WARM

NAME	IP PROTECTION RATING	POWER CONSUMPTION	REF.
LED tape K-BT27T50-0910-24	20	9.1 W/m	K-BT27T50-0910-24