# Profile OPK-4

## Ref. A00370



### KEY FEATURES

- Wide range of accessories
- Easy maintenance
- Small bending radius
- Possibility of bending in the light plane

### APPLICATION

main and decorative lighting

### MOUNTING

recessed, using a dedicated mounting track

### ADDITIONAL INFORMATION

- disassembly from the mounting track using special plates
- smooth transition from a recessed into a suspended fixture
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

Standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)

### IP PROTECTION RATING

IP20 IP67

### MOUNTING METHOD


Suspended

Recessed with suspension function

### SPECIAL FEATURES

Possibility of bending

### TECHNICAL DRAWING




### AVAILABLE COLOURS

| LENGTH | REF |
|---|---|
| 1000 mm | A00370A_1 |
| 2005 mm | A00370A_2 |
| 3010 mm | A00370A_3 |

### TECHNICAL SPECIFICATIONS

| | |
|---|---|
| Material | aluminum |
| Color | silver anodized |
| Possible fixture IP | 20, 67 |
| Possible fixture shapes | linear, polygonal |
| Profile cross-section | rectangular |
| Width | 15.2 mm |
| Height | 13.5 mm |
| LED gluing width A | 12 mm |
| Max. number of LED strips A (8 mm wide) | 1 |
| Width of the glow | 11.2 mm |
| Max power of a single KLUŚ LED strip | 24 W/m |
| Possibility of obtaining a line of light | yes |
| Possibility of bending | yes |
| Radius of the light arc | yes |
| Inward | 300 mm |
| Outdoor | 300 mm |
| Downward light arc radius | yes |
| Down | 500 mm |
| Building type | Residential, Retail, HoReCa object |
| Facility zone | kitchen, under-cabinet / furniture |
| The cover is cut to the length of the profile | yes |
| Can be easily connected into runs | yes |
| Mounting to drywall | yes |
| Wire out back of extrusion | yes |

### RELATED ACCESSORIES > COVERS

| NAME | KEY FEATURES | MATERIAL | MATERIAL TRANSMITTANCE | COLOR | REF. |
|---|---|---|---|---|---|
| Cover BENCO-11 NEW | - For indoor and outdoor applications<br>- UV resistant | silicon | 50 % | frosted | B17215F |
| | | | 21 % | black | B17037B |
| Cover LIGER-11 | - hight light quality<br>- Ease of obtaining a line of light<br>- Perfectly diffusing<br>- For indoor and outdoor applications | PC | 59 % | satin | B17037S |

# Profile OPK-4
## Ref. A00370

| NAME | KEY FEATURES | MATERIAL | MATERIAL TRANSMITTANCE | COLOR | REF. |
|---|---|---|---|---|---|
| Cover HS-11  | - For indoor and outdoor applications<br>- UV resistant<br>- hight durability | PC | 59 % | frosted | B17208F |
| | | | 88 % | clear | B17208C |
| Cover KA-11  | - maximum brightness<br>- indoor use<br>- basic<br>- universal | PC | 67 % | frosted | B17064F |
| | | | 89 % | clear | B17064C |
| Cover KA-T-11  | - maximum brightness<br>- indoor use<br>- economic<br>- universal for basic applications | PVC | 54 % | frosted | B17179F |
| | | | 86 % | clear | B17179C |

### LINE OF LIGHT TABLE

| LED TAPE | LIGER-11 SATIN | LIGER-11 BLACK | HS-11 FROSTED | KA-11 FROSTED, |
|---|---|---|---|---|
| K-0360-24 | ✓ (1) | X | ✓ (1) | ✓ (1) |
| K-0720-24 | ✓ (1) | X | ✓ (1) | ✓ (1) |
| K-1080-24 | ✓ (1) | X | ✓ (1) | ✓ (1) |
| K-0500-24 | ✓ (1) | X | ✓ (1) | ✓ (1) |
| K-1000-24 | ✓ (1) | X | ✓ (1) | ✓ (1) |
| K-HD-0430-24 | ✓ (1) | ✓ (1) | ✓ (1) | ✓ (1) |
| K-1500-24 | ✓ (1) | X | ✓ (1) | ✓ (1) |
| K-CB-1000-24 | ✓ (1) | ✓ (1) | ✓ (1) | ✓ (1) |
| K-HD-0830-24 | ✓ (1) | ✓ (1) | ✓ (1) | ✓ (1) |
| K-HD-1260-24 | ✓ (1) | ✓ (1) | ✓ (1) | ✓ (1) |
| KWP-0360-24 | ✓ (1) | X | ✓ (1) | ✓ (1) |
| KWP-0720-24 | ✓ (1) | X | ✓ (1) | ✓ (1) |
| KWP-1080-24 | ✓ (1) | X | ✓ (1) | ✓ (1) |
| KWP-0500-24 | ✓ (1) | X | ✓ (1) | ✓ (1) |
| KWP-1000-24 | ✓ (1) | X | ✓ (1) | ✓ (1) |
| KWP-1500-24 | ✓ (1) | X | ✓ (1) | ✓ (1) |
| KWP-G-0500-24 | ✓ (1) | X | ✓ (1) | ✓ (1) |
| KWP-G-1000-24 | ✓ (1) | X | ✓ (1) | ✓ (1) |
| KWP-G-1500-24 | ✓ (1) | X | ✓ (1) | ✓ (1) |
| KWP-GHD-0430-24 | ✓ (1) | ✓ (1) | ✓ (1) | ✓ (1) |
| KWP-GHD-0830-24 | ✓ (1) | ✓ (1) | ✓ (1) | ✓ (1) |
| KWP-GHD-1260-24 | ✓ (1) | ✓ (1) | ✓ (1) | ✓ (1) |
| KWP-HD-0430-24 | ✓ (1) | ✓ (1) | ✓ (1) | ✓ (1) |
| KWP-HD-0830-24 | ✓ (1) | ✓ (1) | ✓ (1) | ✓ (1) |
| K-2400-24 | ✓ (1) | X | ✓ (1) | ✓ (1) |
| KWP-GDL-1229-24 | ✓ (1) | X | X | ✓ (1) |
| K-RGB-0700-24V | ✓ (1) | X | X | ✓ (1) |
| K-RGB-1200-24 | ✓ (1) | X | X | ✓ (1) |
| KWP-RGB-1200-24 | ✓ (1) | X | X | ✓ (1) |
| K-18D30-0960-24 | ✓ (1) | ✓ (1) | ✓ (1) | ✓ (1) |
| KWP-18D30-0960-24 | ✓ (1) | ✓ (1) | ✓ (1) | ✓ (1) |
| KWP-27T50-1440-24 | ✓ (1) | ✓ (1) | ✓ (1) | ✓ (1) |
| K-27T50-1440-24 | ✓ (1) | ✓ (1) | ✓ (1) | ✓ (1) |

Description

✓ - Line of Light for a number (X) of rows - Pixel free imaging
X - Visible Dotting from Diodes
HL - Centered Line of Light - Concentrated in middle
HL (X) - Centered Line of Light for a number (X) of rows - Concentrated in middle

Line of Light Guide



Clean Line of Light (Pixel free imaging)



Centered Line of Light



Visible Dotting from Diodes

# Profile OPK-4
## Ref. A00370

### RELATED ACCESSORIES > END CAPS

| NAME | MATERIAL | COLOR | REF. |
|---|---|---|---|
| End cap OPK-4  | ABS | gray | C24238C02 |

### RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > CANOPIES

| NAME | KEY FEATURES | MATERIAL | COLOR | REF. |
|---|---|---|---|---|
| Canopy Fi-60mm | - Convenient cable length adjustment, in the ZM system | steel | gray lacquered<br>white lacquered<br>black lacquered | C24540L01<br>C24540L10<br>C24540L07 |
| Canopy BOX-M70 | | aluminum | silver anodized<br>white lacquered<br>black anodized | C24541A<br>C24541L10<br>C24541A07 |
| Canopy BOX-M600 | | aluminum | silver anodized<br>white lacquered<br>black anodized | C24542A<br>C24542L10<br>C24542A07 |

### RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > MOUNTING BRACKETS

| NAME | KEY FEATURES | MATERIAL | COLOR | REF. |
|---|---|---|---|---|
| Fastener set NEO-ZM-3 | - 3 pieces for heavy fixtures | magnet | silver | C28105N00 |
| Fastener set NEO-ZM-4 | - 4 pieces for light fixtures | magnet | silver | C28106N00 |

### RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > FASTENERS AND HEADS FOR PROFILES

| NAME | KEY FEATURES | MATERIAL | COLOR | REF. |
|---|---|---|---|---|
| Fastener FI-8-LIN-ZM | - Installation in the ZM system | stainless steel, PA | silver<br>white<br>black | C28170N00<br>C28170L10<br>C28170L07 |
| Fastener FI-10-ZM-P, silver | - Cross mounting | stainless steel | silver | C28117N00 |
| Fastener UCHO-ZM | - Convenient mounting in the ZM system | aluminum | black anodized | C28192L07 |

### RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > CONDUCTIVE FASTENERS AND HEADS FOR PROFILES

| NAME | KEY FEATURES | MATERIAL | COLOR | REF. |
|---|---|---|---|---|
| Head BZP-ZO | | stainless steel | silver | 42214 |
| Fastener PUSZ-LIN-ZM | - Power supply cable - mounting in the ZM system | stainless steel, brass, nylon, aluminum<br>aluminum, brass, nylon<br>aluminum, brass, nylon | silver<br>white lacquered<br>black lacquered | C28160N00<br>C28160L10<br>C28160L07 |
| Fastener FI-8-LIN-ZMZ | - Power supply - mounting in the ZM system | stainless steel, steel, PA, EPDM<br>aluminum, PA, EPDM<br>aluminum, PA, EPDM | silver<br>white<br>black | C28171N00<br>C28171L10<br>C28171L07 |
| Fastener PUSZ-PRET-ZM | - Power supply cable - mounting in the ZM system | stainless steel, brass, nylon<br>aluminum, brass, nylon<br>aluminum, brass, nylon | silver<br>white<br>black | C28161N00<br>C28161L10<br>C28161L07 |
| Fastener PUSZ-LIN-MR | - Power supply cable - mounting in thin walls (from 1mm) | stainless steel, brass, nylon<br>aluminum, brass, nylon<br>aluminum, brass, nylon | silver<br>white lacquered<br>black lacquered | C28163N00<br>C28163L10<br>C28163L07 |

### RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > CONNECTORS

| NAME | KEY FEATURES | MATERIAL | COLOR | REF. |
|---|---|---|---|---|
| Connector ZM | | stainless steel | silver | 42716<br>42720<br>42728<br>C28070N00<br>C28071N00<br>C28072N00<br>C28073N00<br>C28074N00<br>C28075N00<br>C28243N00 |
| Connector ZM-G | | stainless steel | silver | 42304<br>42306<br>42308<br>42310<br>42324<br>42326<br>42328<br>42330<br>42332<br>42334<br>42336<br>42338 |
| Connector ZM-Y | | stainless steel | silver | C28082N00 |
| Connector ZM-X | | stainless steel | silver | C28079N00<br>C28080N00<br>C28081N00 |

# Profile OPK-4
## Ref. A00370

| NAME | KEY FEATURES | MATERIAL | COLOR | REF. |
|---|---|---|---|---|
| Connector ZM-T | | stainless steel | silver | C28076N00<br>C28077N00<br>C28078N00 |
| Connector ZM-PION | - for connecting profiles in the vertical plane | stainless steel | silver | 42314<br>42316<br>42320<br>42718<br>42719<br>C28084N00<br>C28085N00<br>C28086N00<br>C28087N00<br>C28088N00 |
| Connector ZM-MINI | | stainless steel | silver | C28083N00 |

### RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > SUSPENSION AND MOUNTING SETS

| NAME | KEY FEATURES | MATERIAL | COLOR | REF. |
|---|---|---|---|---|
| Fastener set W1 | | brass, stainless steel | silver | C28203N00 |
| Fastener set W6 | | stainless steel, brass | silver | C28205N00 |
| Fastener set W7 | | brass, stainless steel | silver | 42605 |
| Fastener set RD-1 | - Smooth cable adjustment, cable included | brass | silver glossy<br>silver satin<br>white lacquered<br>black lacquered | C28231P00<br>C28231P01<br>C28231L10<br>C28231L07 |
| Fastener set RG-1 | - Cable adjustment at the ceiling, cable included | brass | silver glossy<br>silver satin<br>white colored<br>black colored | C28230P00<br>C28230P01<br>C28230L10<br>C28230L07 |
| Fastener set RD-2 | - Smooth cable adjustment, angled mounting, cable included | brass | silver glossy<br>silver satin<br>white lacquered<br>black lacquered | C28232P00<br>C28232P01<br>C28232L10<br>C28232L07 |
| Fastener set RD-3 | - Smooth cable adjustment | brass | silver glossy<br>silver satin<br>white lacquered<br>black lacquered | C28233P00<br>C28233P01<br>C28233L10<br>C28233L07 |
| Fastener set RD-4 | - Smooth cable adjustment, angled mounting | brass | silver glossy<br>silver satin<br>white lacquered<br>black lacquered | C28234P00<br>C28234P01<br>C28234L10<br>C28234L07 |
| Fastener set FI-8-ZM-1 | - Power supply, for wall and drywall, in the ZM system | stainless steel, aluminum | silver<br>white lacquered<br>black lacquered | C28134N00<br>C28134L10<br>C28134L07 |
| Fastener set FI-8-ZM-2 | - Convenient cable length adjustment, in the ZM system | stainless steel, aluminum | silver<br>white lacquered<br>black lacquered | C28135N00<br>C28135L10<br>C28135L07 |
| Fastener set PUSZ-ZM-1 | - Power supply, for wall and drywall, in the ZM system | stainless steel, aluminum | silver<br>white lacquered<br>black lacquered | C28130N00<br>C28130L10<br>C28130L07 |
| Fastener set PUSZ-ZM-2 | - Convenient cable length adjustment, in the ZM system | stainless steel, aluminum | silver<br>white lacquered<br>black lacquered | C28131N00<br>C28131L10<br>C28131L07 |

### RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > LATCHES

| NAME | KEY FEATURES | MATERIAL | COLOR | REF. |
|---|---|---|---|---|
| Adapters set ZM-16 | - Connection of the ZM system with the 45-STN mount | PC | transparent | C29001C00 |

### RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > SURFACE SPRINGS

| NAME | MATERIAL | COLOR | REF. |
|---|---|---|---|
| Spring GP | stainless steel | silver | C24500N00 |

### RELATED ACCESSORIES > RELATED LED > HIGH EFFICACY

| NAME | KEY FEATURES | IP PROTECTION RATING | POWER CONSUMPTION | REF. |
|---|---|---|---|---|
| LED tape K-VHE-0480-24 | - universal for basic applications<br>- high efficacy<br>- High Efficacy | 20 | 4.8 W/m | K-VHE27-0480-24<br>K-VHE30-0480-24<br>K-VHE40-0480-24 |
| LED tape K-VHE-0960-24 | - universal for basic applications<br>- high efficacy<br>- High Efficacy | 20 | 9.6 W/m | K-VHE40-0960-24 |
| LED tape K-VHE-1440-24 | - universal for basic applications<br>- high efficacy<br>- High Efficacy | 20 | 14.4 W/m | K-VHE27-1440-24<br>K-VHE30-1440-24<br>K-VHE40-1440-24<br>K-VHE50-1440-24 |

# Profile OPK-4
## Ref. A00370

### RELATED ACCESSORIES > RELATED LED > CRI 95+

| NAME | KEY FEATURES | IP PROTECTION RATING | POWER CONSUMPTION | REF. |
|---|---|---|---|---|
| LED tape K-CR-0480-24 | - universal for basic applications<br>- CRI over 95 | 20 | 4.8 W/m | K-CR27-0480-24<br>K-CR30-0480-24<br>K-CR40-0480-24 |
| LED tape K-CR-0960-24 | - universal for basic applications<br>- CRI over 95 | 20 | 9.6 W/m | K-CR40-0960-24 |
| LED tape K-CR-1440-24 | - universal for basic applications<br>- CRI over 95 | 20 | 14.4 W/m | K-CR27-1440-24<br>K-CR30-1440-24<br>K-CR40-1440-24 |
| LED tape KWP-CR-0480-24 | - universal for basic applications<br>- CRI over 95 | 65 | 4.8 W/m | KWP-CR27-0480-24<br>KWP-CR30-0480-24<br>KWP-CR35-0480-24<br>KWP-CR40-0480-24<br>KWP-CR50-0480-24 |
| LED tape KWP-CR-0960-24 | - universal for basic applications<br>- CRI over 95 | 65 | 9.6 W/m | KWP-CR40-0960-24<br>KWP-CR50-0960-24 |

### RELATED ACCESSORIES > RELATED LED > WHITE MONO

| NAME | KEY FEATURES | IP PROTECTION RATING | POWER CONSUMPTION | REF. |
|---|---|---|---|---|
| LED tape K-0360-24 3.6 W/m, IP20 NEW | | 20 | 3.6 W/m | K-27-0360-24<br>K-30-0360-24<br>K-35-0360-24<br>K-40-0360-24<br>K-50-0360-24 |
| LED tape K-HD-0430-24 4.3 W/m, IP20 NEW | | 20 | 4.3 W/m | K-HD18-0430-24<br>K-HD22-0430-24<br>K-HD27-0430-24<br>K-HD30-0430-24<br>K-HD35-0430-24<br>K-HD40-0430-24<br>K-HD50-0430-24 |
| LED tape K-0480-24 | - universal for basic applications | 20 | 4.8 W/m | K-27-0480-24<br>K-30-0480-24<br>K-35-0480-24<br>K-50-0480-24 |
| LED tape K-HD-0480-24 | - high LED density<br>- Ease of obtaining a line of light | 20 | 4.8 W/m | K-HD27-0480-24<br>K-HD40-0480-24 |
| LED tape K-0500-24 5 W/m, IP20 NEW | - Thin line of light<br>- longitudinal bending<br>- Flexibility for bending | 20 | 5 W/m | K-30-0500-24<br>K-40-0500-24 |
| LED tape K-0720-24 7.2 W/m, IP20 NEW | | 20 | 7.2 W/m | K-27-0720-24<br>K-30-0720-24<br>K-35-0720-24<br>K-40-0720-24<br>K-50-0720-24 |
| LED tape K-HD-0830-24 8.3 W/m, IP20 NEW | | 20 | 8.3 W/m | K-HD27-0830-24<br>K-HD30-0830-24<br>K-HD35-0830-24<br>K-HD40-0830-24<br>K-HD50-0830-24 |
| LED tape K-0960-24 | - universal for basic applications | 20 | 9.6 W/m | K-30-0960-24<br>K-40-0960-24<br>K-40-0960-24-R30 |
| LED tape K-HD-0960-24 | - high LED density<br>- Ease of obtaining a line of light | 20 | 9.6 W/m | K-HD40-0960-24 |
| LED tape K-1000-24 10 W/m, IP20 NEW | | 20 | 10 W/m | K-30-1000-24<br>K-40-1000-24 |
| LED tape K-CB-1000-24 10 W/m, IP20 NEW | | 20 | 10 W/m | K-CB27-1000-24<br>K-CB30-1000-24<br>K-CB40-1000-24<br>K-CB50-1000-24 |
| LED tape K-1080-24 10.8 W/m, IP20 NEW | | 20 | 10.8 W/m | K-27-1080-24<br>K-30-1080-24<br>K-35-1080-24<br>K-40-1080-24<br>K-50-1080-24 |
| LED tape K-HD-1260-24 12.6 W/m, IP20 NEW | | 20 | 12.6 W/m | K-HD27-1260-24<br>K-HD30-1260-24<br>K-HD35-1260-24<br>K-HD40-1260-24<br>K-HD50-1260-24 |
| LED tape K-1440-24 | - universal for basic applications | 20 | 14.4 W/m | K-27-1440-24<br>K-40-1440-24<br>K-40-1440-24-R30 |
| LED tape K-HD-1440-24 | - high LED density<br>- Ease of obtaining a line of light | 20 | 14.4 W/m | K-HD40-1440-24 |
| LED tape K-1500-24 15 W/m, IP20 NEW | | 20 | 15 W/m | K-30-1500-24<br>K-35-1500-24<br>K-40-1500-24 |
| LED tape K-2300-24 | - high power | 20 | 23 W/m | K-30-2300-24<br>K-40-2300-24 |
| LED tape K-2400-24 | - high power | 20 | 24 W/m | K-27-2400-24<br>K-30-2400-24<br>K-35-2400-24<br>K-40-2400-24<br>K-50-2400-24 |

# Profile OPK-4
## Ref. A00370

| NAME | KEY FEATURES | IP PROTECTION RATING | POWER CONSUMPTION | REF. |
|---|---|---|---|---|
| LED tape KWP-0360-24 3.6 W/m, IP65 NEW | | 65 | 3.6 W/m | KWP-27-0360-24<br>KWP-30-0360-24<br>KWP-35-0360-24<br>KWP-40-0360-24<br>KWP-50-0360-24 |
| LED tape KWP-GHD-0430-24 4.3 W/m, IP65 NEW | | 65 | 4.3 W/m | KWP-GHD27-0430-24<br>KWP-GHD30-0430-24<br>KWP-GHD35-0430-24<br>KWP-GHD40-0430-24<br>KWP-GHD50-0430-24 |
| LED tape KWP-HD-0430-24 4.3 W/m, IP65 NEW | | 65 | 4.3 W/m | KWP-HD27-0430-24<br>KWP-HD30-0430-24<br>KWP-HD35-0430-24<br>KWP-HD40-0430-24<br>KWP-HD50-0430-24 |
| LED tape KWP-0480-24 | - universal for basic applications | 65 | 4.8 W/m | KWP-27-0480-24<br>KWP-30-0480-24<br>KWP-50-0480-24 |
| LED tape KWP-GHD-0480-24 | - high LED density<br>- Ease of obtaining a line of light | 65 | 4.8 W/m | KWP-GHD27-0480-24 |
| LED tape KWP-0500-24 5 W/m, IP65 NEW | | 65 | 5 W/m | KWP-30-0500-24<br>KWP-40-0500-24 |
| LED tape KWP-G-0500-24 5 W/m, IP65 NEW | | 65 | 5 W/m | KWP-G30-0500-24<br>KWP-G40-0500-24 |
| LED tape KWP-0720-24 7.2 W/m, IP65 NEW | | 65 | 7.2 W/m | KWP-27-0720-24<br>KWP-30-0720-24<br>KWP-35-0720-24<br>KWP-40-0720-24<br>KWP-50-0720-24 |
| LED tape KWP-GHD-0830-24 8.3 W/m, IP65 NEW | | 65 | 8.3 W/m | KWP-GHD27-0830-24<br>KWP-GHD30-0830-24<br>KWP-GHD35-0830-24<br>KWP-GHD40-0830-24<br>KWP-GHD50-0830-24 |
| LED tape KWP-HD-0830-24 8.3 W/m, IP65 NEW | | 65 | 8.3 W/m | KWP-HD27-0830-24<br>KWP-HD30-0830-24<br>KWP-HD35-0830-24<br>KWP-HD40-0830-24<br>KWP-HD50-0830-24 |
| LED tape KWP-0960-24 | - universal for basic applications | 65 | 9.6 W/m | KWP-40-0960-24 |
| LED tape KWP-1000-24 10 W/m, IP65 NEW | | 65 | 10 W/m | KWP-30-1000-24<br>KWP-40-1000-24 |
| LED tape KWP-G-1000-24 10 W/m, IP65 NEW | | 65 | 10 W/m | KWP-G30-1000-24<br>KWP-G40-1000-24 |
| LED tape KWP-1080-24 10.8 W/m, IP65 NEW | | 65 | 10.8 W/m | KWP-27-1080-24<br>KWP-30-1080-24<br>KWP-35-1080-24<br>KWP-40-1080-24<br>KWP-50-1080-24 |
| LED tape KWP-GHD-1260-24 12.6 W/m, IP65 NEW | | 65 | 12.6 W/m | KWP-GHD27-1260-24<br>KWP-GHD30-1260-24<br>KWP-GHD35-1260-24<br>KWP-GHD40-1260-24<br>KWP-GHD50-1260-24 |
| LED tape KWP-HD-1260-24 12.6 W/m, IP65 | | 65 | 12.6 W/m | KWP-HD27-1260-24<br>KWP-HD30-1260-24<br>KWP-HD35-1260-24<br>KWP-HD40-1260-24<br>KWP-HD50-1260-24 |
| LED tape KWP-1440-24 | - universal for basic applications | 65 | 14.4 W/m | KWP-27-1440-24<br>KWP-40-1440-24 |
| LED tape KWP-1500-24 15 W/m, IP65 NEW | | 65 | 15 W/m | KWP-30-1500-24<br>KWP-40-1500-24 |
| LED tape KWP-G-1500-24 15 W/m, IP65 NEW | | 65 | 15 W/m | KWP-G30-1500-24<br>KWP-G40-1500-24 |

### RELATED ACCESSORIES > RELATED LED > RGB / RGB-W / RGB-CCT

| NAME | KEY FEATURES | IP PROTECTION RATING | POWER CONSUMPTION | REF. |
|---|---|---|---|---|
| LED tape K-RGB-0700-24V | - RGB | 20 | 7 W/m | K-RGB-0700-24V |
| LED tape K-RGB-1200-24 | - RGB | 20 | 12 W/m | K-RGB-1200-24 |
| LED tape K-RGBW-1530-24 15.3 W/m, IP20 NEW | - RGBW<br>- high LED density | 20 | 15.3 W/m | K-RGB30-1530-24<br>K-RGB40-1530-24 |
| LED tape KWP-RGB-0700-24 | - RGB | 65 | 7 W/m | KWP-RGB-0700-24 |
| LED tape KWP-RGB-1200-24 | - RGB | 65 | 12 W/m | KWP-RGB-1200-24 |
| LED tape KWP-GRGB-1530-24 15.3 W/m, IP65 NEW | - RGBW<br>- high LED density | 65 | 15.3 W/m | KWP-GRGB30-1530-24<br>KWP-GRGB40-1530-24 |
| LED tape KWP-RGBW-1530-24 15.3 W/m, IP65 NEW | - RGBW<br>- high LED density | 65 | 15.3 W/m | KWP-RGB30-1530-24<br>KWP-RGB40-1530-24 |

# Profile OPK-4
## Ref. A00370

### RELATED ACCESSORIES > RELATED LED > ADJUSTABLE WHITE / DIM TO WARM

| NAME | KEY FEATURES | IP PROTECTION RATING | POWER CONSUMPTION | REF. |
|---|---|---|---|---|
| LED tape K-18D30-0960-24 | - Dim To Warm LED Tape | 20 | 9.6 W/m | K-18D30-0960-24 |
| LED tape K-27T50-1440-24 | - RGB+Tunable White | 20 | 14.4 W/m | K-27T50-1440-24 |
| LED tape KWP-18D30-0960-24 | - Dim To Warm LED Tape | 65 | 9.6 W/m | KWP-18D30-0960-24 |
| LED tape KWP-27T50-1440-24 | | 65 | 14.4 W/m | KWP-27T50-1440-24 |

### RELATED ACCESSORIES > ELECTRONICS > SWITCHES

| NAME | KEY FEATURES | IP PROTECTION RATING | REF. |
|---|---|---|---|
| Proximity switch UNI-11 | - touchless switch<br>- width 11mm | 20 | E61603 |
| Proximity switch UNI-P | - touchless switch<br>- width only 7mm<br>- factory pre-soldered wires | 20 | E61580 |
| Switch MICRO 96W IP20 | - push button switch<br>- factory pre-soldered wires<br>- version with logo | 20 | 1491LOGO |
| Switch MICRO 96W IP20 | - push button switch<br>- factory pre-soldered wires<br>- version with logo | 20 | 1576LOGO |
| Proximity switch UNI-11P | - touchless switch<br>- width 11mm<br>- factory pre-soldered wires | 20 | E61604 |
| Proximity switch UNI | - touchless switch<br>- width only 7mm | 20 | E61579 |