
Canopy BOX-KR600

Ref. C24667



TECHNICAL DRAWING





- Completed set of items
- Compartment for driver and electrical components
- Aesthetic masking for electrical components
- Easy maintenance
- Simple and convenient installation of the luminaire by one installer

APPLICATION

- mounting of power supplies and electronic components

MOUNTING

- recessed, by bending out the spring arm
- easy installation and deinstallation of pressed-in fixtures

ADDITIONAL INFORMATION

- the power supply can be secured inside the profile using dedicated accessories

TECHNICAL SPECIFICATIONS

Material	**aluminum**
IP protection rating	**20**
Length	**600 mm**
Width	**86 mm**
Height	**46.9 mm**
Lifting capacity	**2.8 kg**

Color	Ref
■ black lacquered	**C24667L07**
□ white lacquered	**C24667L10**

SAMPLE PROJECTS





Canopy BOX-KR600
Ref. C24667

RELATED PROFILES > SUSPENDED



Profile INTER-PLUS
A18078



Profile PIKO-DUO
A00022



Profile 3035
A18039



Profile 4050
A18050



Profile GIZA-DUO-LL
A02162



Profile GLAZA-DUO
A03059



Profile GLAZA-LL
A02627



Profile JAZ
A08547



Profile JAZ-DUO
A00788



Profile OLEK
A08505



Profile PDS-ZMG
A01418



Profile PIKO-ZM
A01168

RELATED PROFILES > SURFACE MOUNTED



Profile GIZA
A05556



Profile GIZA-LL
A00758



Profile MICRO-PLUS
A02966



Profile PDS-4-PLUS
A01263




Profile PIKO-O
A01167

Canopy BOX-KR600

Ref. C24667



Profile REGULOR
A18068



Profile SEPOD
A06593

RELATED PROFILES > RECESSED WITH SUSPENSION FUNCTION



Profile OPK-4
A00370



Profile PDS-ZM-PLUS
A02056