Profile ROGER
Ref. A06885



KEY FEATURES

- For installation on wall corners
- Space provided for an electrical connector
- Colored covers, including phosphorescent ones
- Possibility of continuing the light line in the corner

APPLICATION

warning lighting and corner protection

MOUNTING

to the corner using glue

ADDITIONAL INFORMATION

- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

Standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)

IP PROTECTION RATING

IP20 | IP65

MOUNTING METHOD

Surface mounted

TECHNICAL DRAWING



AVAILABLE COLOURS

COLOR	LENGTH	REF
black anodized	1000 mm	A06885A07_1
	2000 mm	A06885A07_2
	3000 mm	A06885A07_3
silver anodized	1000 mm	A06885A_1
	2000 mm	A06885A_2
	3000 mm	A06885A_3

TECHNICAL SPECIFICATIONS

Material	aluminum
Possible fixture IP	20, 65
Possible fixture shapes	linear
Width	31.1 mm
Height	31.1 mm
LED gluing width A	4 mm
Max. number of LED strips A (8 mm wide)	0
Width of the glow	4 mm
Max power of a single KLUŚ LED strip	4.8 W/m
Building type	Commercial, Retail, Outdoor
Facility zone	parking / garage / driveway, decorative
The cover is cut to the length of the profile	yes
Can be easily connected into runs	yes
Warning lighting	yes
Wire out back of extrusion	yes

RELATED ACCESSORIES > COVERS

NAME	KEY FEATURES	MATERIAL	COLOR	REF.
Cover BENCO-5	- warning function - creates a line of light - indoor use	silicon	grey	B17002Y
			orange	B17002R
			phosphorescent	B17002N

RELATED ACCESSORIES > END CAPS

NAME	MATERIAL	COLOR	REF.
	ABS	black	C20015C07
		gray	C20015C02