

## Exit & Emergency

### Evade Emergency Light Series

- LED Thermoplastic Emergency Unit
- Compact, Contemporary Appearance
- Fully Adjustable LED Heads
- Wall or Ceiling Mount
- Remote Capacity Option
- LED Life-Cycle Exceeding 10 Years

### Specifications

#### Description

The Evade Emergency Unit Series offers a quality emergency lighting solution along the path of egress for hallway, stairwells, and other Life Safety applications. The compact design makes it ideal to mount on walls or ceilings illuminating the path of egress for a minimum of 90 minutes after a power loss. Available with remote capacity.

#### Electrical

- 120 / 277 VAC, 50/60Hz input
- Emergency test button and battery charging indicator
- Long-life maintenance free NiCad battery
- 24 Hour recharge time
- Low voltage battery protection circuit
- Overload/short circuit protection
- (2) Two 1.0W lamp heads delivering 240 lumens
- 5700K CCT
- 10°C - 40°C operating temperature

#### Certifications

- UL924 Damp Location listed
- NFPA 101 and NFPA 70
- CEC T20 compliant



#### Construction & Mounting

- Rugged, injection-molded, flame retardant, high temperature, white thermoplastic housing
- Designed for quick installation
- Suitable for wall and ceiling mount
- Universal J-box mounting pattern on back plate

# Evade Emergency Light Series

## Ordering Information

Product SKU	Product Code	Product Description
95008	EV-EME-R	Evade Emergency Unit
95009	EV-EME-R-RC	Evade Emergency with Remote Capacity
Remote Heads		
95010	EV-RH-1-IND	Evade Single Indoor Round Remote Head
95011	EV-RH-2-IND	Evade Dual Indoor Round Remote Head
97012	EV2-RH-1-OUT-RD	Evade Single Outdoor Round Remote Head
97013	EV2-RH-2-OUT-RD	Evade Double Outdoor Round Remote Head

## Specifications Table

	EV-EME-R	EV-EME-R-RC
Input Current	80mA Max	100mA Max
Input Wattage	0.8W	1W
Battery	Ni-Cad	Ni-Cad
Lamp Head Wattage	1W Ea (2W Total)	
Lamp Head Lumens	240 LM	220 LM
Recharge Time	24 Hours	
Input Voltage	120 or 277 VAC	
Output Voltage	3.6VDC	
Frequency	50/60Hz	
Housing	Injection-Molded Thermoplastic Housing	
Testing Function	Manual Push to Test Button	
Operating Temperature	10°C to 40°C	
Listings & Compliance	UL 924, CEC Title 20, NFPA 70 & NFPA 101	
Environment	Damp Location Listed	
Warranty*	2 Year	

\*All life safety equipment, including emergency lighting for path of egress must be maintained, serviced, and tested in accordance with all National Fire Protection Association (NFPA) and local codes. Failure to perform the required maintenance, service, or testing could jeopardize the safety of occupants and will void all warranties.

## Evade Emergency Light Series

### Remote Head Specifications

Product SKU	Product Code	Input Voltage	Input Wattage	Lumens
95010	EV-RH-1-IND	3.6VDC	.8W	85
95011	EV-RH-2-IND	3.6VDC	1.5W	170
97012	EV2-RH-1-OUT-RD	3-12VDC	.8W	75
97013	EV-RH-2-OUT-RD	3-12VDC	1.5W	150

### Remote Head

#### EV-RH-1-IND

- Single, white, indoor remote head
- Suitable for damp location. UL, cUL listed



#### EV-RH-2-IND

- Double, white, Indoor remote head
- Suitable for damp location. UL, cUL listed



#### EV2-RH-1-OUT-RD

- Single, white, indoor remote head
- Suitable for damp location. UL, cUL listed



#### EV2-RH-2-OUT-RD

- Double, white, indoor remote head
- Suitable for damp location. UL, cUL listed



### Dimensions

