

Item Bundle - 125 A Load Center with Compartment for Optional Wiring Devices, 8-Breaker Spaces

Item T4000R4



PRODUCT DESCRIPTION

Can be used as a Load Center only, or add mechanisms or wiring devices for complete control systems.

FEATURES

- ▶ Eight breaker spaces
- ▶ Reduces installation costs
- ▶ All-in-one electrical load center eliminates the need for additional service panels
- ▶ Accepts any combination of PF1000M Series, P1403ME, P1353ME, P4043ME, P4243ME, T100M Series or RC2000M Series mechanisms
- ▶ Fully compatible with all electrical requirements for pool/spa installations
- ▶ Load center dead front has four knockouts for switches or GFCIs (Note: T4000R4 has one knockout)
- ▶ Wiring devices may be installed in these Load Centers with the use of Standoffs, sold separately

APPLICATIONS

- ▶ Distribution/Control Panel

TECHNICAL DATA

General

| | |
|--------------------------------|--|
| Model Number | T4000R4 |
| Description | 125 A Load Center with Compartment for Optional Wiring Devices, 8-Breaker Spaces |
| UPC Code | 078275043077 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | MEXICO |
| Warranty Period | 1-Year limited |

Mechanical Specifications

| | |
|-----------------------------|----------------|
| Number of Breaker Knockouts | 8 |
| Enclosure Type | 3R Beige metal |

Dimensions

| | |
|-----------------------------------|--|
| Product Dimensions (H x W x D) in | 20.875 x 12.875 x 4.75 in |
| Knockout Dimensions Bottom | (5) 1/2" - 3/4", (4) 1/2", (2) 3/4" - 1", 1 1/4" |
| Knockout Dimensions Back | (4) 1/2" - 3/4", (2) 3/4" - 1" |
| Knockout Dimensions Left | (2) 1/2" - 3/4" |
| Knockout Dimensions Right | (1) 1 3/4" x 2 3/4" |

Material Specifications

| | |
|-------|-------|
| Color | Beige |
|-------|-------|

Load Ratings

| | |
|------------|--|
| Mechanisms | Load Center with Compartment for Optional Wiring Devices |
|------------|--|

Electrical Specifications

| | |
|---------------------------------------|---|
| Number of Receptacle/Switch Knockouts | 1 |
|---------------------------------------|---|

Packaging

| | |
|---------------------------------------|----------------|
| Shipping Weight (lbs) | 19.36 |
| Unit Carton Dimensions (H x W x L) in | 6 x 14 x 22 in |

Environmental Specifications

| | |
|-------------------------|--------------------------------------|
| Temperature (operation) | -40 °F to 130 °F / (-40 °C to 54 °C) |
|-------------------------|--------------------------------------|

Standards and Certifications

| | |
|--|--------------|
| CSA Certification | cCSAus |
| Other Certifications and Compatibilities | Green Energy |
| California Proposition 65 | None |
| RoHS Certification | X |

ACCESSORIES



156T1978A
Extra/replacement trippers 1 ON and 1 OFF



21T166A
Spacer-Standoff, 3" long - 2 pack



21T156A
Spacer-Standoff, 3" long - 4 pack



124T1952
Insulator for Double-Pole Time Switch (T103, T104, T105, T173, T174, T175, T176, T185, WH40)



WP1000C
Plastic In-Use Weatherproof Cover, Single-Gang, Vrt, 2.25" Clear



22T338GR
Mounting Bracket for Intermatic Standardized Timer Mechanisms

22T713
Bracket Painted

8--00008A
Latch-Enclosure

124--00140A
Pool Panel Breaker Base, 8-pole

156PA13715A
1" Nonmetallic Hub Kit

24T5796-WWH
Painted Plate Filler

6T2496A-WWH
Cover Assembly Painted 12x20 T40000 Series