

20' H-TRACK SYSTEM - SURFACE MOUNT KIT LR43849, LR43850

TRACK SUSPENSION SYSTEM INSTALLATION STEPS:

1. PREPARE:

GATHER TOOLS (WRENCH, SCREWDRIVER, ETC.) AND CHECK ALL PARTS.

2. INSTALL TRACK:

SECURE THE TRACK WITH BOLTS AT THE DESIRED LOCATION.

3. ATTACH TO CEILING:

DRILL HOLES AND INSERT TOGGLE BOLTS INTO THE CEILING.

ATTACH THE CANOPY CABLE HOLDER TO THE TOGGLE BOLTS.

4. CONNECT CABLE:

SECURE THE TOP END OF THE GALVANIZED CABLE TO THE CANOPY CABLE HOLDER.

THREAD THE CABLE THROUGH THE QUICK-RELEASE BUTTON AND ATTACH TO THE TRACK CABLE HOLDER.

5. ADJUST AND SECURE:

FIX THE TRACK CABLE HOLDER ONTO THE TRACK AND USE STRAIN RELIEF.

ADJUST CABLE LENGTH USING THE QUICK-RELEASE BUTTON TO LEVEL THE TRACK.

6. FINAL CHECK:

ENSURE ALL PARTS ARE SECURE AND THE TRACK IS LEVEL.

CLEAN UP THE INSTALLATION AREA.

