

The all new Exitronix Tempo Pro family of LED emergency exit luminaires provide a more complete, compact, powerful light offering with a higher performance than most currently on the market.

Model: _____ Date: _____
Accessories: _____
Job Name: _____ Type: _____

FEATURES

- 3.6 volt compatible
- 4.5" diameter round mounting plate for 3" or 4" standard hole pattern
- Lamp and mounting plate combination is approximately 2" deep
- SMD 1W or 2W LED per lamp head
- Narrow or wide distributions available
- Fully adjustable
- Standard finish: Black or White
- UL 924 and cUL Certified
- Suitable for damp locations



WARRANTY

Any component that fails due to manufacturers defect is guaranteed for 3 years. The warranty does not cover physical damage, abuse or acts of God. See the full Exitronix warranty document for detailed information. (Terms and conditions apply)

ON-CENTER SPACING (Using multiple units mounted at a typical 7.5 foot height, 85/50/20 reflectance)

Model	# of LED Lamps	3' Path, 6' Corridor	6' Path, 6' Corridor
2RL52-LO	2	10'	9'
2RL52-W-LO	2	18'	14'
2RL52-W	2	25'	21'
2RL52	2	18'	17'

See the [Remote Lamp Compatibility Chart](#) for a complete list of compatible fixtures.

ORDERING INFORMATION Example: RL52-WH

Series	Finish	Distribution	LED Lamp
RL52 = Single	BL = Black	[BLANK] = Narrow	[BLANK] = 2W LED Lamp
2RL52 = Double	WH = White	W = Wide	LO ¹ = 1W LED Lamp

