

Shallow Pro Puck™ Ordering Guide



Description:

Made from die cast aluminum body, these low profile, high output LED lights give you design freedom and offer an energy efficient, maintenance free alternative to traditional under cabinet lighting. Designed to be recessed or surface mounted these Pro Pucks would be the perfect choice for accent, task or general lighting, to highlight your fireplace, countertops, backsplash, curios cabinets and book shelves, to light dark corners and eliminate shadows. The perfect choice for your home or office, these Pro Puck fixtures have up to 207.4 lumens per fixture and are available in Anodized Black, Brushed Aluminum and Flat White colours. LED Driver sold separately.

Features:

- 3.3 Watts per LED.
- Available in 3000°K and 5500°K CCT.
- Up to 207.4 lumens per fixture.
- Minimum CRI of 80.
- 104° beam angles.
- 24V DC constant voltage.
- Dimmable when used with dimming driver.
- Can be surface or recessed mounted.
- Available with DC 2.1 connectors or bare wires for hardwire applications.
- Available in Anodized Black, Brushed Aluminum and Flat White.
- cETLus listed.
- Approved for damp locations.



Ordering Guide:

	Wattage	Colour Temperature	Voltage	Wiring	Fixture Colour
PRO-1S					
	3 : 3 Watt	30 : 3000°K 55 : 5500°K	24 : 24 volts	H : Hardwire	ABK : Anodized Black AL : Brushed Aluminum FWH : Flat White



Class 2 drivers sold separately. See page 2 for driver options.



Liteline Corporation
Info@liteline.com
www.liteline.com

8 Abacus Road, Brampton
Ontario, Canada L6T 5B7



416-996-1856
1-866-730-7704



905-794-1990
1-888-738-9736

Non Dimming Class II

Plug-In Drivers

**LED-DVR-24V-24W**

LED 24V, 24W Plug-in Driver. Requires power feed.

LED-DVR-24V-36W

LED 24V, 36W Plug-in Driver. Requires power feed.

LED-DVR-24V-60W

LED 24V, 60W Plug-in Driver. Requires power feed.

**LED-HWB-DC21-6-PF**

DC 2.1 to bare leads power feed. Required for all drivers with DC 2.1 jack. Maximum 10' to first fixture.

Hardwire Drivers

**LED-HWB-24V-24W**

LED 24V, 24W Hard wire Box LED Driver. Requires power feed.

LED-HWB-24V-36W

LED 24V, 36W Hard wire Box LED Driver. Requires power feed.

LED-HWB-24V-60W

LED 24V, 60W Hard wire Box LED Driver. Requires power feed.

**LED-HWB-DC21-6-PF**

DC 2.1 to bare leads power feed. Required for all drivers with DC 2.1 jack. Maximum 10' to first fixture.

Dimming Class II

Electronic Hardwire Drivers

**LED-HWBDIM2-24-40**

40W LED dimmable hardwire driver, 2-wire, 24V, powered by Lutron®. Requires power feed.

LED-HWBDIM3-24-40

40W LED dimmable hardwire driver, 3-wire, 24V, powered by Lutron®. Requires power feed.

**LED-HWB-DC21-6-PF**

DC 2.1 to bare leads power feed. Required for all drivers with DC 2.1 jack. Maximum 10' to first fixture.

Magnetic Indoor/Outdoor Hardwire Drivers

**HWB-DIM-MDC-24V-20W**

20W LED magnetic dimmable hardwire driver, 24V.

HWB-DIM-MDC-24V-40W

40W LED magnetic dimmable hardwire driver, 24V.

HWB-DIM-MDC-24V-60W

60W LED magnetic dimmable hardwire driver, 24V.

**HWB-DIM-MDC-24V-96W**

96W LED magnetic dimmable hardwire driver, 24V.

**HWB-DIM-MDC-24V-192W**

192W LED magnetic dimmable hardwire driver, 24V.

Accessories

**LED-DIM 24V**

LED touch dimmer, 24V (non dimmable driver required).

**LED-SP-4**

Optional harness for up to 4 runs, 24V.