



## SLM6WS

SLIMLED<sup>™</sup>

6" Square LED Slim Profile Recessed Retrofit, 12W,  
Wet Location  
Recess Lighting

Job Information	
Project Name	Type
Location	
Quantity	Date
Contact/Phone	
Notes	

### Features

#### Body

Durable airtight aluminum body with UV stable paint and white PMMA diffuser lens for low glare. Includes silicone gasket for wet location applications.

#### LED Characteristics

This general application light fixture features a 12 watt LED module that maintains uniform intensity producing up to 860 lumens; with a typical CRI of 90. Available in 3000 K or 4000 K color temperature.

#### Dimming

100%-10% dimming capability. This fixture is compatible with industry standard TRIAC/ELV dimmers (contact factory for listing of compatible dimmers).

#### Beam Spread

The fixture lens provides 120° beam spread.

#### Mounting

Includes two spring loaded clips to attach to any ceiling material. The slim profile allows to be mounted under joists or duct work.

#### LED Driver

Extruded aluminum hardwire box with 300mA dimmable class II electronic LED driver with 100-135V AC input. Includes an 18" plenum rated FT6 wire with DC 2.1 connector from driver to fixture.

#### Quick Connect push-in terminals

Three "Quick connect" push-in terminals for fast and easy wiring.

#### Operating Temperature

-20°C~40°C (-4°F~104°F)

#### Environment

- Suitable for wet locations.
- Suitable for insulated ceiling applications.


#### SPECIFICATION

Application	Ceiling Recess Mount
Approved Location	Wet / Insulated Ceilings
Beam Angle	120°
CCT	3000 K / 4000 K
Certification	cETLus
Class II	Yes
Color	BK / BN / WH
CRI	90
Dimming	Yes
Dimming Tech	TRIAC/ELV
Energy Star	Yes
Hole Cut	0 6 3/16" (157mm)
Input	100-135V AC, 60Hz, 0.11A
LM79	Yes
LM80	Yes
Lumens	Up to 840 / 860 (based on WH)
Lumens per Watt	Up to 70 / 71 (based on WH)
Power Factor	>0.9
Projected Life	70% @ 50,000 hrs
Warranty	Lifetime
Wattage	12W



### Description

The SLM6WS is a 12 watt 6" slim profile light fixture for recess retrofit application. It is a high-performance, easy to install downlight solution that offers good light output, energy-efficiency and streamlined design. Suitable for wet locations.



**Notes:** Accessories are sold separately. For additional options please consult your Liteline representative.  
Due to our continued efforts to improve our products, product specifications are subject to change without notice.

### Ordering Guide

Color Temperature	Driver Options	Trim Finish
SLM6WS - <input type="text"/>	- <input type="text"/>	- <input type="text"/>
30 : 3000 K	Leave blank for standard 120V driver	<b>BK</b> : Black
40 : 4000 K	<b>E</b> : Lutron Hi-Lume® 1% (EcoSystem®)	<b>BN</b> : Brushed Nickel
	<b>EM</b> : Emergency Backup, 120-277V, 0-10V	<b>WH</b> : White
	<b>C</b> : 120-347V, 0-10V	

## Accessories

---

**SLM-60-FC**

60" Flexible connector, for use with SlimLED fixtures.

**P-6020**

6 $\frac{1}{4}$ " Round pre-mounting plate with driver attachment clip, for 6" SlimLED wet location fixtures.

**P-NCMK-1**

Hanger bar kit. Includes hanger bars, brackets and screws.

**VBE-1**

Vapour barrier extender. For use in new construction applications.

**VBE-3**

Vapour barrier extender. For use in remodel applications.

**VBE-4**

Vapour barrier extender. For use in remodel applications.