

Electronic Timer Control - 24-Hour Electronic Time Control, 3-Circuit, Freeze Protection Probe, Type 3R Metal Enclosure

Item PE153F



PRODUCT DESCRIPTION

This multipurpose 24-hour control is capable of automatically switching loads according to a preset daily schedule. Controls single- and two-speed pumps and cleaner/booster pumps. Three ON/OFF events per circuit per day.

FEATURES

- ▶ Controls single- and two-speed pumps and cleaner/booster pumps
- ▶ Three ON/OFF events per circuit per day
- ▶ Seven preprogrammed modes
- ▶ Freeze and heater protection
- ▶ LCD readout
- ▶ Multivoltage input and output
- ▶ Countdown and override features enable programs to be overridden and automatically resumed without requiring the user to reprogram the system

APPLICATIONS

- ▶ Heater Thermostat Control
- ▶ Motor Control
- ▶ Pump Control

TECHNICAL DATA

General	
Model Number	PE153F
Description	24-Hour Electronic Time Control, 3-Circuit, Freeze Protection Probe, Type 3R Metal Enclosure
UPC Code	078275092365
Brand	Intermatic
Country of Origin (Intermatic)	CANADA
Warranty Period	1-Year limited
Control Specifications	
Maximum ON/OFF Operations	3
Operation Mode	24 hour
Mechanical Specifications	
Enclosure Type	Outdoor type 3R metal
Dimensions	
Product Dimensions (H x W x D) in	9.375 x 5.5 x 3.625 in
Material Specifications	
Color	Black
Communication Method	
Has WiFi	No
Load Ratings	

Tungsten Range(s)	5 A, 120/240 VAC, 50/60 Hz
Resistive Load Ratings Ranges	17 A, 120/240 VAC, 50/60 Hz
Motor Load Ratings Ranges	80 LRA @ 120/240 VAC, 50/60 Hz; 17 FLA @ 120/240 VAC, 50/60 Hz

Electrical Specifications

Voltage Selection Type	Multi Voltage
Input Voltage Range(s)	120/240 VAC, 50/60 Hz
Number of Circuits	3
Switch Type	3-SPST

Packaging

Shipping Weight (lbs)	4.151
Unit Carton Dimensions (H x W x L) in	4.253 x 7.253 x 11.623 in

Standards and Certifications

CSA Certification	cCSAus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	DEHP
RoHS Certification	X