

SLIMLED™ DTW

Indirect Recessed Light - Dim to Warm



Dim to Warm LED Fixtures

The next piece of the LED Lighting puzzle

Today's LEDs can be used in virtually any lighting application with greatly improved colour quality and warm CCTs at high CRI levels. When fixtures are being used on a dimmer, as the light level drops, today's LEDs maintain the same colour temperature that they exhibit at full power. Incandescent and halogen lamps dim to a warmer CCT at lower levels.

Dim-to-warm technology is now available in LED lighting fixtures they can deliver 3000°K CCT light at full power yet smoothly reduce the CCT to the 2000°K range at the lowest dimming light levels. This technology was designed to mimic the incandescent and halogen lamps that dim to a warmer colour temperature using the same low-cost triac dimmers.

Features

- LED technology fits anywhere you need general light source
- No Recessed fixture required
- Slim 1½" thickness design
- I.C. rated for direct contact with insulation
- Perfect solution where joists or duct work would normally prevent recessed installation
- Ideal for drop ceilings
- Easy to install yourself
- Lifetime Warranty
- Damp location rated for soffit applications
- Dim to warm, 3000°K ~ 2000°K
- Integrated LED fixtures
- Available in white

SIZE & SHAPE OPTIONS



SLM4I / ROUND



SLM4IS / SQUARE

4" / 9W / 120V / DTW / Up to 500 lumens



SLM6I / ROUND



SLM6IS / SQUARE

6" / 12W / 120V / DTW / Up to 800 lumens



Dimmable



Indoor



3000°K~2000°K
Colour Temp



Damp
Location



80
CRI



140°
Beam Angle



IC Rated



For more information on Lifetime Warranty program, please visit www.liteline.com/goldlabel



LITELINE CORPORATION | www.liteline.com
P 416-996-1856 | 1-866-730-7704
F 905-709-5255 | 1-888-738-9736

Ordering Guide



Part #	Description	UPC	Case Qty.	Master Qty.
INDLED™ Dim to Warm Kits				
4" Round Kit, 9W, Up to 500 Lumens				
SLM4I-3020DTW-WH	4" Indirect LED fixture and driver, round, 9W, 120V, 3000°K~2000°K, white	771250108654	12	48
4" Square Kit, 9W, Up to 500 Lumens				
SLM4IS-3020DTW-WH	4" Indirect LED fixture and driver, square, 9W, 120V, 3000°K~2000°K, white	771250108692	12	48
6" Round Kit, 12W, Up to 800 Lumens				
SLM6I-3020DTW-WH	6" Indirect LED fixture and driver, round, 12W, 120V, 3000°K~2000°K, white	771250108791	12	24
6" Square Kit, 12W, Up to 800 Lumens				
SLM6IS-3020DTW-WH	6" Indirect LED fixture and driver, square, 12W, 120V, 3000°K~2000°K, white	771250108838	12	24
Accessories				
SLM-60-FC	60" Flexible connector, for use with SlimLED series fixtures.	771250976079	12	48
P-4020	4" Pre-mounting plate, for use with SLM4I series.	771250977397	–	50
P-4020S	4" Pre-mounting plate, for use with SLM4IS series.	771250977410	–	50
P-6020	6" Pre-mounting plate, for use with SLM6I series.	771250976093	–	30
P-6020S	6" Pre-mounting plate, for use with SLM6IS series.	771250977403	–	30
P-NCMK-1	New construction mounting kit, includes hanger bars, brackets and screws.	771250224316	–	64
VBE-1	Vapour barrier extender for 4" & 6" fixtures. For use in new construction applications.	771250094942	–	50
VBE-2	Vapour barrier extender for 4" fixtures. For use in remodel applications.	771250971388	–	50
VBE-3	Vapour barrier extender for 4" & 6" fixtures. For use in remodel applications.	771250976086	–	50
VBE-4	Vapour barrier extender for 4" & 6" fixtures. For use in remodel applications.	771250190895	–	50

SLIMLED™ DTW

Indirect Low Glare Reflector Recessed Light - Dim to Warm



Dim to Warm LED Fixtures

The next piece of the LED Lighting puzzle

Today's LEDs can be used in virtually any lighting application with greatly improved colour quality and warm CCTs at high CRI levels. When fixtures are being used on a dimmer, as the light level drops, today's LEDs maintain the same colour temperature that they exhibit at full power. Incandescent and halogen lamps dim to a warmer CCT at lower levels.

Dim-to-warm technology is now available in LED lighting fixtures they can deliver 3000°K CCT light at full power yet smoothly reduce the CCT to the 2000°K range at the lowest dimming light levels. This technology was designed to mimic the incandescent and halogen lamps that dim to a warmer colour temperature using the same low-cost triac dimmers.


Features

- LED technology fits anywhere you need general light source
- No Recessed fixture required
- Slim 1½" thickness design
- I.C. rated for direct contact with insulation
- Perfect solution where joists or duct work would normally prevent recessed installation
- Low glare reflector
- Ideal for drop ceilings
- Easy to install yourself
- Lifetime Warranty
- Damp location rated for soffit applications
- Dim to warm, 3000°K ~ 2000°K
- Integrated LED fixtures
- Available in white

SIZE & SHAPE OPTIONS



SLM4I / ROUND



SLM4IS / SQUARE

4" / 9W / 120V / DTW / Up to 450 lumens



SLM6I / ROUND



SLM6IS / SQUARE

6" / 12W / 120V / DTW / Up to 750 lumens



Dimmable



Indoor



3000°K~2000°K
Colour Temp



Damp
Location



80
CRI
Colour
Accuracy



120°
Beam Angle



IC Rated



For more information on Lifetime Warranty program, please visit www.liteline.com/goldlabel



LITELINE CORPORATION | www.liteline.com
P 416-996-1856 | 1-866-730-7704
F 905-709-5255 | 1-888-738-9736

Ordering Guide



Part #	Description	UPC	Case Qty.	Master Qty.
INDLED™ LGR Dim to Warm Kit				
4" Round Kit, 9W, Up to 450 Lumens				
SLM4I-3020DTW-L-WH	4" Indirect low glare reflector LED fixture and driver, round, 9W, 120V, 3000°K~2000°K, white	771250108647	12	48
4" Square Kit, 9W, Up to 450 Lumens				
SLM4IS-3020DTW-L-WH	4" Indirect low glare reflector LED fixture and driver, square, 9W, 120V, 3000°K~2000°K, white	771250108685	12	48
6" Round Kit, 12W, Up to 750 Lumens				
SLM6I-3020DTW-L-WH	6" Indirect low glare reflector LED fixture and driver, round, 12W, 120V, 3000°K~2000°K, white	771250108784	12	24
6" Square Kit, 12W, Up to 750 Lumens				
SLM6IS-3020DTW-L-WH	6" Indirect low glare reflector LED fixture and driver, square, 12W, 120V, 3000°K~2000°K, white	771250108821	12	24
Accessories				
SLM-60-FC	60" Flexible connector, for use with SlimLED series fixtures.	771250976079	12	48
P-4020	4" Pre-mounting plate, for use with SLM4I series.	771250977397	–	50
P-4020S	4" Pre-mounting plate, for use with SLM4IS series.	771250977410	–	50
P-6020	6" Pre-mounting plate, for use with SLM6I series.	771250976093	–	30
P-6020S	6" Pre-mounting plate, for use with SLM6IS series.	771250977403	–	30
P-NCMK-1	New construction mounting kit, includes hanger bars, brackets and screws.	771250224316	–	64
VBE-1	Vapour barrier extender for 4" & 6" fixtures. For use in new construction applications.	771250094942	–	50
VBE-2	Vapour barrier extender for 4" fixtures. For use in remodel applications.	771250971388	–	50
VBE-3	Vapour barrier extender for 4" & 6" fixtures. For use in remodel applications.	771250976086	–	50
VBE-4	Vapour barrier extender for 4" & 6" fixtures. For use in remodel applications.	771250190895	–	50