

PROJECT			
TYPE			

<u>VOLTAGE</u>

# OUTDOOR WALL/CEILING FIXTURE S772WF

### **OUTDOOR DECORATIVE MARLEX®**



**SPECIFICATIONS** 

• Wall or Ceiling Mount

Mounting Hardware Included

• Frosted Polycarbonate Diffuser

• Minimum Starting Temp -20°F

• UL Listed for Wet Locations


Composite Construction

WH WHITE

• Black or White

Non-Corrosive

BK BLACK



Wave Lighting's S772WF adds a contemporary look to any outdoor space. Wave Lighting's S772WF is designed for wall or ceiling applications and mounting hardware is included. Options include photocell.













# LED SOURCE OPTIONS

## **LIGHTWAVE LED - LR/LT**

- 120V, 50/60 Hz
- AC Driver-On-Board Array
- Estimated 50,000 Hrs  $L_{70}$
- Low Flicker (LT models)
- Surge Supression
- Dimmable (see compatible dimmer list)
- High Efficacy LED Light Source
- 3000K or 4000K CCT 80 or 90CRI
- 5 Year Warranty
- Energy Star

## **LED MULTI-VOLT SYSTEM - L22**

- 120-277V, 50/60Hz
- Estimated 50,000 Hrs  $L_{70}$
- 4000K CCT, 80CRI
- 3 Year Warranty

#### **E26 MEDIUM BASE - LE26**

- 120V, 50/60Hz
- "Screw-In" Medium Base A19/E26 LED Lamp
- Estimated 15,000 Hrs L<sub>70</sub>
- Low Flicker (3K models)
- Dimmable (see compatible dimmer list)
- 3000K CCT 90CRI or 4000K CCT 80CRI
- 3 Year Warranty
- Energy Star

# GUIDE CODE: S772WF-LR12W-WH-PC

#### **CALL FOR PHOTOMETRIC INFORMATION**

ITEM#	DIFFUSER	LIGHT SOURCE	сст	COLOR	OPTIONS
S772W POLYCARBONATE F-Frosted Ribbon		E26 MEDIUM BASE	<b>C</b> -4K	<b>BK</b> -Black	PC-Photocell
	POLYCARBONATE BACK PAN (1) 60W MAX Medium Base LE26-9.5W 800lm (E26 LED Lamp) + *	<b>W</b> -3K	WH-White	(120V Lightwave LED only)	
		120V LIGHTWAVE LED			
		ALUMINUM BACK PAN LR12-13W 1000lm 80CRI ★ LR15-15W 1400lm 80CRI ★ LR22-23W 1900lm 80CRI ★ LT12-12W 1040lm 90CRI LT15-16W 1400lm 90CRI LT22-24W 2020lm 90CRI			
		120-277V MULTI-VOLT LED			
		<b>L22-</b> 22W 1824Im	4K		

**<sup>+</sup>** Lamp included. **★**Energy Star qualified product.