



DALS LIGHTING

Canada
80, de la Seigneurie blvd., E.
Blainville, Quebec J7C 4N1

U.S.A.
4383, NW 124th Ave.,
Coral Springs, Florida 33065

877.430.1818
info@dals.com
dals.com

MODEL GMB2-CC

NAME Scope

2" LED Round Gimbal, 5CCT

When searching for lighting flexibility, look no further than our 4" LED directional downlight. With a powerful lumen output and the ability to shine your light with a 360 degree rotation, this product will meet your every need.


PROJECT

TYPE


DATE

QTY

NOTES



LIGHT DISTRIBUTION



*Lumen output measured at 3000k

QUICK SPECS

Size	2"
Watts (W)	8
Delivered lumens*	750
CRI	90
Voltage (v)	120
Beam angle (deg)	40
Cut hole size (in)	2-1/4"
FT rating	FT6
UGR	19.7
Binning	3 SDCM
LED model	COB
Color temperature	2700K/3000K/3500K/4000K/5000K
Certifications	ETL, FCC, ICES, JA8/T24, ES, IC, ASTM E283-04

ELECTRICAL DETAILS

Environment	Wet
Location	Indoor/Outdoor
Operating temp. (° C)	-20 to 40
IP rating	IP65
Input voltage (V)	100-135
Output voltage (V)	33.8
Output current (mA)	180
Power factor (%)	90
Driver type	Constant current
THD	17%
Lifespan (hrs)	50 000

ORDERING GUIDE

GMB2-CC	-	Voltage	-	Finish
		BLANK - 120v, TRIAC		WH - White
		V - 120-277-347V, 0-10v		BK - Black

CONSTRUCTION

Lens material	Acrylic
Optic type	Optical lens
Finish type	Matte
Housing material	Aluminum

WHAT'S IN THE BOX	ACCESSORIES	ADAPTORS
LED recessed fixture	RFP-GMB2	REC-CC-EXT8FT
Junction box	Drilling plate	96" extension cord for recessed fixtures
3x Push-in wire connectors		
Non-Metallic Connector 1/2in		REC-CC-EXT20FT
Instruction sheet		240" extension cord for recessed fixtures

RECOMMENDED DIMMER LIST*

BRAND	MODEL	DIMMER SPECS	DIMMING RANGE %		MAX LOAD (units)
			MIN	MAX	
Dals	SM-DIMSW Smart Dimmer*	Triac, 250W LED/CFL	5	100	31
Lutron	DVCL-153PR-WH-C*	Triac, 150 W Dimmable CFL/LED	8	100	19
Lutron	CTCL-153PDH-WH-C*	Triac, 150 W Dimmable CFL/LED	8	100	19
Lutron	DVLV-600P-BL	Magnetic Low Voltage, 450W	10	100	56
Lutron	MACL-153MRHW-WHC*	Triac, 150 W Dimmable CFL/LED	0	100	19
Lutron	DVELV-300P-WH	300W electronic low voltage dimmer	11	100	38
Lutron	MA-PRO-WH*	ELV, 250W LED/CFL	0	100	31
Lutron	Caseta PD-6WCL-WH-R-C*	Triac, 300W Dimmable CFL/LED	7	100	19
Lutron	Caseta PD-5NE-WH-C*	ELV, LED—up to 250 W	2	100	31
Lutron	Caseta PD-10NXD-WH*	Triac, LED—up to 250 W	0	100	31
Leviton	DSM10-1LZ*	Triac, 450W Dimmable CFL/LED	1	100	56
Leviton	PL06-10Z*	Triac, 150 W Dimmable CFL/LED	11	100	19
Leviton	DSL06-1LZ*	Triac, 300 W Dimmable CFL/LED	11	100	38
Leviton	D26HD-742-1RW*	Triac, 300W LED/CFL	0	100	38
Legrand	ADTP703TUM4*	Triac, 450W Dimmable CFL/LED	0	100	56
Control 4	C4-APD120-WH	ELV, 120W LED	0	100	15
Control 4	C4-FPD120-WH	Triac, 200W LED	0	100	25
Commercial Electric	HPDA311CWB*	Triac, 150W LED & CFL	0	100	19
TP-Link	HS220*	Triac, 150 W, Dimmable LED (MLV)	1	100	19

V version 0-10v dimming

Lutron	DVSTV (0–10 V Controls)*	960W, 8A, 120–277 V	1	94	120
Leviton	IP710-DLZ(0–10 V Controls)	1200VA, 10A LED, 120-277V	0	100	150
Leviton	ZS057-30Z(0–10 V Controls)	1388VA, 4A , 347V	0	100	100
Lutron	Vive PowPak Dimming ModuleRMJS-8T-D	960VA, 8A, 120-277V	0	100	120

*With Low-End Adjustment Feature. Minimal buzzing noise may occur with some dimmers.

WARRANTY

DALS offers a 5-year warranty from the date of purchase which covers repairs or replacement of defective parts of the housing, optics, and electronics. To contact DALS customer service call 1-877-430-1818 or send an e-mail to info@dals.com.