

GTX

Surface & Recessed Mount Extrusion

The ultimate extrusion compatible with all Trulux tape light, the GTX is the perfect blend of utility and sleek design. Utilize the medium height profile to eliminate most dotting regardless of the light source while providing evenly diffused lighting. Need double the light output but limited on mounting space? No worries, as the GTX allows for side by side tape light installation for tape light widths 12mm or less.

- Surface or recessed mounting capable
- Allows for side by side tape light installation for double the output
- Frosted lens protects lights source while evenly diffusing light
- Anodized aluminum provides excellent heat dissipation
- Field cuttable extrusion and lens
- Compatible with 10-12mm wide tape light with HD connectors

Available Finishes



Anodized Aluminum

Compatible Tape Light

- Single Color (10mm) + HD Connector
- Tunable CCT (10mm) + HD Connector
- RGB (10mm) + HD Connector
- RGBW (12mm) / RGBTW (12mm) + HD Connector

PROJECT:
TYPE:
LOCATION:
CATALOG NUMBER:



GTX ORDERING INFORMATION

ITEM NUMBER	DESCRIPTION
PE-GTX-1M	1M GTX Aluminum Extrusion
PE-GTX-LENS-1M	1M Frosted Polycarbonate UV Lens
PE-GTX-END	GTX End Cap
PE-SLOTLENS-3M	3M Frosted Polycarbonate Lens (Special Order)
PE-SLOTLENS-6M	6M Frosted Polycarbonate Lens (Special Order)
PE-180-CON	180° Connector
PE-90-CON	90° Connector

GTX ACCESSORIES



PE-180-CON



PE-90-CON

GTX DIMENSIONS

