

Plug-In Timer - Digital Astronomic Landscape Timer

Item DT200LT



PRODUCT DESCRIPTION

Digital 24-hour landscape timer with DST, rated for use in low voltage transformers up to 1200W featuring ON programming at Dusk or predetermined time and OFF at Dawn or predetermined time.

FEATURES

- ▶ For use in low voltage transformers up to 1200 W
- ▶ Program ON at dusk or specific time
- ▶ Program OFF at dawn or specific time
- ▶ Automatic Daylight Savings Time adjustment
- ▶ Intermatic Linesync timing technology for years of accurate timing

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Outdoor Lighting Control
- ▶ Landscape Water Control

TECHNICAL DATA

General

Model Number	DT200LT
Description	Digital Astronomic Landscape Timer
UPC Code	078275148901
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
TARIC HS Code	9107.00.00

Control Specifications

Minimum ON/OFF Times	1 min
Maximum ON/OFF Operations	2
Operation Features	Astronomic
Operation Mode	24 hour
Backup Type	Battery
Battery Type	LR44
Mechanism Type	Digital/Electrical
Application Compatibilities	Incandescent; Fluorescent; HID; LED; CFL
Chemical Composition of the Battery Cell	Alkaline
Number of Batteries Included	2
Battery Weight (grams)	1.95
Number of Lithium-ion Cells in Battery	N/A
Number of Lithium Metal Cells in Battery	N/A
Watt Hours Per Battery	0.225
Lithium Content (grams) in Battery	N/A

Mechanical Specifications

Number of Plugs	2
-----------------	---

Plug Configurations	5-15
---------------------	------

Dimensions

Product Dimensions (H x W x D) in	3.188 x 3.307 x 2.224 in
-----------------------------------	--------------------------

Material Specifications

Color	Black
-------	-------

Load Ratings

Incandescent Load Ratings	1000 W, 120 VAC, 60 Hz
---------------------------	------------------------

Inductive	12 A, 120 VAC, 60 Hz
-----------	----------------------

Motor Load Ratings Ranges	1/2 HP, 120 VAC, 60 Hz
---------------------------	------------------------

Electrical Specifications

Input Voltage Range(s)	120 VAC, 60 Hz
------------------------	----------------

Packaging

Shipping Weight (lbs)	0.509
-----------------------	-------

Unit Carton Dimensions (H x W x L) in	3.375 x 3.375 x 3.062 in
---------------------------------------	--------------------------

Environmental Specifications

Usage Environments	Outdoor
--------------------	---------

Standards and Certifications

UL Certification	cULus
------------------	-------

Other Certifications and Compatibilities	Title 20; Green Energy
--	------------------------

California Proposition 65	None
---------------------------	------

RoHS Certification	X
--------------------	---