

GLOBE POST TOP FIXTURE 2001/8001

OUTDOOR DECORATIVE



Wave Lighting's Residential Globe Fixture is ideal for any outdoor patio or walkway. This fixture is available in incandescent with A19 LED lamp option and is easily relamped via 2 screws in fitter. Wave Lighting's 12" Dia. Globe fits on a 3" diameter pole (sold separately) mounting hardware is included.



LED SOURCE OPTIONS

LIGHTWAVE LED - LR/LT

- 120V, 50/60 Hz
- AC Driver-On-Board Array
- Estimated 50,000 Hrs L₇₀
- Low Flicker (LT models)
- Surge Supression
- Dimmable (see compatible dimmer list)
- High Efficacy LED Light Source
- 3000K or 4000K CCT 80 or 90 CRI
- 5 Year Warranty

E26 MEDIUM BASE - LE26

- 120V, 50/60Hz
- "Screw-In" Medium Base A19/E26 LED Lamp
- Estimated 15,000 Hrs L₇₀
- Low Flicker (3K models)
- Dimmable (see compatible dimmer list)
- 3000K CCT 90CRI or 4000K CCT 80CRI
- 3 Year Warranty

E39 RETRO-FIT LED - LC

- 120-277V, 50/60Hz
- 250W Metal Halide Equivalent Lamp
- E39 Mogul Base Socket
- Estimated 50,000 Hrs L₇₀
- Surge Supression
- Available in 4000K CCT 80CRI
- Type 3, Type 5, or Dark Sky Distribution
- 5 Year Warranty

SPECIFICATIONS

- Cast Aluminum or Polycarbonate Fitters
- Black, White, or Bronze (Aluminum Only)
- Post Mount Only
- Polycarbonate or Acrylic Globe Diffuser
- Clear, Opal, Smoke, Clear Prism, or Frost Diffuser Options
- UL Listed For Wet Locations
- Non-Corrosive



GUIDE CODE: 2001CL-LR12C-BP

CALL FOR PHOTOMETRIC INFORMATION

ITEM #	LENS	LIGHT SOURCE	CCT	FITTER MATERIAL	OPTIONS
2001*-12" DIA	POLYCARBONATE Opal CL-Clear SM-Smoke PR-Clear Prismatic	E26 MEDIUM BASE	C-4K W-3K	CAST ALUMINUM Black WH-White BZ-Bronze	MG-E39 Mogul Socket
		(1) 75W MAX Medium Base LE26-9.5W 800lm (E26 LED Lamp) †			
8001-12" DIA	ACRYLIC Opal CL-Clear FA-Frost SM-Smoke PR-Clear Prismatic	120V LIGHTWAVE LED	C-4K	POLYCARBONATE BP-Black WP-White	
		LR12-13W 1000lm 80CRI LT12-12W 1040lm 90CRI			
		E39 RETRO-FIT LED 120-277V			
		LC5-24W 3120lm, Type 5 † LC3-20W 3000lm, Type 3 † LCD-24W 2400lm, Dark Sky †			

† Lamp included. *Not available in clear prismatic.