LUXRITE®

Life is bright™

LED LINEAR STRIP
LINEAR - 5CCT & 4 WATTAGE SELECT
24", 36", 48", 96" - HIGH OUTPUT - SENSOR READY

DLC LISTED PREMIUM

UL CERTIFIED

24"
LR25360

13W	17W	21W	26W

EMERGENCY OPTION ALSO AVAILABLE

LR25360+EM BATTERY BACKUP

36"
LR25362

13W	17W	21W	26W

EMERGENCY OPTION ALSO AVAILABLE

LR25362+EM BATTERY BACKUP

48"
LR25363

21W	26W	34W	40W

LR25364

40W	47W	53W	68W

EMERGENCY OPTION ALSO AVAILABLE

LR25363+EM
LR25364+EM BATTERY BACKUP

96"
LR25365

40W	53W	68W	80W

LR25366

80W	94W	106W	136W

EMERGENCY OPTION ALSO AVAILABLE

LR25365+EM
LR25366+EM BATTERY BACKUP



*SENSOR READY (INTEGRAL)

*SENSOR SOLD SEPARATELY

AVAILABLE ACCESSORIES
*SOLD SEPARATELY



LR25367
4' REFLECTOR



LR25371
4' REFLECTOR STRAIGHT

LR25369
SUSPENSION MOUNT KIT

LR25374
10' SUSPENSION MOUNT KIT

LR25370
CHAIN KIT

LR25368
STRAIGHT CONNECTOR

LR25359
ANGLE CONNECTOR

LR25378
4' WIRE GUARD

CRI 80

COLOR SELECTABLE
3000K | 3500K | 4000K | 5000K | 6500K

WATTAGE SELECTABLE
4 OPTIONS

BATTERY BACKUP
*OPTION AVAILABLE

SENSOR READY

DIMMABLE
0-10V

120-277V

HIGH OUTPUT

DAMP LOCATION RATED

5 YEAR WARRANTY

ELECTRICAL

		MODEL	DESCRIPTION	INPUT VOLTS	POWER	LUMEN	EFFICACY	LIFETIME	EMERGENCY TIME
24"	VERY HIGH OUTPUT	LR25360	LED24/LINEAR/5CCT/4WO/UNV/D/VHO	120-277V	13	2,000	150	0-10V	
					17	2,500			
					21	3,000			
					26	4,000			
		LR25360+EM	LED24/LINEAR/5CCT/4WO/UNV/D/VHO+EM	120-277V	13	2,000	150	0-10V	90 MINS
					17	2,500			
					21	3,000			
					26	4,000			
36"	HIGH OUTPUT	LR25362	LED36/LINEAR/5CCT/4WO/UNV/D/HO	120-277V	13	2,000	150	0-10V	
					17	2,600			
					21	3,200			
					26	4,000			
		LR25362+EM	LED36/LINEAR/5CCT/4WO/UNV/D/HO+EM	120-277V	13	2,000	150	0-10V	90 MINS
					17	2,600			
					21	3,200			
					26	4,000			
48"	HIGH OUTPUT	LR25363	LED48/LINEAR/5CCT/4WO/UNV/D/HO	120-277V	21	3,300	150	0-10V	
					26	4,100			
					34	5,200			
					40	6,300			
		LR25363+EM	LED48/LINEAR/5CCT/4WO/UNV/D/HO+EM	120-277V	21	3,300	150	0-10V	90 MINS
					26	4,100			
					34	5,200			
					40	6,300			
	VERY HIGH OUTPUT	LR25364	LED48/LINEAR/5CCT/4WO/UNV/D/VHO	120-277V	40	6,000	150	0-10V	
					47	7,000			
					53	8,000			
					68	10,000			
		LR25364+EM	LED48/LINEAR/5CCT/4WO/UNV/D/VHO+EM	120-277V	40	6,000	150	0-10V	90 MINS
					47	7,000			
					53	8,000			
					68	10,000			
96"	HIGH OUTPUT	LR25365	LED96/LINEAR/5CCT/4WO/UNV/D/HO	120-277V	40	6,600	150	0-10V	
					53	8,200			
					68	10,400			
					80	12,600			
		LR23565+EM	LED96/LINEAR/5CCT/4WO/UNV/D/HO+EM	120-277V	40	6,600	150	0-10V	90 MINS
					53	8,200			
					68	10,400			
					80	12,600			
	VERY HIGH OUTPUT	LR25366	LED96/LINEAR/5CCT/4WO/UNV/D/VHO	120-277V	80	13,000	150	0-10V	
					94	15,000			
					106	16,000			
					136	20,000			
		LR25366+EM	LED96/LINEAR/5CCT/4WO/UNV/D/VHO+EM	120-277V	80	13,000	150	0-10V	90 MINS
					94	15,000			
					106	16,000			
					136	20,000			

PHOTOMETRIC

MODEL	DESCRIPTION	COLOR SELECTABLE (CCT)	FLOOD°	CRI	UL	DLC LISTED
LR25360	LED24/LINEAR/5CCT/4WO/UNV/D/VHO	3000K/3500K/4000K/5000K/6500K	110°	80	YES	S-RF7TVD STANDARD
LR25360+EM	LED24/LINEAR/5CCT/4WO/UNV/D/VHO+EM	3000K/3500K/4000K/5000K/6500K	110°	80	YES	S-RF7TVD STANDARD
LR25362	LED36/LINEAR/5CCT/4WO/UNV/D/HO	3000K/3500K/4000K/5000K/6500K	110°	80	YES	
LR25362+EM	LED36/LINEAR/5CCT/4WO/UNV/D/HO+EM	3000K/3500K/4000K/5000K/6500K	110°	80	YES	
LR25363	LED48/LINEAR/5CCT/4WO/UNV/D/HO	3000K/3500K/4000K/5000K/6500K	110°	80	YES	S-68LP81 PREMIUM
LR25363+EM	LED48/LINEAR/5CCT/4WO/UNV/D/HO+EM	3000K/3500K/4000K/5000K/6500K	110°	80	YES	S-68LP81 PREMIUM
LR25364	LED48/LINEAR/5CCT/4WO/UNV/D/VHO	3000K/3500K/4000K/5000K/6500K	110°	80	YES	S-1XP54S PREMIUM
LR25364+EM	LED48/LINEAR/5CCT/4WO/UNV/D/VHO+EM	3000K/3500K/4000K/5000K/6500K	110°	80	YES	S-1XP54S PREMIUM
LR25365	LED96/LINEAR/5CCT/4WO/UNV/D/HO	3000K/3500K/4000K/5000K/6500K	110°	80	YES	S-9X2RN8 PREMIUM
LR25365+EM	LED96/LINEAR/5CCT/4WO/UNV/D/HO+EM	3000K/3500K/4000K/5000K/6500K	110°	80	YES	S-9X2RN8 PREMIUM
LR25366	LED96/LINEAR/5CCT/4WO/UNV/D/VHO	3000K/3500K/4000K/5000K/6500K	110°	80	YES	S-VBB1DX PREMIUM
LR25366+EM	LED96/LINEAR/5CCT/4WO/UNV/D/VHO+EM	3000K/3500K/4000K/5000K/6500K	110°	80	YES	S-VBB1DX PREMIUM

ACCESSORIES

*SOLD SEPARATELY



LR25367
4' REFLECTOR



LR25371
4' REFLECTOR STRAIGHT

INSTALLED ON LR25366 OR LR25365 (*NEEDS 2 PCS)

LR25368
STRAIGHT CONNECTOR

LR25369
SUSPENSION MOUNT KIT

LR25374
10' SUSPENSION MOUNT KIT

LR25370
CHAIN KIT

LR25359
ANGLE CONNECTOR



LR25378
4' WIRE GUARD

SENSOR COMPATIBILITY

LR25375
AUDIO JACK
STANDARD SENSOR



WORKS WITH:
LR25189
MW BI-LEVEL
REMOTE

ADJUSTABLE
DIP SWITCH ON
THE BACK

SENSOR* READY



*SENSOR SOLD SEPARATELY

SENSOR INSTALLED



MOTION SENSOR - SPECIFICATIONS

MODEL	DESCRIPTION	POWER	INPUT VOLTS	DIMMING	INSTALL HEIGHT	DETECTION RANGE	DETECTION ANGLE
LR25375	LEDSNS/A/LINEAR/MW/BILEVEL/1P	<0.5W	10-15V	0-10V	13FT	22.9FT	30-150°

AMBIENT TEMPERATURE: -13°F ~ 140°F

SENSOR PARAMETER	Detection Area	Remote Control Only: 25%/50%/75%/100%
	Holdtime	Remote control Options：5s/ 30s/ 1min/ 3min/ 5min/ 10min/ 20min/ 30min DIP switch: 5s/5min
	Daylight Threshold	Remote control: Disable/400Lux/350Lux/300Lux/250Lux/200Lux/120Lux/ 80Lux/50Lux/30Lux/10Lux/2Lux DIP Switch: Disable/50Lux
	Standby Dimming Level	Remote control: 10%/20%/30%/50%　DIP Switch: 5min/+∞
	Standby Period	Remote control Options：0s/ 10s/ 30s/ 1min/ 5min/ 10min/ 30min/ 60min/+∞ DIP Switch: 5min/+∞
	Dusk/Dawn Sensing/ Photocell	Daylight threshold as 30lux/ 50lux/ 80lux/ 120lux/ 200Lux/ 250Lux/300Lux/ 350Lux/ 400Lux Standby period as +∞ ; Standby dimming level as 10%/20%/30%
	Daylight Harvesting	1. Adjust "daylight" value higher than 50lux 2. Preset "standby period" 0S 3. Press MW/PIR button 3 times till MW/PIR icons both blicking on LCD screen, daylight harvesting function enabled. (With BLE verison, press DH button, daylight harvesting function enabled.)

SENSOR COMPATIBILITY

LR25372
AUDIO JACK
STANDARD SENSOR



WORKS WITH:
LR25189
MW BI-LEVEL
REMOTE

SENSOR* READY



*SENSOR SOLD SEPARATELY

SENSOR INSTALLED



MOTION SENSOR - SPECIFICATIONS

MODEL	DESCRIPTION	POWER	INPUT VOLTS	DIMMING	INSTALL HEIGHT	DETECTION RANGE	DETECTION ANGLE
LR25372	LEDSNS/LINEAR/MW/BILEVEL/1P	<0.3W	12V	0-10V	13.12FT	9FT	30-150°

AMBIENT TEMPERATURE: -13°F ~ 140°F

SENSOR PARAMETER	Detection Area	25%/50%/75%/100%
	Holdtime	Remote control Options：5s/ 30s/ 1min/ 3min/ 5min/ 10min/ 20min/ 30min APP Control Options：5s/ 30s/ 1min/ 2min/ 3min/ 5min/ 10min/ 15min/ 20min/ 25min/30min/ 45min/ 60min/ 90min/ 120min
	Daylight Threshold	Disable/400Lux/350Lux/300Lux/250Lux/200Lux/120Lux/ 80Lux/50Lux/30Lux/10Lux/2Lux
	Standby Dimming Level	10%/20%/30%/50%
	Standby Period	Remote control Options：0s/ 10s/ 30s/ 1min/ 5min/ 10min/ 30min/ 60min/+∞ APP Control Options：0s/5s/30s/1min/2min/3min/5min/10min/15min/20min/ 25min/30min/45min/60min/+∞
	Dusk/Dawn Sensing/ Photocell	Daylight threshold as 30lux/ 50lux/ 80lux/ 120lux/ 200Lux/ 250Lux/300Lux/ 350Lux/ 400Lux Standby period as +∞ ; Standby dimming level as 10%/20%/30%
	Daylight Harvesting	1. Adjust "daylight" value higher than 50lux 2. Preset "standby period" 0S 3. Press MW/PIR button 3 times till MW/PIR icons both blicking on LCD screen, daylight harvesting function enabled. (With BLE verison, press DH button, daylight harvesting function enabled.)

DIMENSIONS



24″



36″



48″



96″