

## Exit & Emergency

### Emergence Low Profile Combo

- Compact, Low-Profile All-in-One Exit Sign/Emergency Unit
- Translucent, Low-Glare Acrylic Lens
- Chrome Plated, Metalized Reflector
- High Performance, Maintenance Free LED Light Strip

### Specifications

#### Description

Halco's Emergence Low Profile Combination Exit Sign/EM Unit offers a thin code compliant solution for hallway, stairwell, and other Life Safety applications. Originally designed for low level applications, this product also works well in restricted spaces above a doorway. The translucent low glare acrylic lens exhibits a minimalist aesthetic, yet performs exceptionally well due to its chrome plated metalized reflector controlling (24) white LED maintenance free lamps. Halco's Low Profile Combo is available with a red or green stencil face and mounts easily to smooth surfaces with its built in key hole slots or to a standard junction box using the universal knock out pattern on the back plate. This All-in-One Exit Sign / Emergency light includes field-selectable chevron indicators as well as dual input voltage.

#### Electrical

- 120 / 277 VAC, 60Hz Input
- Long-life, maintenance free NiCad battery
- 24 hour recharge time
- Battery low voltage circuit protection
- Solid state transfer circuit
- 3.1W (24 LEDs x 0.13W) Light Strip

#### Certifications

- UL924 damp location listed
- NFPA 101 and NFPA 70
- CEC Title 20 Compliant
- 0°C to 50°C operating temperature

## EMERGENCE™ SERIES



#### Construction & Mounting

- Injection molded, UL 94 5VA flame retardant, thermoplastic housing
- Chrome Plated, Metalized Reflector, low glare acrylic lens
- Fully illuminated 6" legend with 3/4" stroke
- Red or green stencil face
- Field-Selectable snap out chevrons
- Universal key hole slots and J-Box mounting pattern on back plate

#### Applications

- Commercial
- Retail
- Hospitality
- Office
- Medical
- Multi-Residential
- Low level exit sign requirements

# Emergence Low Profile Combo

## Ordering Information

<b>Series</b>	-	<b>Legend Color</b>	-	<b>Housing Color</b>
EMG-LPCU = Low Profile Combo Unit		R = Red G = Green		WH = White BK = Black

\*Footnotes: 3-5 Business Day Lead time

## Specifications Table

	EMG-LBCU
Housing	Injection molded 5VA Flame-retardant Thermoplastic
Mounting	Surface or J-Box Mount
Face	Injection molded Thermoplastic Stencil
Lamp Heads	(24) LEDs in (1) Light Wrap
Lamp Head Illumination	147 Lumens Total
Spacing	11' @ 6' on 3' Path of Egress
Legend	Uniformly illuminated 6" height, 3/4" stroke
Chevrons	Field-selectable Snap In/Out Chevrons
Letter Color	Red or Green
LED Life Expectancy	100,000+ hours
Input Voltage	120 / 277 VAC
Frequency	60Hz
Battery	Maintenance Free NiCad
Recharge Time	<24 hours
Discharge Time	90 minutes+
Output Voltage	9.6 VDC
Testing Function	Manual Test Button w/Charging Indicator
Protections	Low Voltage Disconnect Battery Protection
Operating Temperature	0°C – 50°C
Listings & Compliance	UL 924, CEC Title 20, NFPA 101 & NFPA 70
Environment	Damp Location Listed
Warranty	2 Year

\*All life safety equipment, including emergency lighting for path of egress must be maintained, serviced, and tested in accordance with all National Fire Protection Association (NFPA) and local codes. Failure to perform the required maintenance, service, or testing could jeopardize the safety of occupants and will void all warranties.

Exit & Emergency

## Emergence Low Profile Combo

### Ordering Information

Stocking SKUs		
Product SKU	Product Code	Watts
97139	EMG-LPCU-R-WH	Low Profile Exit & Emergency Combo, Single Face, Red Legend, White Housing
Non-Stocking SKUs*		
97140	EMG-LPCU-R-BK	Low Profile Exit & Emergency Combo, Single Face, Red Legend, Black Housing
97141	EMG-LPCU-G-WH	Low Profile Exit & Emergency Combo, Single Face, Green Legend, White Housing
97142	EMG-LPCU-G-BK	Low Profile Exit & Emergency Combo, Single Face, Green Legend, Black Housing

\*Footnotes: 3-5 Business Day Lead time

### Dimensions

