

Weather Proof Cover - 5x5, 24" Double-Gang Hinge Top Pedestal, Black

Item OP5BK24



PRODUCT DESCRIPTION

Provides convenient access to power in shared spaces with a heavy-duty power pedestal from Intermatic. These easy-to-install, low-maintenance cULus 1773 approved solutions are built of heavy gauge 304L stainless steel with 14 GA uprights, powder-coated and designed to withstand the harshest outdoor environments. Each power pedestal includes a self-closing, lockable cover for added security. Ideal for retrofit and new construction applications, they're a simple way to support everyday power needs (e.g., phone charging) and facility operations (e.g., holiday lighting).

FEATURES

- ▶ OP5XXXX Double-Gang Pedestals require a selection of an MPXXXXX Device Mounting Plate that meets your application needs. (Order Separately)
- ▶ Welded construction, built of heavy gauge 304L stainless steel with 14 GA uprights, powder-coated and designed to withstand the harshest outdoor environments.
- ▶ Welded construction, built of heavy gauge 304L stainless steel with 14 GA uprights, powder-coated and designed to withstand the harshest outdoor environments.
- ▶ Designed for quick and easy installation and low maintenance.
- ▶ Model accommodates 20 A to 60 A devices.
- ▶ Secure - in-use, tamper-resistant with self-closing reinforced hinge-top and hasp accepting up to 1/4" lock.

APPLICATIONS

- ▶ Power Pedestals

TECHNICAL DATA

| General | |
|-------------------------------------|--|
| Model Number | OP5BK24 |
| Description | 5x5, 24" Double-Gang Hinge Top Pedestal, Black |
| UPC Code | 078275158047 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | CANADA |
| Warranty Period | 2-Year limited |
| Mechanical Specifications | |
| Hinge Direction | Vertical |
| Base | Surface Mount |
| Device Type Mounting Plate | Order separately - See accessories on product page |
| Mounting Plate Included | No |
| Ground Wire Max | 4 GA Copper Solid |
| Ground Wire Min | 14 GA Copper Solid |
| Number of Gangs | Double |
| Max Load | 20 A; 30-60 A (must be water-tight) |
| Pedestal Type | Hinge-Top |
| Dimensions | |
| Lockable Hasp Maximum Diameter (in) | 0.25 |
| Lockable Hasp Maximum Diameter (mm) | 6.35 |
| Product Dimensions (H x W x D) in | 24 x 2.8 x 6.375 |
| Pedestal Height | 24" |

Material Specifications

| | |
|--------------------------------|--|
| Color | Black |
| Base Material | 304L 3/16" Powder Coated Stainless Steel |
| Body Material | 304L 14GA Powder Coated Stainless Steel |
| UV Resilient Outdoor Enclosure | Yes |

Packaging

| | |
|---------------------------------------|-----------------|
| Shipping Weight (lbs) | 16 |
| Unit Carton Dimensions (H x W x L) in | 27 x 11 x 11 in |
| Product Weight (lbs) | 15.5 |
| Product Weight (kg) | 7.03 |

Standards and Certifications

| | |
|---------------------------|-------------------------------------|
| UL Certification | UL Listed Mounting Pedestal E536618 |
| UL Standard | UL1773 |
| California Proposition 65 | None |
| RoHS Certification | Y |

ACCESSORIES



MP5BKD
20 A, Double-Gang Mounting Plate, Black



MP5BKS3S
30 A, 1-9/16" Mounting Plate, Black



MP5BKS3L
30 A, 2-1/8" Mounting Plate, Black



MP5BKS56L
50/60 A, Mounting Plate, Black