

NOXAC-432TW

4" AC Onyx LED Retrofit Baffle with Selectable CCT

Source: 11.5W

900lm

PRODUCT DESCRIPTION

4" AC Onyx Retrofit Series requires no driver and allow for a sleek design. Spun aluminum construction provides clean sharp edges and is suitable for use with most 4" recessed housings. Deep regressed optics and round aperture deliver even and glare-free illumination.

FEATURES

- Over 900 delivered lumens
- Five color temperatures in each fixture (2700K / 3000K / 3500K / 4000K / 5000K)
- Dimmable AC LED
- Includes medium base socket adapter for easy retrofitting in 4" recessed housings
- Quick connector is compatible with dedicated LED housings
- 5-year limited warranty
- Classified for wet locations

SPECIFICATION

Reflector: One piece, spun aluminum construction dissipates heat and extends life. Unitized Thermal Management, UTM, provides exceptional cool operation.

Mounting: Two steel, spring mounting blades allow for easy and secure mounting in most 4" housings.

Retrofit: Luminaires include a medium base screw-socket adapter ([NRA-21ISM](#)) for retrofitting into medium base downlight housings. Intended to be used as a LED lamp replacement. GU24 socket adapter ([NRA-212SM](#)) is available.

ELECTRICAL

Voltage: 120VAC

Lumens / Wattage: 900lm / 11.5W

Color Temperature: Selectable CCT: 2700K / 3000K / 3500K / 4000K / 5000K (*Note: Preset to 3000K*)

Color Rendering Index: 90+ CRI

Operating Temperature: 0°C to 35°C ambient temperature

Lifetime: 50,000 hours @ L70

Dimming: Triac/ELV

[Click Here](#) or check complete dimmer list at [www.NoraLighting.com](#) in the "Compatibility" page under "Resources" tab

COMPATIBLE HOUSINGS

Onyx retrofits are compatible with most 4" IC and Non-IC housings by Nora and others.

Fire Box

[NFJB-R4*](#)

[NFBIC-4LMRATA*](#)

[NFBIC-427LMRATA*](#)

[NFBIC-4INCATA](#)

ICAT Junction Box

IC Air-Tight Dedicated LED Firebox

Shallow ICAT Dedicated LED Firebox

IC Air-Tight Line Voltage Firebox

New Construction

[NHIC-4LMRAT*](#)

[NHIC-4LMRAT/277*](#)

(includes step-down transformer)

[NHICCP-4LMRAT*](#)

[NHIC-427LMRAT*](#)

[NSIC-401QAT](#)

[NS-401QAT](#)

[NHIC-4G24AT](#)

IC Air-Tight Dedicated LED

ICAT Dedicated LED, 277V

Chicago Plenum Dedicated LED

Shallow IC Air-Tight Dedicated LED

IC Air-Tight Line Voltage

Air-Tight Line Voltage

IC Air-Tight GU24

Remodel

[NHRIC-4LMRAT*](#)

[NHRIC-427LMRAT*](#)

[NSR-404QAT](#)

[NSRIC-404QAT](#)

IC Air-Tight Dedicated LED

Shallow IC Air-Tight Dedicated LED

Air-Tight Line Voltage

IC Air-Tight Line Voltage

* Nora LED Dedicated housings are listed for use only with Nora LED Retrofits.

ACCESSORIES

[NOX-4EYELIDW](#): White round eyelid used to convert round reflector or baffle to half moon wall wash trim.

[NOX-4OR-W](#): White round oversize ring used to cover ceiling cut-outs up to 5-7/8".

[NEPK-23LEDUNV](#): 23W Emergency with Remote Test Switch

[NEPKA-20/23LEDRTS](#): Ribbon Test Switch for NEPK-23LEDUNV

LABELS AND LISTINGS

- cULus classified for Wet Locations
- [5-Year Limited Warranty](#)
- Meets ASTM 283 Airtight requirements
- FCC compliant
- Certified to the high efficacy requirements of California Title 24 JA8-2025



Type

Project

Catalog No.

Notes

Performance Data

Part Number	Lumens	CCT
NOXAC-432TWWW	816lm	2700K
NOXAC-432TWWW	857lm	3000K
NOXAC-432TWWW	914lm	3500K
NOXAC-432TWWW	919lm	4000K
NOXAC-432TWWW	915lm	5000K

PRODUCT IMAGES AND DIMENSIONS





NOXAC-432TWWW
White Finish



NOXAC-432TW / NOX-4EYELIDW
White Eyelid



NOXAC-432TW / NOX-4OR-W
White Oversize Ring



4" AC Onyx LED Retrofit Baffle with Selectable CCT

Finish

NOXAC-432TWWW = White Finish

Optional Accessories

Description

NOX-4EYELIDW = 4" Round White Eyelid

NOX-4OR-W = 4" Round White Oversize Ring

NRA-21ISM = Medium base screw-in socket (included w/ each)

NRA-212SM = Socket adapter for use with GU24 housings

NEPK-23LEDUNV = 23W Emergency LED Driver w/ Remote Test Switch

NEPKA-20/23LEDRTS = Ribbon Test Switch for NEPK-23LEDUNV

Example: **NOXAC-432TWWW** = 4" AC Onyx LED Round Baffle Reflector with Selectable CCT, White Baffle / White Flange