

Project Name:	Part Number:	Type:
---------------	--------------	-------

SKYLINE

AREA LIGHT SERIES

FEATURES

- Specification Grade die-cast aluminum housing
- Bronze polyester powder coat finish (standard)
- Custom and factory select colors available
- 5 Optical Distributions with Highest Uniformity in their product class
- Factory Rotatable Type 2, 3, 4, 5 Square, & Automotive Front Row Optics
- Optional Spill Light Control Integral Shield (HSS)
- Universal Quick Pole Mount Allows for 1 man installation on existing poles with no drilling required
- 9 Different Optional Mounting Methods (3G Rated)³
- Single Fastener hinged door driver access
- 120-277V Universal Voltage or 347-480V High Voltage
- 0-10V Dimmable Driver (std.)
- PIR Occupancy, Photocell, & Bi-Level Dimming Sensors Available
- 3-Pin & 7-Pin ANSI C136.41 Control Receptacle Options
- Wireless control integrated luminaire
- 3000K, 4000K & 5000K CCT
- >70 Color Rendering Index (CRI)
- Calculated L80 >100,000 hrs @ 25°C per TM-21-11
- IP66 Rated Luminaire
- Dark Sky Compliant^{1,2}
- 5 Year Warranty; 10 Year Optional Warranty⁴
- ETL Listed for Wet Locations
- DesignLights Consortium® Premium Qualified Luminaire

¹ 3000K is IDA Listed ² Must select UMB, WFM, or HTM mounting options to qualify

³ TRN & SLPF 1.5G Rated ⁴ Requires additional Surge Protection (SP1, SP2, SP480V2);

For additional details see General Terms and Conditions



* Shown with UMB Mounting



407-478-3759
www.ilp-inc.com

Product Overview



SCAN ME



SUITABLE APPLICATIONS

- Parking Lots
- Parking Structure
- Parks
- Education
- Hospitals
- Car Dealerships
- Roadways
- Shopping Centers

ORDERING GUIDE

SERIES	LUMENS	VOLTAGE	CCT	DISTRIBUTION	ORIENTATION	MOUNTING	FINISH	WARRANTY
SAS Small	6L 6,000 lm	U 120-277v	30 3000K	T2 T2 - Type 2	(Blank) - Standard	SLPF Adjustable Slip Fitter	BRZ	(Blank) 5YR
	9L 9,000 lm	HV 347-480v	40 4000K	T3 T3 - Type 3	L Optics Rotated Left	UMB Universal Fixed	BLK	10YR ¹⁰ 10YR
	12L 12,000 lm		50 5000K	T4 T4 - Type 4	R Optics Rotated Right	UMB/R Universal Mount Sqr/Rnd pole 3"-6"	WHT	
	15L 15,000 lm			T5S Type 5 Square		UAB Universal Adjustable	SLV	
	18L 18,000 lm			FTA Forward Throw Automotive		UAB/R Universal Adjustable Sqr/Rnd pole 3"-6"	RALxxxx ⁹	
SAM Med	24L 24,000 lm					WFM Wall Fixed Mount		
	30L 30,000 lm					WAM Wall Adjustable Mount		
	36L 36,000 lm					TRN Trunnion Mount		
	42L 42,000 lm					HTM Horizontal Tenon Mount		
	50L 50,000 lm							

BASIC CONTROLS

ADVANCED CONTROLS

(Blank)	None	(Blank)	None
FAO ⁸	Field Adjustable Output	SYN ^{5,8}	Synapse Control System
CR3P ⁸	3-Pin NEMA Control receptacle	SYN/S/LX ^{5,8}	Synapse Control System w/ Sensor (X = Mounting Height 3=10-20'; 7=20-40')
CR7P ^{6,8}	7-Pin NEMA Control receptacle	SU/5S/LR/CL ^{1,8}	Enlighted 5S Connected Lighting (CL) Sensor with Control Unit
FSP-311/LX ^{1,3,8}	Legrand FSP-311 120-277V Sensor (X = Mounting Height 3=10-20'; 7=20-40')	SU/5S/LR/IOT ^{1,8}	Enlighted 5S Internet of Things (IOT) Sensor with Control Unit
FSP-321/LX ^{3,8}	Legrand FSP-321 347-480V Sensor (X = Mounting Height 3=10-20'; 7=20-40')	ZLD1Z ^{1,3,8}	Leviton ZLD1Z 120-277V Bluetooth Groupable Sensor (16 Devices) with 8-20' & 20-40' lens included
CR3P/FAO ⁸	Universal 3-Pin control receptacle (See acc. for photocells) with Field Adjustable Output - 7 level selection connected to 0-10V dimming wires		
CR7P/FSP/Lx ⁸	Universal 7-Pin control receptacle with FSP Sensor (X= Mounting Height, 3=20'; 7=40') (Controls provided by others)		

OPTIONS - FACTORY INSTALLED

ACCESSORIES

(Blank)	None	SAX/BIRD	Bird Spikes (x= fixture size)	TL7/HVG ^{5,7}	Synapse Twist Lock Mesh
SP1 ¹	10kA Surge Protection Device	SAX/GS ²	Rotatable Glare Shield (x= fixture size)		Network 480V
SP2 ¹	20kA Surge Protection Device	TL7/B2 ^{1,5,7}	Synapse Twist Lock Mesh Network 120-277V	TLPC/HV ⁴	347-480V Twist Lock Photocell
SP1HV	10kA Max 480V Surge Protector	ILP PAINT CHIP PACK	ILP Standard Color Paint Chips	TLPC/UNV ^{1,4}	120-277V Twist Lock Photocell
SP480V2	20kA Max 480V Surge Protector	TLSC ¹¹	Twist Lock Shorting cap for use with CRxP Option (120V-480V)		
HSS ²	Rotatable House Side Shield				
FUSE/SXXX	FUSE 120V, 277V, 347V (x= voltage)				
FUSE/DXXX	FUSE 208V, 240V, 480V (x= voltage)				
SMLxxx	Specified Lumen Output (xxx=lumen output, nearest hundred)				

¹ Not available with HV option ² Option Not DLC qualified

³ Requires Bluetooth Enabled device for programming (provided by others)

⁴ Only Compatible with CR3P and CR7P

⁵ Contact Factory for Site Layout, For HV models contact Factory for pricing.

⁶ Dimming Leads will be wired to receptacle unless otherwise specified

⁷ CR7P Required

⁸ Only one control option allowed

⁹ Contact factory for pricing and availability

¹⁰ Requires additional Surge Protection (SP1, SP2, SP480V2);

For additional details see General Terms and Conditions.

Consult Factory for pricing

¹¹ UMB/R standard, see mounting options for adders on alternate mounting methods

SKYLINE

AREA LIGHT SERIES

LED SYSTEMS INFO		3000K		4000K		5000K		BUG Rating	Watts ²	Replaces
Part Numbers	Distribution	Lumens	Efficacy	Lumens	Efficacy	Lumens	Efficacy			
SAS-6L	2	6322	138.0	6655	145.3	6788	148.2	B1-U0-G1	46 W	175W MH
	3	6301	137.6	6633	144.8	6766	147.7	B1-U0-G2		
	4	6234	136.1	6562	143.3	6693	146.1	B1-U0-G1		
	5S	6345	138.5	6679	145.8	6813	148.7	B3-U0-G2		
	FTA	6824	149.0	7183	156.8	7327	160.0	B1-U0-G1		
SAS-9L	2	8941	127.9	9412	134.6	9600	137.3	B1-U0-G2	70 W	250W MH
	3	8912	127.5	9381	134.2	9569	136.9	B2-U0-G2		
	4	8817	126.1	9281	132.8	9467	135.4	B2-U0-G2		
	5S	8973	128.4	9445	135.1	9634	137.8	B4-U0-G2		
	FTA	9650	138.1	10158	145.3	10361	148.2	B1-U0-G1		
SAS-12L	2	12693	154.4	13361	162.5	13628	165.8	B2-U0-G2	82 W	320W MH
	3	12652	153.9	13318	162.0	13584	165.3	B2-U0-G2		
	4	12516	152.3	13175	160.3	13439	163.5	B2-U0-G2		
	5S	12739	155.0	13409	163.1	13677	166.4	B4-U0-G2		
	FTA	13700	166.7	14421	175.4	14709	178.9	B2-U0-G1		
SAS-15L	2	16013	148.1	16856	155.9	17193	159.0	B2-U0-G2	108 W	400W MH
	3	15962	147.7	16802	155.4	17138	158.5	B2-U0-G2		
	4	15791	146.1	16622	153.8	16954	156.8	B2-U0-G2		
	5S	16070	148.7	16916	156.5	17254	159.6	B4-U0-G2		
	FTA	17283	159.9	18193	168.3	18557	171.7	B2-U0-G1		
SAS-18L	2	18245	138.5	19205	145.8	19589	148.7	B3-U0-G2	132 W	400W MH
	3	18186	138.1	19143	145.4	19526	148.3	B3-U0-G3		
	4	17984	136.6	18931	143.7	19310	146.6	B3-U0-G3		
	5S	18310	139.0	19274	146.3	19659	149.3	B5-U0-G3		
	FTA	19692	149.5	20728	157.4	21143	160.5	B2-U0-G1		
SAM-24L	2	23494	142.4	24730	149.9	25225	152.9	B3-U0-G3	165 W	400W MH
	3	23373	141.7	24603	149.1	25095	152.1	B3-U0-G4		
	4	23203	140.6	24424	148.0	24912	151.0	B3-U0-G4		
	5S	23911	144.9	25169	152.5	25672	155.6	B5-U0-G3		
	FTA	23559	142.8	24799	150.3	25295	153.3	B2-U0-G2		
SAM-30L	2	30061	135.0	31643	142.1	32276	144.9	B3-U0-G3	222 W	750W MH
	3	29906	134.3	31480	141.4	32110	144.2	B3-U0-G4		
	4	29688	133.3	31251	140.3	31876	143.1	B3-U0-G4		
	5S	30594	137.4	32204	144.6	32848	147.5	B5-U0-G4		
	FTA	30144	135.4	31730	142.5	32365	145.3	B3-U0-G2		
SAM-36L	2	36547	153.6	38470	161.7	39239	164.9	B3-U0-G3	237 W	750W MH
	3	36357	152.8	38271	160.9	39036	164.1	B3-U0-G5		
	4	34913	146.8	36750	154.5	37485	157.6	B3-U0-G5		
	5S	35977	151.2	37871	159.2	38628	162.4	B5-U0-G4		
	FTA	35448	149.0	37314	156.8	38060	160.0	B3-U0-G2		
SAM-42L	2	39231	141.6	41296	149.0	42122	152.0	B4-U0-G3	277 W	1000W MH
	3	39099	141.1	41157	148.5	41980	151.5	B3-U0-G5		
	4	38885	140.3	40932	147.7	41751	150.7	B3-U0-G5		
	5S	39927	144.1	42028	151.7	42869	154.7	B5-U0-G4		
	FTA	39340	142.0	41410	149.4	42238	152.4	B3-U0-G2		
SAM-50L	2	48196	142.3	50732	149.8	51747	152.8	B4-U0-G4	338.6	1000W MH
	3	48033	141.9	50561	149.3	51573	152.3	B4-U0-G5		
	4	47771	141.1	50285	148.5	51291	151.5	B4-U0-G5		
	5S	49050	144.9	51631	152.5	52664	155.5	B5-U0-G5		
	FTA	48329	142.7	50872	150.2	51890	153.2	B3-U0-G3		

¹Values are nominal, see IES file for more detail

²Electrical data at 25C (77F). Actual wattage may differ by +/-10%.


SKYLINE

AREA LIGHT SERIES

EPA RATINGS AND VIBRATION CHART

	SLPF		UMB		UAB		WFM		WAM		TRN		HTM		WEIGHT
SAS	0.53	1.5g	0.47	3g	0.53	3g	0.47	3g	0.53	3g	0.47	1.5g	0.47	3g	11 lbs
SAM	0.71	1.5g	0.64	3g	0.71	3g	0.64	3g	0.71	3g	0.64	1.5g	0.64	3g	22 lbs
WEIGHT	4.5 lbs		2.5 lbs		5.5 lbs		3.0 lbs		6.0 lbs		2.5 lbs		3.5 lbs		

* EPA Ratings listed assume fixture is mounted horizontally. For adjustable mounting options, EPA will vary with selected angle.

TILT DEGREE		0°	30°	45°	TILT DEGREE		0°	30°	45°
 Single	SAS	0.47	1.32	1.72	 T90°	SAS	1.13	1.83	2.39
	SAM	0.64	2.49	3.32		SAM	1.54	3.46	4.61
 D180°	SAS	1.03	1.32	1.72	 TN120°	SAS	1.22	2.77	3.58
	SAM	1.41	2.49	3.32		SAM	1.66	5.23	6.91
 D90°	SAS	0.85	1.58	1.72	 Q90°	SAS	1.13	1.83	2.39
	SAM	1.15	2.99	3.32		SAM	1.54	3.46	4.61

*EPA for UMB, WFM, TRN, and HTM mounts

ELECTRICAL DATA (AMPS)

Lumen Package	120V	208V	240V	277V	347V	480V
6L	0.38 A	0.22 A	0.19 A	0.17 A	0.13 A	0.10 A
9L	0.58 A	0.34 A	0.29 A	0.25 A	0.20 A	0.15 A
12L	0.73 A	0.42 A	0.37 A	0.32 A	0.25 A	0.18 A
15L	0.92 A	0.53 A	0.46 A	0.40 A	0.32 A	0.23 A
18L	1.14 A	0.66 A	0.57 A	0.49 A	0.39 A	0.29 A
24L	1.39 A	0.80 A	0.70 A	0.60 A	0.48 A	0.35 A
30L	1.83 A	1.06 A	0.92 A	0.79 A	0.63 A	0.46 A
36L	1.96 A	1.13 A	0.98 A	0.85 A	0.68 A	0.49 A
42L	2.27 A	1.31 A	1.13 A	0.98 A	0.78 A	0.57 A
50L	2.82 A	1.63 A	1.41 A	1.22 A	0.98 A	0.71 A

¹Electrical data at 25C (77F). Actual wattage may differ by +/-10%.

SKYLINE

AREA LIGHT SERIES

FIELD ADJUSTABLE OUTPUT DATA (FAO)

Part Number	FAO Position	0	1	2	3	4	5	6	7
SAS-6L-U-40-T4	Input Power (W)	46	40	35	29	24	19	13	8
	Approx Lumens @3000K	6234	5421	4743	3930	3253	2575	1762	1084
	Approx Lumens @4000K	6562	5706	4993	4137	3424	2710	1854	1141
	Approx Lumens @5000K	6693	5820	5093	4220	3492	2765	1892	1164
SAS-9L-U-40-T4	Input Power (W)	70	61	52	44	35	27	19	10
	Approx Lumens @3000K	8817	7683	6550	5542	4409	3401	2393	1260
	Approx Lumens @4000K	9281	8088	6894	5834	4641	3580	2519	1326
	Approx Lumens @5000K	9467	8250	7033	5951	4734	3652	2570	1352
SAS-12L-U-40-T4	Input Power (W)	82	72	61	52	43	33	23	14
	Approx Lumens @3000K	12516	10990	9311	7937	6563	5037	3511	2137
	Approx Lumens @4000K	13175	11568	9801	8355	6909	5302	3695	2249
	Approx Lumens @5000K	13439	11800	9997	8522	7047	5408	3769	2294
SAS-15L-U-40-T4	Input Power (W)	108	95	82	70	57	44	31	18
	Approx Lumens @3000K	15791	13890	11989	10235	8334	6433	4533	2632
	Approx Lumens @4000K	16622	14621	12620	10774	8773	6772	4771	2770
	Approx Lumens @5000K	16954	14913	12872	10989	8948	6907	4866	2826
SAS-18L-U-40-T4	Input Power (W)	132	117	100	85	68	53	37	21
	Approx Lumens @3000K	17984	15940	13624	11581	9264	7221	5041	2861
	Approx Lumens @4000K	18931	16780	14342	12190	9752	7601	5306	3012
	Approx Lumens @5000K	19310	17116	14629	12434	9948	7753	5413	3072
SAM-24L-U-40-T4	Input Power (W)	165	142	123	104	84	64	44	25
	Approx Lumens @3000K	23203	19969	17297	14625	11812	9000	6187	3516
	Approx Lumens @4000K	24424	21019	18207	15395	12434	9474	6513	3701
	Approx Lumens @5000K	24912	21439	18571	15702	12682	9663	6643	3775
SAM-30L-U-40-T4	Input Power (W)	222	196	169	142	115	88	62	34
	Approx Lumens @3000K	29688	26211	22600	18990	15379	11768	8291	4547
	Approx Lumens @4000K	31251	27591	23790	19989	16189	12388	8728	4786
	Approx Lumens @5000K	31876	28143	24266	20389	16512	12636	8902	4882
SAM-36L-U-40-T4	Input Power (W)	237	210	182	154	126	99	71	42
	Approx Lumens @3000K	34913	30936	26811	22686	18561	14584	10459	6187
	Approx Lumens @4000K	36750	32563	28222	23880	19538	15351	11009	6513
	Approx Lumens @5000K	37485	33215	28786	24357	19929	15658	11230	6643
SAM-42L-U-40-T4	Input Power (W)	277	239	207	174	142	109	76	43
	Approx Lumens @3000K	38885	33551	29058	24426	19934	15301	10669	6036
	Approx Lumens @4000K	40932	35317	30588	25712	20983	16107	11230	6354
	Approx Lumens @5000K	41751	36023	31200	26226	21403	16429	11455	6481
SAM-50L-U-40-T4	Input Power (W)	339	292	253	213	174	133	93	53
	Approx Lumens @3000K	47771	41148	35652	30015	24520	18742	13105	7469
	Approx Lumens @4000K	50285	43313	37528	31595	25810	19728	13795	7862
	Approx Lumens @5000K	51291	44180	38279	32227	26326	20123	14071	8019

SKYLINE

AREA LIGHT SERIES

SPECIFICATIONS

CONSTRUCTION

The Skyline series features a slim profile die-cast aluminum housing available in 2 different sizes for a fully scalable solution. The versatile 9 optional mounting methods allow for easy installation while the hinged door allows for quick drop-down driver access for maintenance. The standard Keyhole / slotted UMB mounting bracket allows for a "no-drilling" 1-man installation by mounting the UMB on existing pole drillings and the luminaire head onto the UMB, substantially reducing installation labor. The fully gasketed housing is IP66 rated for whole luminaire ingress protection against moisture and environmental contaminants. The Skyline's low-profile design results in a low EPA, allowing pole optimization to thinner or smaller size pole shafts. Vibration rated per ANSI C136.31 on all mountings (see table Above). The Skyline Series is protected with a durable bronze polyester powder coat finish to withstand extreme weather changes without cracking or peeling.

OPTICS

The IP66 silicone gasket sealed optical chamber utilizes proprietary polycarbonate refractive optics to provide exceptional coverage and uniformity in factory rotatable IES Types 2, 3, 4, 5S (Square) or FTA (Forward Throw Automotive). Polycarbonate optics are impact resistant and UV stabilized for maximum longevity. Available in 5000K, 4000K, and 3000K, color temperatures per ANSI C78.377. Minimum CRI of 70. The optical integrated House side shield (HSS) option allows for improved backlight control without any large shields taking away from the site. The Skyline series produces Zero uplight and is IDA listed in 3000K color temperature. Optional field installed 3-sided glare shield accessory is available for on-site external house side protection.

ELECTRICAL

Class 1 High-performance drivers features over-voltage, under-voltage, short circuit and over temperature protection. 0-10V dimming (10% - 100%) standard. Standard Universal Voltage (120-277 Vac) Input 50/60 Hz or optional High Voltage (347-480 Vac). L80 >100,000 hrs. in accordance with IESNA TM-21-19 projected values at 25°C Ambient temperature. Total harmonic distortion: <20%. Power factor: >0.90. Input power stays constant over life. Minimum 6kV surge rating meets a minimum Category C Low operation (per ANSI/IEEE C62.41.2). Additional protection is available in 10kV and 20kV options.

THERMAL

The Skyline Series features an array of High-efficacy LED's mounted on a metal core circuit board. The LED boards are mounted directly to the cast aluminum housing with heat dissipating fins to provide excellent thermal performance extending the life of electronic components. Operating Ambient Temperature: -40°C to +50°C (-40°F to 122°F) 50L Lumen -- Package: -40°C to +45°C (-40°F to 113°F).

INSTALLATION

The versatile Skyline series comes with 9 optional mounting methods. The standard keyhole / slotted universal mounting bracket (UMB) allows for a "no-drilling" 1-man installation by mounting the UMB on existing pole drillings and the luminaire head onto the UMB, substantially reducing installation labor. The 3G rated UMB quick mount allows for pole mounting onto square 4-6" poles with a vertical mounting pattern between 2"-5" and the UMB/R adds additional mounting capability to any round pole 3"-6" in diameter. The 3G rated universal adjustable mount (UAB) model adds full range tilting to the standard UMB fixed model. The 3G rated wall fixed mount (WFM) allows for easy installation to any vertical wall surface or J-box. The optional 3G rated wall adjustable mount (WAM) adds full range wall mount tilting. The 3G rated horizontal mast arm (HTM) mount is designed for straight horizontal 2"(2-3/8" OD) mast arms. The 1.5G rated adjustable slip fitter (SLPF) mounts to any vertical or horizontal tenon 2" pipe (2-3/8" OD) allowing for full range tilting.

The 3G rated wall fixed mount (WFM) allows for easy installation to any vertical wall surface or J-box. The optional 3G rated wall adjustable mount (WAM) adds full range wall mount tilting. The 3G rated horizontal mast arm (HMA) mount is designed for straight horizontal 2"(2-3/8" OD) mast arms. The 1.5G rated adjustable slip fitter (SLPF) mounts to any vertical or horizontal tenon 2" pipe (2-3/8" OD) allowing for full range tilting.

The trunnion/yoke bracket (TRN) enables the Skyline to be used for general flood applications with full range tilting as required.

All mounting methods are provided with a 3-wire 3' outdoor rated cord is provided for wiring. 5-wire cord optional for external dimming, consult factory. See charts above for all vibration, weight, and EPA results.

CONTROLS

Standalone Controls:

Factory installed 3-Pin & 7-Pin ANSI C136.41 Control Receptacle Options available. Dusk to Dawn twist lock photocells sold separately (See accessories). Optional PIR sensors available installed in housing hinged door. Sensors provide optional on/off control, photocell capability, bi-level dimming, high-end trim, and bluetooth configuration allows for on-site modifications.

Wireless Control Systems:

The Skyline Series is wireless mesh controls ready with Synapse, Enlighted, and Leviton Bluetooth Mesh wireless control platforms. Available with and without PIR sensors. Inquire with factory for more information or for additional controls options, including customer supplied items.

WARRANTY

5 Year Warranty Standard; 10 Year Warranty Optional (Terms and Conditions apply).

CERTIFICATIONS

ETL Listed for wet locations. Tested in accordance with IESNA LM-79 and LM-80 standards. BAA compliant. RoHS Compliant. Title 24 Compliant; see local ordinance for qualification information. IP66 rated Luminaire per IEC 60598. IP66 rated optical chamber. ASTM B117 Salt Spray Tested 500 Hrs.

DLC Premium Listed Product, Not all versions of this product may be DLC Premium qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.

SKYLINE

AREA LIGHT SERIES

BASIC

FAO

Internal bi-level switch offers adjustable light levels for greater flexibility within one product. Utilizes 0-10V dimming wires and cannot be combined with other sensor or control options.

CRxP

3-Pin or 7-pin ANSI C136.41-2013 control receptacle option available for NEMA twist lock photocontrols or wireless control modules. Control accessories sold separately. Dimming leads from the receptacle will be connected to the driver dimming leads (Consult factory for alternate wiring). x = Number of pins (3 or 7).

FSP-311/Ly - FSP-321/Ly


Optional Bluetooth Programmable PIR sensor allows for Continuous Dimming, Motion and/ or daylight harvesting, Fully adjustable high/low dimmed light levels, and Adjustable time delay/ cutoff delay. The sensor is programmed via a free iOS® or Android® Sensor Configuration App (compatible device provided by others). Available in 10'-20' or 20'-40' mounting lenses. See coverage patterns below, L7=20'-40', L3=20'-40'.

Default Settings:


- High Mode: 100% Output
- Low Mode: 10% Output
- Time Delay: 5 mins
- Cutoff: 1 hr
- Sensitivity: High
- Photocell: Disabled
- Continuous Dimming: Disabled

COVERAGE PATTERNS

SYNS/L2 and FSP-311/Ly - FSP-321/Ly



SYNS/L3 and FSP-311/Ly - FSP-321/Ly



ADVANCED

Synapse (SYN or TL7)

Utilizing a robust 2.4 GHz Self-Healing Mesh Network, Synapse provides flexibility and scalability making it a perfect outdoor solution for both new construction and retrofit projects. The easy-to-use web application is accessible on any device with an internet connection and allows for complete customization of the system and its features. Integral radio (SYN) includes (2) 24V inputs for a Wattstopper sensor or twist lock photocell into the wireless lighting system. External radio (TL7) includes (1) low voltage input for a Wattstopper sensor, available in both universal(120-277V) or high voltage (480V). Sensors available in 20' or 40' mounting lenses. See coverage patterns below. Sensor mounted on hinged driver cover. Antenna exits side of luminaire for maximum connectivity.

Enlighted

Enlighted's three-tier, over-the-air upgradeable wireless control platforms provide out-of-the-box compliance with energy use regulations. The comprehensive capabilities of the sensor include vacancy detection, daylight harvesting, demand response, and energy savings reporting. Enlighted's enterprise system allows for easy integration of indoor and outdoor lighting with building management systems for site-wide IOT management. Enlighted ruggedized sensor mounted on hinged driver cover.

Enlighted Connected (SU/5S/LR/CL)

-Fixtures are controlled based on occupancy & ambient light. Includes individual lighting control plus connection to Enlighted Energy Manager. The Energy Manager provides data analysis for all data collected by the Enlighted Smart Sensors for energy, occupancy & environment.

Enlighted IOT (SU/5S/LR/IOT)

-Fixtures are controlled based on occupancy and ambient light. Includes individual lighting control plus connection to Enlighted Energy Manager. The Energy Manager provides data analysis for all data collected by Enlighted Smart Sensors for energy, occupancy & environment. Additionally, the IOT functionality takes the data access and function beyond just lighting to a wide range of applications beyond the standard connected lighting controls.


Leviton ZLD1Z

Optional Bluetooth Groupable PIR sensor that allows for Programmable Options such as, Continuous Dimming, Motion and/ or daylight harvesting, fully adjustable high/ low dimmed light levels, and Adjustable time delay/ cutoff delay. The sensor is programmed via a free iOS® or Android® Sensor Configuration App (compatible device provided by others). Sensor Mesh Grouping allows for 16 devices per group, with both Occupancy and Daylight Control. Recommended spacing < 100'. Comes standard with both 8'-20' or 20'-40' mounting lenses. See coverage patterns on page 6..

Default Settings:

- High Mode: 100% Output
- Auto-ON/Auto-OFF with 20-minute timeout
- Sensitivity: High
- Daylight Harvesting: Enabled

SYNS/L7 and FSP-311/Ly - FSP-321/Ly




SKYLINE


AREA LIGHT SERIES

COVERAGE PATTERNS

Leviton Low Mount



Leviton High Mount



BACK LIGHT CONTROL OPTIONS



HSS
Integral House Side Shield

Delivers backlight control that significantly reduces light spill behind the pole for applications with pole locations close to adjacent properties. Shown with Medium housing . HSS rotates with optic distribution.



GS
External Glare Shield


Rotatable 3-sided field installable external glare shield. Shown with Medium housing

SKYLINE


AREA LIGHT SERIES

LINE DRAWINGS


SAS Universal Mounting Bracket (UMB/R)




UMB/R, UAB/R Mounting Detail




SAS Universal Adjustable Mount Bracket (UAB/R)



SAS Adjustable Slip Fitter (SLPF)




SAS Horizontal Tenon Mount (HTM)




SKYLINE

AREA LIGHT SERIES


SAS Wall Fixed Mount (WFM)




SAS Wall Adjustable Mount Bracket (WAM)



SAS Trunnion Mount (TRN)




SAM Universal Mounting Bracket (UMB/R)




SKYLINE

AREA LIGHT SERIES


SAM Universal Adjustable Mount Bracket (UAB/R)




SAM Adjustable Slip Fitter (SLPF)




SAM Horizontal Tenon Mount (HTM)



SAM Wall Fixed Mount (WFM)




WFM/WAM Mounting Detail




SKYLINE

AREA LIGHT SERIES



SAM Wall Adjustable Mount Bracket WAM




SAM Trunnion Mount (TRN)



OPTICS ORIENTATION



FACTORY SELECT FINISH GUIDE



COLOR NAME AND DESCRIPTION		PRICING
WHT	- ILP White	Standard
SLV	- ILP Silver	Standard
BRZ	- ILP Bronze	Standard
BLK	- ILP Black	Standard
COLORS SHOWN ABOVE ARE TO BE USED AS REFERENCE, NOT EXACT MATCH. PLEASE REQUEST PAINT CHIPS FOR EXACT MATCH.		


SKYLINE

AREA LIGHT SERIES


PHOTOMETRIC REPORTS

Photometric values based upon tests performed in compliance with LM-79. IES files can be downloaded at www.ilp-inc.com


FTA




T2



T3



T4



T5S

