

Power Center - Control Panel Only

Item T10000R



PRODUCT DESCRIPTION

Can be used as a power center only, or add mechanisms or wiring devices for complete control systems.

FEATURES

- ▶ Available with one or two heavy-duty time switch mechanisms
- ▶ Accepts any combination of PF1000M, P1403ME, P1353ME, P4043ME, P4243ME, T100M or RC2000M Series mechanisms
- ▶ Load center dead front has two knockouts for switches or GFCLs and one on the side
- ▶ Wiring devices may be installed in these load centers with the use of Standoffs, sold separately below
- ▶ Control two-speed pumps with the T10604R

APPLICATIONS

- ▶ Distribution/Control Panel

TECHNICAL DATA

General

| | |
|--------------------------------|--------------------|
| Model Number | T10000R |
| Description | Control Panel Only |
| UPC Code | 078275116795 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | MEXICO |
| Warranty Period | 1-Year limited |

Dimensions

| | |
|-----------------------------------|---|
| Product Dimensions (H x W x D) in | 12.875 x 10.875 x 4.75 in |
| Knockout Dimensions Bottom | (5) combination 1/2" - 3/4" and (2) combination 3/4" - 1" |
| Knockout Dimensions Back | (1) combination 1/2" - 3/4" and (1) 3/4" - 1" |
| Knockout Dimensions Left | (1) combination 1/2" - 3/4" |
| Knockout Dimensions Right | (1) 1 3/4" x 2 3/4" |

Material Specifications

| | |
|-------|-------|
| Color | Beige |
|-------|-------|

Load Ratings

| | |
|------------|-------------------|
| Mechanisms | Power Center Only |
|------------|-------------------|

Electrical Specifications

| | |
|--------------------------------|---|
| Number of Receptacle Knockouts | 2 |
|--------------------------------|---|

Packaging

| | |
|---------------------------------------|-------------------------|
| Shipping Weight (lbs) | 9.331 |
| Unit Carton Dimensions (H x W x L) in | 5.63 x 12.06 x 13.81 in |

Standards and Certifications

| | |
|--|--------------|
| CSA Certification | cCSAus |
| Other Certifications and Compatibilities | Green Energy |
| California Proposition 65 | None |
| RoHS Certification | X |

ACCESSORIES



156T1978AMX
1 Set of ON/OFF Trippers for T100, T7000,
and WH40



156T1978A
Extra/replacement trippers 1 ON and 1 OFF




124--00066
Insulator for 3-Circuit Timers



21T166A
Spacer-Standoff, 3" long - 2 pack



21T156A
Spacer-Standoff, 3" long - 4 pack



22T338GR
Mounting Bracket for Intermatic Standardized
Timer Mechanisms

22T713
Bracket Painted

8--00008A
Latch-Enclosure

24TP6019-WWH
Painted Plate Dead-Front for the T1000 Series 1" Nonmetallic Hub Kit

156PA13715A

6TP2819A-WWH
Cover Assembly Painted 10x12 T10000 Series