

Project Name

Location

Prepared By



**SATCO 67-113**

EL EXIT SIGN - SF RD CLR

## Notes

[www] 10-30-2020 00:00:20

## General

|                           |           |
|---------------------------|-----------|
| Status                    | Active    |
| Fixture Type              | Exit Sign |
| Finish                    | Clear     |
| Wattage                   | 3.14W     |
| Indoor or Outdoor Fixture | Indoor    |

## Specifications

|                       |                             |
|-----------------------|-----------------------------|
| Technology            | LED                         |
| Voltage               | 120V/277V                   |
| Operating Temperature | +10C (+50F) to +40C (+104F) |
| Dimmable              | Non-Dimmable                |
| Weight (lb.)          | 2.76                        |
| Material              | Aluminum                    |

## Dimensions

|              |       |
|--------------|-------|
| Height (in.) | 9.69  |
| Width (in.)  | 12.06 |
| Length (in.) | 1.81  |

## Compliance

|                        |                                     |
|------------------------|-------------------------------------|
| Safety Listing         | ULus - Certified                    |
| Location Rating        | Damp                                |
| Energy Star            | No                                  |
| CA T20 / T24 Rationale | T20 Exempt - Fixtures Not Regulated |
| California Status      | Lawful for sale in California       |
| Title 20 / 24 Status   | Lawful for sale                     |
| California Prop 65     | Lead                                |
| RoHS Compliant         | Yes                                 |
| FCC Compliant          | Yes                                 |

## Additional Information

|                        |                                                                                                                                                         |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| Additional Information | Input Wattage: 3.14W; Output Wattage: 0.4W; Energy Used in Maintenance Mode: 3.14W                                                                      |
| Specification Note     | Aluminum, Acrylic Panel, 4.8V AA300mAh Ni-Cad Battery, 90 minutes duration, 24 hour charge time, 10C-40C; Letter Height: 6 in.; Letter Stroke: 0.75 in. |
| Includes               | Mounting hardware and accessories                                                                                                                       |
| Warranty               | 2 Year Limited                                                                                                                                          |