

LED SURFACE MOUNT DOUBLE RING - BRUSHED NICKEL BI-LEVEL MOTION SENSOR 10", 12", 14", 16", 18"



10"



12"



14"



16"



18"



MOTION SENSOR DEFAULT SETTINGS

BI-LEVEL MOTION SENSOR SETTINGS*		
DETECTION ANGLE 360° CEILING MOUNTED	DETECTION ANGLE 150° WALL MOUNTED	DETECTION RANGE UP TO 39'
1 MIN HOLD TIME	INFINITY STANDBY MODE	30% STANDBY BRIGHTNESS

*OPTION TO CHANGE SETTINGS VIA REMOTE AVAILABLE.

COMPATIBLE WITH

MICROWAVE BI-LEVEL REMOTE
LR25189



COLOR SELECTABLE

2700K 3000K 3500K 4000K 5000K

DETECTION ANGLE

360°
CEILING MOUNTED

150°
WALL MOUNTED

BI-LEVEL MOTION SENSOR

BEAM SPREAD
110°

120-277V

DAMP LOCATION RATED

5
YEAR WARRANTY

ELECTRICAL

	MODEL	DESCRIPTION	POWER	INPUT VOLTS	EFFICACY	LIFETIME	COST/YR
10"	LR23280+MS	LED10"FLUSH/CHROME/5CCT/D+MS	14	120-277V	75	50,000	\$ 1.69
12"	LR23281+MS	LED12"FLUSH/CHROME/5CCT/D+MS	14	120-277V	80	50,000	\$ 1.69
14"	LR23282+MS	LED14"FLUSH/CHROME/5CCT/D+MS	18	120-277V	80	50,000	\$ 2.16
16"	LR23283+MS	LED16"FLUSH/CHROME/5CCT/D+MS	24	120-277V	80	50,000	\$ 2.89
18"	LR23284+MS	LED18"FLUSH/CHROME/5CCT/D+MS	24	120-277V	90	50,000	\$ 2.89

PHOTOMETRIC

MODEL	DESCRIPTION	COLOR (CCT)	TEMP	LUMEN	FLOOD	CRI	ETL
LR23280+MS	LED10"FLUSH/CHROME/5CCT/D+MS	2700K/3000K/3500K/4000K/5000K	CCT SELECT	1050	110°	80	YES
LR23281+MS	LED12"FLUSH/CHROME/5CCT/D+MS	2700K/3000K/3500K/4000K/5000K	CCT SELECT	1120	110°	80	YES
LR23282+MS	LED14"FLUSH/CHROME/5CCT/D+MS	2700K/3000K/3500K/4000K/5000K	CCT SELECT	1440	110°	80	YES
LR23283+MS	LED16"FLUSH/CHROME/5CCT/D+MS	2700K/3000K/3500K/4000K/5000K	CCT SELECT	1920	110°	80	YES
LR23284+MS	LED18"FLUSH/CHROME/5CCT/D+MS	2700K/3000K/3500K/4000K/5000K	CCT SELECT	2160	110°	80	YES

MOTION SENSOR DEFAULT SETTINGS

DETECTION ANGLE

360°

CEILING MOUNTED

150°

WALL MOUNTED

DETECTION RANGE

UP TO 39'

1 MIN HOLD TIME

INFINITY STANDBY MODE

30% STANDBY BRIGHTNESS

COMPATIBLE MICROWAVE BI-LEVEL REMOTE

*SOLD SEPARATELY



MICROWAVE BI-LEVEL REMOTE

LR25189

LEDSNS/MW/BIlevel/REMOTE

DIMENSIONS

