

IBMIRROR

PRODUCT SPECIFICATION SHEET

Chic Arch™ Vanity LED Mirror

Model Variant: 36" × 60" × 2" (Vertical Mounting Layout)

Refined and timeless, the Chic Arch Vanity LED Mirror brings graceful curves and luminous functionality to your premium commercial or residential bathroom setup. Designed with a soft arched silhouette and a durable frame casing, it offers a seamless blend of classic shape architecture and top-tier lighting performance.

1. TECHNICAL & ELECTRICAL SPECIFICATIONS

SYSTEM FOOTPRINT & ENGINEERING DATA

Dimensions	36" Width × 60" Height × 2" Depth (914 mm × 1524 mm × 51 mm)
Model Configuration	Chic Arch 3660 Series (Ref: #621/623 Variant Upgrade)
Voltage Input	110V–120V AC, 50/60 Hz (Standard hardwire application)
Lumen Output	Approx. 7,100 Lumens (Evenly distributed front-facing output)
CRI Value	90+ CRI (True color accuracy for cosmetic application and grooming)
Color Temperatures	Adjustable settings ranging from Warm White (3000K) to Daylight (6000K)
Dimming Support	Fully compatible with forward-phase standard TRIAC or MLV wall switches
LED System Lifespan	Up to 120,000 Hours projected lifetime rating
Certifications	UL & cUL Safety Listed for US and Canadian regulatory standards
Environmental Certification	Damp Location Certified (Engineered for moisture-rich environments)

2. PREMIUM FEATURES & CONSTRUCTION DETAILS

- Elegant Arch Casing:** Smooth, curved architectural crown introduces structural elegance, breaking up angular patterns in modern interiors.
- Dimmable Front Lighting:** Inward-facing diffused frosted layout delivers crisp, powerful lighting that fully eliminates overhead shadows.
- Heavy-Duty Profile Frame:** Rigid protective perimeter metal frame, available in luxurious matte finishes (Black/Gold), defending the edge profiles.

- **Copper-Free Core Mirror:** Premium eco-sustainable multi-layer glass structure specifically protected against humidity and dark-edge scaling.

3. MOUNTING DIMENSIONS & ALIGNMENT LAYOUT

DIMENSIONAL FOOTPRINT BLUEPRINT

36" [914mm] Width × 60" [1524mm] Height

Designed strictly for vertical wall mount configuration to accommodate the arched layout. Hardwire center connection recommended. Lock mounting cleats securely into wall studs.

Due to continuous product improvements, physical, structural, and electrical specifications are subject to modification without notice. Always cross-verify dimensions on-site prior to final positioning.