


## Graesslin Mechanical Time Switch - 24-Hour 12/24V Electromechanical Flush Mount Timer Module with Battery Backup, 15 Minute Intervals, 21A, SPDT

Item MIL72EQTUZ-24



### PRODUCT DESCRIPTION

The MIL72 series time switches are designed to be mounted inside a control panel and can accommodate surface/DIN rail or flush panel mounting. The MIL72 series is a light duty commercial time switch for 12-24 VAC/VDC, 120 or 208/240 VAC single-phase applications.

### FEATURES

- 21 A SPDT switch
- Synchronous drive or quartz drive (Q Models) with self-recharging battery backup
- 72-hour carry-over battery backup on Q models
- Captive trippers with 15-minute intervals
- Available with or without override
- True clock face, easy-to-set
- Surface/DIN rail or flush mount
- Clear plastic dust cover
- Compact size

### APPLICATIONS

- Refrigeration Merchandiser
- Air Movement & Ventilation
- Aeration
- Septic Treatment
- Generator Exercising

### TECHNICAL DATA

#### General

Model Number	MIL72EQTUZ-24
Description	24-Hour 12/24V Electromechanical Flush Mount Timer Module with Battery Backup, 15 Minute Intervals, 21A, SPDT
UPC Code	078275153417
Brand	Domestic Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

#### Control Specifications

Maximum Cycle Time	24 hrs
Timing Interval	15 min
Clock Drive Type	Quartz
Backup Type	72-hour Carry-over; Battery; Self-recharging
Battery Type	NiMh
Backup Protection Time	72 Hours
Battery Service Type	Rechargeable
Mechanism Type	Electromechanical
Has Captive Trippers	Yes
Has Real-time Clock Face	Yes
Application Compatibilities	Incandescent; Fluorescent; CFL; LED

### Mechanical Specifications

Mounting Options	Flush
Number of Trippers Included	96

### Dimensions

Product Dimensions (H x W x D) in	2.609 x 2.828 x 1.359 in
Cut-Out Width (In)	2 5/8
Cut-Out Height (in)	2 5/8
Cut-Out Height (mm)	66

### Material Specifications

Color	White
-------	-------

### Load Ratings

Motor Load Ratings Ranges	1 HP, 120 VAC, 50/60 Hz; 2 HP, 240 VAC, 50/60 Hz
---------------------------	--------------------------------------------------

### Electrical Specifications

Maximum Power Consumption (VA)	0.1
Wiring Option	1/4" Quick connect terminals
Switch Type	SPDT

### Display and Format

Shortest switching time	ON/OFF 15 minutes
-------------------------	-------------------

### Packaging

Shipping Weight (lbs)	0.319
Unit Carton Dimensions (H x W x L) in	2.25 x 3.25 x 3.25 in

### Environmental Specifications

Operating Humidity	0 to 95%, Non-condensing
Temperature (operation)	-4 °F to 131 °F / (-20 °C to 55 °C)
Operating Temperature with Battery Backup	-4° F to 131° F (-20° C to 55° C)

### Standards and Certifications

CSA Certification	cCSAus
Other Certifications and Compatibilities	cRUs; CE; Green Energy
California Proposition 65	None
RoHS Certification	X