

MODEL CFLEDSQ10-CC NAME DELTA SERIES 10" Square Flush Mount


Our LED flush mounts incorporate edge-lit technology, eliminating hot spots and glare. Can be installed indoors or out and icludes five switch-selectable CCT settings.



Canada 80, de la Seigneurie blvd., E. Blainville, Quebec J7C 4N1 **U.S.A.** 4383, NW 124th Ave., Coral Springs, Florida 33065 877.430.1818 info@dals.com **dals.com**


PROJECT:	TYPE:
DATE:	QTY:
NOTES:	





QUICK SPECS

SIZE	WATTS	DELIVERED LUMENS*	COLOR °T 5CCT	CRI	VOLTAGE	BEAM ANGLE	LIGHT DIRECTION	FINISH
10" *Lumen o	17W Dutput measured at	880lm t 3000K	2700K 3000K 3500K 4000K 5000K	90	120V	110°	Straight	WhiteBlackSatin nickel



CONSTRUCTION	Lens Frosted Lens material PC	Finish type Paint (BK, WH) Electroplate (SN) Housing material Cast aluminum	Type of LED Edge lit SMD Mounting Twist bracket
RATINGS	Placement Indoor/outdoor Location Wet (Covered ceiling mounted only)	Lifespan 50,000 hrs. Certifications ETL, JA8, FCC, ES	IP rating IP44 Operating temperature -20° to 40° C
ACCESSORIES -		ADAPTERS -	

WHAT'S IN THE BOX

LED flush mount fixture Mounting bracket Mounting hardware Wire nuts Instruction sheet

dals		Canada 80, de la Seigneurie blvd., E Blainville, Quebec J7C 4N1	U.S.A. 4383, NW 124 th Ave Coral Springs, Flor		877.430.1818 info@dals.com dals.com	ļ		
ELECTRICAL DETAILS	Input voltage 108-120V	Output current 135mA	Power factor 90%	Driver ty Constant	•			
	Output voltage 126V	LED model # 2835	THD harmonic distortion <30%	Binning (3 SDCM	type			
FEATURES	Integrated dimmable driver	Smooth 360° wide spread	Switch-selectable CCT: 2700K/ 3000 K/ 3500 K/ 4000 K/ 5000 K					
	Superior LED performance and lifespan	Minimal heat emission Edge-lit technology						
WARRANTY	DALS offers a 5-year warranty from the date of purchase which covers repairs or replacement of defective parts of the housing,							
	optics, and electronics. To contact DALS customer service call 1-877-430-1818 or send an e-mail to <u>info@dals.com</u> .							

RECOMMENDED DIMMER LIST*

BRAND	MODEL #	DIMMER SPECS	GRADE	DIMMING RANGE (%) MIN MAX	MAX LOAD
Dals	SM-DIMSW Smart Dimmer	Triac, 250W LED/CFL	Compatible	0 100	15
Lutron	DVELV-300P-WH	300W electronic low voltage dimmer	Compatible	0 74	18
Lutron	MA-PRO-WH	ELV, 250W LED/CFL	Compatible	0 91	15
Lutron	Caseta PD-5NE-WH-C	ELV, LED—up to 250 W	Compatible	0 97	15
Leviton	D26HD-742-1RW	Triac, 300W LED/CFL	Compatible	0 100	18
Legrand	ADTP703TUM4	Triac,450W Dimmable CFL/LED	Compatible	0 79	26
Control 4	C4-APD120-WH	ELV, 120W LED	Compatible	0 100	7

 * Minimal buzzing noise may occur with some dimmers