

PROJECT		
TYPE		
VOLTAGE		

OUTDOOR BOLLARD FIXTURE S75TC

OUTDOOR DECORATIVE MARLEX*



Wave Lighting's S75TC adds a welcoming look to any outdoor space. Wave Lighting's S75TC fits on a 3" diameter pole (sold separately) mounting hardware is included.









LED SOURCE OPTIONS

LIGHTWAVE LED - LR/LT

- 120V, 50/60 Hz
- AC Driver-On-Board Array
- Estimated 50,000 Hrs L_{70}
- Low Flicker (LT models)
- Surge Supression
- Dimmable (see compatible dimmer list)
- High Efficacy LED Light Source
- 3000K or 4000K CCT 80 or 90CRI
- 5 Year Warranty

E26 MEDIUM BASE - LE26

- 120V, 50/60Hz
- "Screw-In" Medium Base A19/E26 LED Lamp
- Estimated 15,000 Hrs L₇₀
 Low Flicker (3K models)
- Dimmable (see compatible dimmer list)
- 3000K CCT 90CRI or 4000K CCT 80CRI
- 3 Year Warranty

SPECIFICATIONS

- · Black or White
- Mounting Hardware Included
- Clear Prismatic Acrylic Diffuser
- Post Mount Only
- Minimum Starting Temp -20°F
- UL Listed for Wet Locations
- Composite Construction
- Non-Corrosive





GUIDE CODE: S75TC-BK

CALL FOR PHOTOMETRIC INFORMATION

ITEM#	DIFFUSER	LIGHT SOURCE	ССТ	COLOR
S75T ACRYLIC C-Clear Prismatic		E26 MEDIUM BASE	C -4K	BK -Black WH -White
	C -Clear Prismatic	(1) 60W MAX Medium Base LE26 -9.5W 800lm (E26 LED Lamp) +	W -3K	
		120V LIGHTWAVE LED		
		LR12 -13W 1000lm 80CRI LT12 -12W 1040lm 90CRI		

⁺ Lamp included.