

JOB NAME

CONTACT

ORDERING CODE

24VDC LED Driver



LM-79

ORDERING CODES

PART NUMBER	70478	LED Driver
VOLTAGE	24V	24V
WATTAGE	20W 60W 96W	20W 60W 96W

ORDERING CODE




Follow the steps to specify your fixture, example:
70478 - 24V - 96W






20W, 60W



96W



20W, 60W



96W

DESCRIPTION

- No minimum load requirements
- Dimming control: 120V Magnetic Low Voltage (MLV) Single Pole or 3-Way Dimmer
- Dimming range: 100-3%
- Thermal protection
- Overload protection (current limiting with Auto Reset)
- Integrated wiring compartment with 1/2" knockouts for primary & secondary circuits

PRODUCT COMPATIBILITY

- 20W Driver – maximum 4ft LEDbar
- 60W Driver – maximum 12ft LEDbar, one unit Line Linear 2 fixture
- 96W Driver – maximum 20ft LEDbar, one unit Line Linear 3 fixture, or two units Line Linear 2 fixture

TECHNICAL SPECS

20W:	60W:	96W:
- 120/277Vac, 60Hz input	- 120/277Vac, 60Hz input	- 120/277Vac, 60Hz input
- 24Vdc output, max 20VA, 0.83A	- 24Vdc output, max 60VA, 2.5A	- 24Vdc output, max 96VA, 4A
- Unit Weight: 5 lbs	- Unit Weight: 5 lbs	- Unit Weight: 7.5 lbs
- Remote Distances:	- Remote Distances:	- Remote Distances:
- 80ft using 14 AWG wire	- 30ft using 14 AWG wire	- 20ft using 14 AWG wire
- 150ft using 12 AWG wire	- 50ft using 12 AWG wire	- 30ft using 12 AWG wire

LISTINGS

- Suitable for dry location only (must be well ventilated)
- UL Listed (standard 1012), Class 2 rated (standard 1310)